

## This document was generated on 09/22/2021 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

| Part Number:                                       | <u>0451420410</u>  |   |                        |                                  |
|--|--|---|------------------------|----------------------------------|
| Status:  | Active   |   |                        |                                  |
| -  |  | ors with Precision-Machined Contacts              | ant                    | THE 12 118                       |
| =  | MultiCat-to-MultiCat High-Power Off-the-Shelf (OTS) Cable Assembly, Male, Single |   |                        |                                  |
|  |  | G, 4 Circuits, Key A, Black                       | 1                      | 1                                |
|  |  |   | 14                     | 1 10                             |
| Documents:   |  |   |                        | See 1                            |
| <u>3D Model</u>                                    |  | <u>Datasheet (PDF)</u>                            |                        |                                  |
| <u>3D Model (PDF)</u>                              |  | RoHS Certificate of Compliance (PDF)              |                        |                                  |
| <u>Drawing (PDF)</u>                               |  |   |                        | <b>D</b> ( )                     |
| 0  |  |   | Series image           | e - Reference only               |
| General<br>Product Family                          |  | Cable Assemblies                                  | EU ELV                 |                                  |
| Series   |  | 45142   | Not Relevant           |                                  |
|  |  | Power, Wire-to-Wire                               | Not Relevant           |                                  |
| Application  |  | Dual Ended Connectors                             | EU RoHS                | China RoHS                       |
| Assembly Configuration                             |  |   | Compliant with         |                                  |
| Connector to Connector                             |  | MultiCat-to-MultiCat                              | Exemption 6(c)         |                                  |
| Overmolded   |  | No  | REACH SVHC             |                                  |
| Overview   |  | MultiCat Power Connectors with Precision-Machined | Contained Per -        |                                  |
|  |  | Contacts  |                        |                                  |
| Product Name                                       |  | MultiCat  | D(2021)4569-DC (8      |                                  |
| Туре   |  | Discrete Wire Assembly, High Reliability Assembly | July 2021)             |                                  |
| UPC  |  | 191128292573                                      | Lead                   |                                  |
| Dissolution  |  |   | Halogen-Free           |                                  |
| Physical   |  |   | <u>Status</u>          |                                  |
| Cable Length                                       |  | 1.0m  | Not Low-Halogen        |                                  |
| Circuits (Loaded)                                  |  | 4   | For more information   | n, please visit <u>Contact L</u> |
| Color - Resin                                      |  | Black   |                        | <b>50</b> Jac <b>5 5</b>         |
| Gender   |  | Male-Male   | China ROHS             | 50 Image                         |
| Lock to Mating Part                                |  | Yes   | ELV                    | Not Relevant                     |
| Material - Metal                                   |  | Copper Alloy                                      | RoHS Phthalates        | Not Contained                    |
| Material - Plating Mating                          |  | Gold over Nickel Phosphorus                       |                        |                                  |
| Material - Plating Termir                          | nation   | Gold  |                        |                                  |
| Material - Resin                                   |  | PEI   | Search Parts in t      | his Series                       |
| Net Weight   |  | 445.700/g   | 45142 Series           |                                  |
| Number of Rows                                     |  | 1   |                        |                                  |
| Packaging Type                                     |  | Bag   |                        |                                  |
| Pitch - Mating Interface                           |  | 7.40mm  | Mates With             |                                  |
| Plating min - Mating                               |  | 0.100µm   |                        | ver Inline Receptacle            |
| Plating min - Termination                          | n  | 0.200µm   | Housing <u>2018410</u> | <u>040</u> , <u>2018410140</u>   |
| Single Ended                                       |  | No  |                        |                                  |
| Termination Interface: S                           | tyle   | Crimp or Compression                              |                        |                                  |
| Wire Insulation Diamete                            |  | 4.03mm-5.84mm                                     |                        |                                  |
| Wire Size AWG                                      |  | 8   |                        |                                  |
| Wire/Cable Type                                    |  | UL 10669  |                        |                                  |
| Electrical   |  |   |                        |                                  |
|  | Contact  | 40.04   |                        |                                  |
| Current - Maximum per Contact<br>Voltage - Maximum |  | 40.0A<br>1000V AC                                 |                        |                                  |
| 5  |  |   |                        |                                  |
| Material Info                                      |  |   |                        |                                  |
| Engineering Number                                 |  | KAB2549L1V01                                      |                        |                                  |
| Reference - Drawing N                              | umbers   |   |                        |                                  |
| Sales Drawing                                      |  | 451420401-000                                     |                        |                                  |

This document was generated on 09/22/2021 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for DC Power Cords category:

Click to view products by Molex manufacturer:

Other Similar products are found below :

172-4000 172-4101 172-7443-E 21033836407 2J-1865A 2R7006A20A120 426055400-3 MN47A4BC01M010 H-OU-2 CA0002 420680840-3 426451500-3 P162PT4-36 1-832692-4 FJ-VSP 3M 96CB-POWER-B-1.8M2 426040200 CA0006 H-OU-27 1700019464 FJ-VSP 10M MN47B4BC01M040 H-OU-20 2-836917-8 867566-1 804001P03M050G 2050KH1-BK 426013710-3 58257-1069 216603-0037 1011147 1011324 1012028 862545-5 BXC-10567 172-2555 32102-022800-200-RS P29000-M2 P29004-M2 DC.CAB.0201.0150 DC.CAB.0301.0150 DC.CAB.0610.0150 DC.CAB.0700.0150 DC.CAB.1000.0300 DC.CAB.1100.0150 DC.CAB.1400.0150 DC.CAB.1410.0150 DC.CAB.1500.0150 DC.CAB.1811.0150 DC.CAB.1900.0150