

This document was generated on 02/21/2018 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:	<u>0453391600</u>		
Status:	Active		570 ATD
		Svetom	C. Bassanaganagat C
		ug for Wire Termination, 16 Circuit	
Documents:			
Drawing (PDF)		Packaging Specification PK-45593-001 (PDF)	
	n PS-44828-001-001 (PDF)	RoHS Certificate of Compliance (PDF)	Photo by by by by by the
			 Interioristication
Agency Certificatio	n		
CSA		LR19980	Series image - Reference only
UL		E29179	
02		220110	EU ELV
General			Not Relevant
Product Family		I/O Connectors	
Series		<u>45339</u>	EU RoHS China RoHS
Application		Wire-to-Board	Compliant
Comments		Please reference Application Specification	REACH SVHC
		AS-44828-001 when designing	Not Contained Per
Component Type		Plug	-ED/01/2018 (15
More Detailed Tech Information		handylink@molex.com	January 2018)
Overview		HandyLink I/O Interconnect System	Halogen-Free
Product Name		HandyLink	<u>Status</u>
Туре		N/A	Not Low-Halogen
UPC		822348013159	Need more information on product
Dhysical			environmental compliance?
Physical		16	
Circuits (Loaded)		16 16	Email productcompliance@molex.com
Circuits (maximum) Circuits Detail			Please visit the <u>Contact Us</u> section for any
Color - Resin		Terminals 1 through 16 loaded Black	non-product compliance questions.
Flammability		94V-0	China ROHS Green Image
Lock to Mating Part		Yes	ELV Not Relevant
Material - Metal		High Performance Alloy (HPA), Stainless Steel	RoHS Phthalates Not Contained
Material - Plating Mating		Gold, Tin	
Material - Plating Termination		Tin	
Material - Resin		High Temperature Thermoplastic	
Net Weight		8.810/g	Search Parts in this Series
Orientation		Vertical	45339 Series
PCB Retention		N/A	
Packaging Type		Tray	Mates With
Panel Mount		No	44828
Pitch - Mating Interfa	ice	0.80mm	
Plating min - Mating		0.102µm, 1.270µm	
Plating min - Termination		1.270µm, 5.080µm	
Polarized to Mating Part		Yes	
Surface Mount Com		No	
Temperature Range		-40°C to +85°C	
Termination Interface		Solder or Weld	
Wire Size AWG		22	
			
Electrical			
Current - Maximum p	per Contact	1.5A	
Shielded		No	
Voltage - Maximum		30V	

Reference - Drawing Numbers Packaging Specification Product Specification Sales Drawing

PK-45593-001 PS-44828-001-001 SD-45339-001, SD-45339-001-002

This document was generated on 02/21/2018 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for I/O Connectors category:

Click to view products by Molex manufacturer:

Other Similar products are found below :

 571763P
 58098-0628
 72.250.1628.2
 72.250.2428.2
 74720-0505
 76.350.0729.0
 76871-1403
 FCN-244F080-G/1
 FCN-260A9920
 PCR

 E36PM
 PCS-XE26MA+
 G38A71314B
 1571250010
 157-22500-3
 MS3471L14-19P L/C
 192991-0703
 172501-4002
 172501-6002
 FCN

 260C008-A/L0
 FCN-260C024-AL0
 FCN-261Z008
 2000314-1
 200331-1
 PCR-E36FC+
 PCS-E28FS+
 PCS-XE26SLFD+
 PCS

 XE26SLFDT+
 G730VID08BDC24
 U90B2054081210
 UE86K842720321
 38113800006
 DP3AR020WQ1R200
 Z4.102.0680.0
 500-1040

 500-1052
 500-1054
 ZP-4008-66L
 0709821002
 DX40-20P(55)
 5554841-1
 MS3474W18-8P-LC*
 U90B3054061110
 U65-E04-4020

 ZPF000000000097891
 747360449
 10099439-003C-TRLF
 10137239-0021LF
 E9320-001-01
 10137239-0011LF
 70289-001LF