

Voltage - Maximum

## This document was generated on 03/27/2019 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:	0471510001			
Status:				
	Active			
Overview:	High Definition Multimedia Int		11	
Description:		cle, Right-Angle, 0.76µm Gold (Au) Plating, Front Solder	11	
		ckel (Ni) Plated, without Back Cover, Black Housing, Tape		
	and Reel Package, 19 Circuit	s, Lead-Free	N. STOP	
				Car and
Documents:			0	6
<u>3D Model</u>		Packaging Specification PK-47151-001 (PDF)		
Drawing (PDF)		RoHS Certificate of Compliance (PDF)		
Product Specification	<u>PS-47152-001 (PDF)</u>		Series image	- Reference only
General			EU ELV	
Product Family		I/O Connectors	Not Relevant	
Series		<u>47151</u>	EU RoHS	China RoHS
Application		Wire-to-Board	Compliant	
Component Type		Receptacle	REACH SVHC	
Electrical Model		Yes	Not Contained Per -	
Overview		High Definition Multimedia Interface (HDMI)* Products		
Product Name		HDMI	ED/61/2018 (27 June 2018)	5
Туре		N/A	,	
UPC		822348794379	Halogen-Free	
Dhysical			<u>Status</u>	
Physical Deat Calar		N1/A	Low-Halogen	
Boot Color		N/A	For more information	, please visit <u>Contact US</u>
Circuits (Loaded)		19 Disele	China ROHS	Green Image
Color - Resin		Black	ELV	Not Relevant
Gender		Female	RoHS Phthalates	Not Contained
Keying to Mating Part		Yes		Not Contained
Lock to Mating Part		Yes		
Material - Metal		Copper Alloy		
Material - Plating Mati		Gold	Search Parts in this Series	
Material - Plating Termination		Tin-Bismuth	47151 Series	
Net Weight		2.050/g		
Number of Rows		2 Diakt Angle	Mates With	
Orientation		Right Angle		Assembly, <u>88764</u> HDMI
PCB Locator		No	Adapter, <u>88767</u> HE	
PCB Retention		Yes		
Packaging Type		Embossed Tape on Reel		
Panel Mount		Without Flange		
Pitch - Mating Interfac		0.50mm		
Pitch - Termination Interface		0.50mm		
Plating min - Mating		0.762µm		
Plating min - Termination		1.016µm		
Polarized to Mating Part		Yes		
Polarized to PCB		Yes		
Ports				
Temperature Range - Operating		-20° to +85°C		
Termination Interface: Style		Surface Mount		
Waterproof / Dustproof		No		
Wire Size AWG		N/A		
Electrical				
	er Contact	0.5A		
Current - Maximum per Contact Shielded		Yes		
Shielded				

40V DC

Solder Pre	ocess Data
------------	------------

Duration at Max. Process Temperature (seconds)	010
Lead-freeProcess Capability	REFLOW
Process Temperature max. C	245

#### **Material Info**

#### **Reference - Drawing Numbers**

Electrical Model Document
Packaging Specification
Product Specification
S-Parameter Model
Sales Drawing

EE-47151-001, EE-47151-002 PK-47151-001 PS-47152-001 SP-47151-002 SD-47151-001

### This document was generated on 03/27/2019 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

# **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for HDMI, Displayport & DVI Connectors category:

Click to view products by Molex manufacturer:

Other Similar products are found below :

<u>1775247-3</u> 2-1932649-5 30-1231 30-528 2069485-1 30-504 30-519 30-542 47648-2000 2002-400 769-103/021-000 1932649-1 233-368NFG6-17NH PJ-210A PJ-35825 3VD51203-3D6A-7H DV11201-H5R6-4F RPI-16337 CC-MDPM-VGAM-6 RPI-16338 CCB-HDMIL-1.5M CCB-HDMIL-1M CCB-HDMIL-2M CCB-HDMIL-3M CCB-HDMIL-5M CCB-HDMIL-7.5M CCBP-HDMI-10M CCBP-HDMI-1M CCBP-HDMI-2M CCBP-HDMI-3M CCBP-HDMI-7.5M CCBP-HDMI8K-1M CCBP-HDMI8K-2M CCBP-HDMI8K-3M AK-AV-02 AK-AV-03 AK-AV-05 AK-AV-11 AK-AV-13 AK-AV-15 CCP-MDP2-6 CCP-MDPMDP2-6 AK-HD-05A AK-HD-100A AK-HD-100P AK-HD-15A AK-HD-15P AK-HD-30A AK-HD-30P 49959