

Voltage - Maximum

This document was generated on 03/28/2019 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:	0474544004		· · · · · · · · · · · · · · · · · · ·	
	<u>0471511001</u>			
Status:	Active		-	
Overview:	High Definition Multimedia Ir	nterface (HDMI)* Products	11	
Description:	0.50mm Pitch HDMI Recept	acle, Right-Angle, Front Solder Tab Length 1.80mm,	Cil V	
-	Shell Nickel (Ni) Plated, with	Back Cover, Black Housing, Tape and Reel Package, 19	1.	SI CIN AND
	Circuits, Lead-Free		A. Carton	
				A STREET
Documents:			0	
3D Model		Packaging Specification PK-47151-001 (PDF)		
Drawing (PDF)		RoHS Certificate of Compliance (PDF)		
Product Specification PS-47152-001 (PDF)		Series image - Reference only		e - Reference only
· ·				
General			EU ELV	
Product Family		I/O Connectors	Not Relevant	
Series		<u>47151</u>		
Application		Wire-to-Board	EU RoHS	China RoHS
Component Type		Receptacle	Compliant	
Electrical Model		Yes	REACH SVHC	
Overview		High Definition Multimedia Interface (HDMI)* Products	Not Contained Per	
Product Name		HĎMI	-ED/88/2018 (15	
Туре		N/A	January 2019)	
UPC		822348824281	Halogen-Free	
			<u>Status</u>	
Physical			Low-Halogen	
Boot Color		N/A	For more information	n, please visit <u>Contact US</u>
Circuits (Loaded)		19		-
Color - Resin		Black	China ROHS	Green Image
Gender		Female	ELV	Not Relevant
Keying to Mating Part		Yes	RoHS Phthalates	Not Contained
Lock to Mating Part		Yes	,	
Material - Metal		Copper Alloy		1
Material - Plating Mating		Gold	Search Parts in this Series	
Material - Plating Termination		Tin-Bismuth	47151 Series	
Net Weight		2.197/g	4/101 Selles	
Number of Rows		2		
Orientation		 Right Angle	Mates With	
PCB Locator		No		e Assembly, <u>88764</u> HDMI
PCB Retention		Yes	Adapter, <u>88767</u> H	DMI Adapter
Packaging Type		Embossed Tape on Reel		
Panel Mount		Without Flange		
Pitch - Mating Interface		0.50mm		
Pitch - Termination Interface		0.50mm		
Plating min - Mating		0.762µm		
Plating min - Termination		1.016µm		
Polarized to Mating Part		Yes		
Polarized to PCB		Yes		
Ports		1		
Temperature Range - Operating		-20° to +85°C		
Termination Interface: Style		Surface Mount		
Waterproof / Dustproof		No		
Wire Size AWG		N/A		
Electrical				
Current - Maximum p	er Contact	0.5A		
Shielded		Yes		
Valtaga Maximum				

40V DC

Solder Process Data	
Duration at Max. Process Temperature (seconds)	010
Lead-freeProcess Capability	REFLOW
Max. Cycles at Max. Process Temperature	002
Process Temperature max. C	250

Material Info

Reference - Drawing Numbers	
Electrical Model Document	EE-47151-001, EE-47151-002
Packaging Specification	PK-47151-001
Product Specification	PS-47152-001
S-Parameter Model	SP-47151-002
Sales Drawing	SD-47151-001

This document was generated on 03/28/2019 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for HDMI, Displayport & DVI Connectors category:

Click to view products by Molex manufacturer:

Other Similar products are found below :

<u>1775247-3</u> <u>2-1932649-5</u> <u>30-1231</u> <u>30-528</u> <u>2069485-1</u> <u>30-504</u> <u>30-519</u> <u>30-542</u> <u>47648-2000</u> <u>2002-400</u> <u>TC142X</u> <u>769-103/021-000</u> <u>1932649-1</u> <u>233-368NFG6-17NH</u> <u>PJ-210A</u> <u>PJ-35825</u> <u>6321-026RDS1MWA02</u> <u>DV11201-H5R6-4F</u> <u>RPI-16337</u> <u>CC-MDPM-VGAM-6</u> <u>RPI-16338</u> <u>CCB-HDMIL-1.5M</u> <u>CCB-HDMIL-1M</u> <u>CCB-HDMIL-2M</u> <u>CCB-HDMIL-3M</u> <u>CCB-HDMIL-5M</u> <u>CCB-HDMIL-7.5M</u> <u>CCBP-HDMI-10M</u> <u>CCBP-HDMI-10M</u> <u>CCBP-HDMI-1M</u> <u>CCBP-HDMI-2M</u> <u>CCBP-HDMI-5M</u> <u>CCBP-HDMI-7.5M</u> <u>CCBP-HDMI8K-1M</u> <u>CCBP-HDMI8K-2M</u> <u>CCBP-HDMI8K-2M</u> <u>CCBP-HDMI8K-2M</u> <u>CCBP-HDMI8K-3M</u> <u>AK-AV-02</u> <u>AK-AV-03</u> <u>AK-AV-05</u> <u>AK-AV-11</u> <u>AK-AV-13</u> <u>AK-AV-15</u> <u>CCP-MDP2-6</u> <u>CCP-MDPMDP2-6</u> <u>AK-HD-05A</u> <u>AK-HD-100A</u> <u>AK-HD-15P</u> <u>AK-HD-15P</u> <u>AK-HD-15P</u> <u>AK-HD-15R</u>