

This document was generated on 03/29/2019 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Dont Numbers				
Part Number:	<u>0471511002</u>			
Status: Active				
Overview:	High Definition Multimedia In	terface (HDMI)* Products	11	
Description:		cle, Right-Angle with Screw Flange, Front Solder Tab	C11 10	
Length 1.80mm, Shell Nickel (Ni) Plated, with Back Cover, Black Housing, Tray			1.	ter in
	Package, 19 Circuits, Lead-F		L CONTRACTOR	
			Children and	A STORE
Documents:				
3D Model		Packaging Specification PK-47151-002 (PDF)		
Drawing (PDF)		RoHS Certificate of Compliance (PDF)		
Product Specification PS-47152-001 (PDF)			Series image -	Reference only
			Oches inage	
General			EU EL V	
Product Family		I/O Connectors	EU ELV Not Relevant	
Series		47151	Not Relevant	
		Wire-to-Board	EU RoHS	China RoHS
Application Component Type		Receptacle	Compliant	
Electrical Model		Yes	REACH SVHC	
Overview		High Definition Multimedia Interface (HDMI)* Products	Not Contained Per	
Product Name		High Deminitor Multimedia Interface (HDMI) Products	-ED/88/2018 (15	
		N/A	January 2019)	
UPC		822350117463	Halogen-Free	
		022000117400	Status	
Physical			Low-Halogen	
Boot Color		N/A		please visit <u>Contact US</u>
Circuits (Loaded)		19		
Color - Resin		Black	China ROHS	Green Image
Flammability		94V-0		Not Relevant
Gender		Female	RoHS Phthalates	Not Contained
Keying to Mating Part		Yes	,	
Lock to Mating Part		Yes		
Material - Metal		Copper Alloy	Search Parts in this Series	
Material - Plating Mating		Gold	47151 Series	
Material - Plating Termination		Tin-Bismuth	<u>47131</u> Selles	
Net Weight		2.539/g		
Number of Rows		2	Mates With	
Orientation		Right Angle	88768 HDMI Cable Assembly, 88764 HDMI	
PCB Locator		No	Adapter, <u>88767</u> HDN	/II Adapter
PCB Retention		Yes		
Packaging Type		Tray		
Panel Mount		With Flange		
Pitch - Mating Interface		0.50mm		
Pitch - Termination Interface		0.50mm		
Plating min - Mating		0.762µm		
Plating min - Termination		1.016µm		
Polarized to Mating Part		Yes		
Polarized to PCB		Yes		
Ports		1		
Temperature Range - Operating		-20° to +85°C		
Termination Interface: Style		Surface Mount		
Waterproof / Dustproof		No		
Wire Size AWG		N/A		
Electrical				
Current - Maximum p	er Contact	0.5A		
Shielded		Yes		
Voltage - Maximum		40V DC		

Solder Process Data	
Duration at Max. Process Temperature (seconds)	003
Lead-freeProcess Capability	REFLOW
Max. Cycles at Max. Process Temperature	002
Process Temperature max. C	250

Material Info

Reference - Drawing NumbersElectrical Model DocumentEE-47151-001, EE-47151-002Packaging SpecificationPK-47151-002Product SpecificationPS-47152-001S-Parameter ModelSP-47151-002

This document was generated on 03/29/2019 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for HDMI, Displayport & DVI Connectors category:

Click to view products by Molex manufacturer:

Other Similar products are found below :

<u>1775247-3</u> <u>2-1932649-5</u> <u>30-1231</u> <u>30-528</u> <u>2069485-1</u> <u>30-504</u> <u>30-519</u> <u>30-542</u> <u>47648-2000</u> <u>2002-400</u> <u>TC142X</u> <u>769-103/021-000</u> <u>1932649-1</u> <u>233-368NFG6-17NH</u> <u>PJ-210A</u> <u>PJ-35825</u> <u>6321-026RDS1MWA02</u> <u>DV11201-H5R6-4F</u> <u>RPI-16337</u> <u>CC-MDPM-VGAM-6</u> <u>RPI-16338</u> <u>CCB-HDMIL-1.5M</u> <u>CCB-HDMIL-1M</u> <u>CCB-HDMIL-2M</u> <u>CCB-HDMIL-3M</u> <u>CCB-HDMIL-5M</u> <u>CCB-HDMIL-7.5M</u> <u>CCBP-HDMI-10M</u> <u>CCBP-HDMI-10M</u> <u>CCBP-HDMI-1M</u> <u>CCBP-HDMI-2M</u> <u>CCBP-HDMI-5M</u> <u>CCBP-HDMI-7.5M</u> <u>CCBP-HDMI8K-1M</u> <u>CCBP-HDMI8K-2M</u> <u>CCBP-HDMI8K-2M</u> <u>CCBP-HDMI8K-2M</u> <u>CCBP-HDMI8K-3M</u> <u>AK-AV-02</u> <u>AK-AV-03</u> <u>AK-AV-05</u> <u>AK-AV-11</u> <u>AK-AV-13</u> <u>AK-AV-15</u> <u>CCP-MDP2-6</u> <u>CCP-MDPMDP2-6</u> <u>AK-HD-05A</u> <u>AK-HD-100A</u> <u>AK-HD-15P</u> <u>AK-HD-15P</u> <u>AK-HD-15P</u> <u>AK-HD-15R</u>