

Voltage - Maximum

This document was generated on 03/27/2019 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:	0471511102			
Status:				
	Active			
Overview:		Interface (HDMI)* Products	11	
Description:		ptacle, Right-Angle with Screw Flange, Front Solder Tab	(1)	
	Length 1.45mm, Shell Nic	kel (Ni) Plated, with Back Cover, Tray Package, Lead-Free		N math
			N. STOP	
Documents:				
<u>3D Model</u>		Packaging Specification PK-47151-003 (PDF)	v	U
Drawing (PDF)		RoHS Certificate of Compliance (PDF)		
Product Specification	PS-47152-001 (PDF)			
			- Series image - Reference only	
General				
Product Family		I/O Connectors	EU ELV	
Series		47151	Not Relevant	
Application		Wire-to-Board		
Component Type		Receptacle	EU RoHS	China RoHS
Electrical Model		Yes	Compliant	
Overview		High Definition Multimedia Interface (HDMI)* Products	REACH SVHC	
Product Name		HDMI	Not Contained Per	
Туре		N/A	-ED/88/2018 (15	
UPC		822350117517	January 2019)	
			Halogen-Free	
Physical			<u>Status</u>	
Boot Color		N/A	Low-Halogen	
Circuits (Loaded)		19	For more information	n, please visit <u>Contact US</u>
Color - Resin		Black		a .
Flammability		94V-0	China ROHS	Green Image
Gender		Female	ELV	Not Relevant
Keying to Mating Part		Yes	RoHS Phthalates	Not Contained
Lock to Mating Part		Yes		
Material - Metal		Copper Alloy		
Material - Plating Mat		Gold	Search Parts in t	his Series
Material - Plating Ter	mination	Tin-Bismuth	47151 Series	
Net Weight		2.539/g		
Number of Rows		2	Mates With	
Orientation		Right Angle		e Assembly, <u>88764</u> HDMI
PCB Locator		No	Adapter, <u>88767</u> H	
PCB Retention		Yes		
Packaging Type		Tray With Floore		
Panel Mount		With Flange		
Pitch - Mating Interface Pitch - Termination Interface		0.50mm		
	nenace	0.50mm		
Plating min - Mating	tion	0.762µm		
Plating min - Termination		1.016µm Xos		
Polarized to Mating Part Polarized to PCB		Yes Yes		
		1 5		
Ports	Operating	l -20° to +85°C		
Temperature Range - Operating Termination Interface: Style				
		Surface Mount		
Waterproof / Dustproof Wire Size AWG		No N/A		
VVIIE SIZE AVVG		IN/ <i>F</i> A		
Electrical				
Current - Maximum p	er Contact	0.5A		
Shielded		Yes		

40V DC

Solder Pre	ocess Data
------------	------------

Duration at Max. Process Temperature (seconds)	010
Lead-freeProcess Capability	REFLOW
Process Temperature max. C	245

Material Info

Reference - Drawing Numbers

Electrical Model Document	
Packaging Specification	
Product Specification	
S-Parameter Model	

EE-47151-001, EE-47151-002 PK-47151-003 PS-47152-001 SP-47151-002

This document was generated on 03/27/2019 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for HDMI, Displayport & DVI Connectors category:

Click to view products by Molex manufacturer:

Other Similar products are found below :

<u>1775247-3</u> <u>2-1932649-5</u> <u>30-1231</u> <u>30-528</u> <u>2069485-1</u> <u>30-504</u> <u>30-519</u> <u>30-542</u> <u>47648-2000</u> <u>2002-400</u> <u>769-103/021-000</u> <u>1932649-1</u> <u>233-</u> <u>368NFG6-17NH</u> <u>PJ-210A</u> <u>PJ-35825</u> <u>6321-026RDS1MWA02</u> <u>FDB0901-M0DB300K6KF</u> <u>3VD51203-3D6A-7H</u> <u>DV11201-H5R6-4F</u> <u>RPI-</u> <u>16337</u> <u>CC-MDPM-VGAM-6</u> <u>RPI-16338</u> <u>CCB-HDMIL-1.5M</u> <u>CCB-HDMIL-1M</u> <u>CCB-HDMIL-2M</u> <u>CCB-HDMIL-3M</u> <u>CCB-HDMIL-5M</u> <u>CCB-HDMIL-5M</u> <u>CCB-HDMIL-1M</u> <u>CCBP-HDMI-3M</u> <u>CCBP-HDMI-5M</u> <u>CCB-HDMIL-5M</u> <u>CCBP-HDMI-10M</u> <u>CCBP-HDMI-1M</u> <u>CCBP-HDMI-2M</u> <u>CCBP-HDMI-5M</u> <u>CCBP-HDMI-7.5M</u> <u>CCBP-HDMI-7.5M</u> <u>CCBP-HDMI8K-1M</u> <u>CCBP-HDMI8K-2M</u> <u>CCBP-HDMI8K-3M</u> <u>AK-AV-02</u> <u>AK-AV-03</u> <u>AK-AV-05</u> <u>AK-AV-11</u> <u>AK-AV-13</u> <u>AK-AV-15</u> <u>CCP-MDP2-6</u> <u>CCP-MDP2-6</u> <u>AK-HD-05A</u> <u>AK-HD-100A</u> <u>AK-HD-15A</u> <u>AK-HD-15P</u>