

## This document was generated on 08/25/2021 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

		WWW.MOLEA.COM FOR LATEST PART	
Part Number:	0472720024		
Status:	Active		
Overview:	DisplayPort and Mini Display		
Description:		eceptacle, Right-Angle, Surface Mount, 0.76µm Gold (Au)	111 -
	-	er, Latch Holes, Mylar, Peg, Solder Tab of Shell, without	and 11 h
	Flange, Lead-Free		1 1/ C
Documents:			
3D Model		Product Specification PS-47272-001-001 (PDF)	
Drawing (PDF)		Packaging Specification PK-47272-001-001 (PDF)	
<u>3D Model (PDF)</u>		RoHS Certificate of Compliance (PDF)	Series image - Reference only
Agency Certification			EU ELV
UL		E29179	Not Relevant
General			EU RoHS China RoHS
Product Family		I/O Connectors	Compliant
Series		47272	REACH SVHC
Application		Wire-to-Board	Not Contained Per -
Comments		Through Hole Peg of Shell	D(2021)4569-DC (8
Component Type		Receptacle	July 2021)
Overview		DisplayPort and Mini DisplayPort Interconnect System	Halogen-Free
Product Name		DisplayPort	<u>Status</u>
Type		N/A	Low-Halogen
UPC		883906043834	
UFG		883900043834	For more information, please visit Contact US
Physical			China ROHS Green Image
Circuits (Loaded)		20	ELV Not Relevant
Circuits (maximum)		20	RoHS Phthalates Not Contained
Color - Resin		Black	,
Flammability		94V-0	
Gender		Female	Search Parts in this Series
Keying to Mating Part		Yes	47272 Series
Lock to Mating Part		Yes	<u>47272</u> Series
Material - Metal		Copper Alloy	
Material - Plating Mati	ng	Gold	Mates With
Material - Plating Tern	nination	Matte Tin	47271 Plug Sub-Assemblies, 68783 Cable
Material - Resin		High Temperature Thermoplastic	Series
Net Weight		3.500/g	
Number of Rows		2	
Orientation		Right Angle	
PCB Locator		Yes	
PCB Retention		Yes	
Packaging Type		Embossed Tape on Reel	
Panel Mount		Without Flange	
Pitch - Mating Interfac	e	0.50mm	
Pitch - Termination Int		0.50mm	
Plating min - Mating		0.762µm	
Plating min - Terminat	ion	1.016µm	
Polarized to Mating Pa		Yes	
Polarized to PCB		Yes	
Ports		1	
Temperature Range -	Operating	-20° to +85°C	
Termination Interface:		Surface Mount	
Waterproof / Dustproo			
	1	No	

Current - Maximum per Contact	0.5A
Grounding to Panel	Yes
Shielded	Yes
Voltage - Maximum	40V AC
<b>Solder Process Data</b> Duration at Max. Process Temperature (seconds) Lead-freeProcess Capability Max. Cycles at Max. Process Temperature Process Temperature max. C	003 REFLOW 002 250

### **Material Info**

Reference - Drawing Numbers Electrical Model Document Packaging Specification Product Specification Sales Drawing

EE-47272-001-001, EE-47272-002-001 PK-47272-001-001 PS-47272-001-001 SD-47272-001-001

### This document was generated on 08/25/2021 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

# **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for HDMI, Displayport & DVI Connectors category:

Click to view products by Molex manufacturer:

Other Similar products are found below :

<u>1775247-3</u> <u>2-1932649-5</u> <u>30-1231</u> <u>30-528</u> <u>2069485-1</u> <u>30-504</u> <u>30-519</u> <u>30-542</u> <u>47648-2000</u> <u>2002-400</u> <u>769-103/021-000</u> <u>1932649-1</u> <u>233-</u> <u>368NFG6-17NH</u> <u>PJ-210A</u> <u>PJ-35825</u> <u>6321-026RDS1MWA02</u> <u>FDB0901-M0DB300K6KF</u> <u>3VD51203-3D6A-7H</u> <u>DV11201-H5R6-4F</u> <u>RPI-</u> <u>16337</u> <u>CC-MDPM-VGAM-6</u> <u>RPI-16338</u> <u>CCB-HDMIL-1.5M</u> <u>CCB-HDMIL-1M</u> <u>CCB-HDMIL-2M</u> <u>CCB-HDMIL-3M</u> <u>CCB-HDMIL-5M</u> <u>CCB-HDMIL-5M</u> <u>CCB-HDMIL-1M</u> <u>CCBP-HDMI-3M</u> <u>CCBP-HDMI-3M</u> <u>CCBP-HDMI-5M</u> <u>CCBP-HDMI-7.5M</u> <u>CCBP-HDMI-10M</u> <u>CCBP-HDMI-1M</u> <u>CCBP-HDMI-2M</u> <u>CCBP-HDMI-5M</u> <u>CCBP-HDMI-7.5M</u> <u>CCBP-HDMI8K-1M</u> <u>CCBP-HDMI8K-2M</u> <u>CCBP-HDMI8K-3M</u> <u>AK-AV-02</u> <u>AK-AV-03</u> <u>AK-AV-05</u> <u>AK-AV-11</u> <u>AK-AV-13</u> <u>AK-AV-15</u> <u>CCP-MDP2-6</u> <u>CCP-MDP2-6</u> <u>AK-HD-05A</u> <u>AK-HD-100A</u> <u>AK-HD-15A</u> <u>AK-HD-15P</u>