

This document was generated on 12/20/2021 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:	5008110010			
Status: Active				
		strict Connector System		
Overview: Mini-HMC Rectangular Indust				0
Description: Mini-HMC Rectangular Industrial Wire-to-Wire Cover, 40 Circuits, for Plug				YG)
				4 30
Documents:				6.0
<u>3D Model (PDF)</u>		Packaging Specification PK-500811-001-001 (PDF)		malae
<u>3D Model</u>		Packaging Specification PK-500811-001-002 (PDF)		
Drawing (PDF)		Packaging Specification PK-500811-001-003 (PDF)		
Product Specification PS-500810-001-001 (PDF)		RoHS Certificate of Compliance (PDF)		
Application Specification AS-500811-001-001 (PDF)			Series image - Reference only	
, 				
General			EU ELV	
Product Family		I/O Connectors	Not Relevant	
Series		500811		
Application		Panel-Mount, Wire-to-Wire	EU RoHS	China RoHS
Component Type		Plug Shell Cover	Compliant with	
Overview		Mini-HMC Rectangular Industrial Connector System	Exemption 6(a)-	
Product Name		Mini-HMC Rectangular Industrial Connector System	I,6(b)-II	
			REACH SVHC	
Туре		N/A	Contained Per -	
UPC		756054862612	D(2021)4569-DC (8	
Physical				
Physical		10	July 2021)	
Circuits (Loaded)		40	Lead	
Circuits (maximum)		40	Halogen-Free	
Durability (mating cycles max)		50	<u>Status</u>	
Gender		Plug	Not Low-Halogen	
Keying to Mating Part		Yes	For more information, p	please visit <u>Contact US</u>
Lock to Mating Part		Yes		
Material - Metal		Aluminum, Stainless Steel, Steel		50 Image
Material - Plating Mating		N/A		Not Relevant
Material - Resin		Polyester	RoHS Phthalates	Not Contained
Net Weight		140.200/g	,	
Orientation		Vertical		
PCB Locator		No		
Packaging Type		Tray	Search Parts in this	s Series
Panel Mount		Screws	<u>500811</u> Series	
Pitch - Mating Interface		N/A		
Polarized to Mating Part		Yes	Mates With	
Polarized to PCB			MiniHMC Shielded P	anelMount I/O
		No		08090000, 5008090010
Surface Mount Compatible (SMC)		N/A		<u>, 200000010</u>
Temperature Rang		-40° to +105°C		
Termination Interface: Style		N/A	Use With	
Waterproof / Dustp	roof	No		008100000 Plug Shell,
Electrical			5008100010 Plug Sh	nell
Electrical	non Contoct			
Current - Maximum per Contact		1.5A, 2.5A		
Shield Type		Full Shield		
Shielded		Yes		
Voltage - Maximum	1	250V AC (RMS)/DC		
Material Info				
Reference - Drawi	ng Numbers			
Application Specification		AS-500811-001-001		
Packaging Specification		PK-500811-001-001, PK-500811-001-002,		
		DK 500911 001 002		

Product Specification

PK-500811-001-001, PK-500811-001-002, PK-500811-001-003 PS-500810-001-001 This document was generated on 12/20/2021 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for I/O Connectors category:

Click to view products by Molex manufacturer:

Other Similar products are found below :

 571763P
 58098-0628
 72.250.1628.2
 72.250.2428.2
 74720-0505
 76.350.0729.0
 76871-1403
 FCN-244F080-G/1
 FCN-260A9920
 PCR

 E36PM
 PCS-XE26MA+
 G38A71314B
 1571250010
 157-22500-3
 MS3471L14-19P L/C
 192991-0703
 172501-4002
 172501-6002
 FCN

 260C008-A/L0
 FCN-260C024-AL0
 FCN-261Z008
 2000314-1
 200331-1
 PCR-E36FC+
 PCS-E28FS+
 PCS-XE26SLFD+
 PCS

 XE26SLFDT+
 G730VID08BDC24
 U90B2054081210
 38113800006
 DP3AR020WQ1R200
 Z4.102.0680.0
 500-1040
 500-1052
 500-1054

 ZP-4008-66L
 0709821002
 DX40-20P(55)
 5554841-1
 MS3474W18-8P-LC*
 U90B3054061110
 U65-E04-4020
 ZPF000000000097891

 747360449
 10099439-003C-TRLF
 10137239-001LF
 F0320-001-01
 10137239-001LF
 70289-001LF
 70.060.1028.0