

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: **5055721000**
Status: **Active**
Overview: Micro-Lock Plus Wire-to-Board Connector System
Description: 2.00mm Pitch, Micro-Lock Plus Female Crimp Terminal, Tin (Sn) Plating, 22-26 AWG, Reel

Documents:

3D Model	Product Specification 5055701001-PS-000 (PDF)
Drawing (PDF)	Application Specification 5055700001-A03 (PDF)
3D Model (PDF)	Packaging Specification 5055729200-200 (PDF)
Product Specification 5055700001-PS-000 (PDF)	RoHS Certificate of Compliance (PDF)



General

Product Family	Crimp Terminals
Series	505572
Application	Signal, Wire-to-Board
Crimp Quality Equipment	Yes
Overview	Micro-Lock Plus Wire-to-Board Connector System
Product Name	Micro-Lock Plus
UPC	889056572521

Physical

Durability (mating cycles max)	30
Gender	Female
Material - Metal	Copper Alloy
Material - Plating Mating	Tin
Material - Plating Termination	Tin
Net Weight	41.650/mg
Packaging Type	Reel
Termination Interface: Style	Crimp or Compression
Wire Insulation Diameter	0.90-1.50mm
Wire Size AWG	22, 24, 26
Wire Size mm ²	AVSS 0.3, CAVUS 0.30, CIVUS 0.22

Electrical

Current - Maximum per Contact	3.0A
Voltage - Maximum	250V AC (RMS)/DC

Material Info

Reference - Drawing Numbers

Application Specification	5055700001-A03
Application Tooling Documents	5781523700ATS-000
Crimp Specification	5055721000-C00
Packaging Specification	5055729200-200
Product Specification	5055700001-PS-000, 5055701001-PS-000
Sales Drawing	5055721000-000

EU ELV

Not Relevant

EU RoHS

Compliant

REACH SVHC

Not Contained Per -
D(2021)4569-DC (8
July 2021)

Halogen-Free

Status

Low-Halogen

For more information, please visit [Contact US](#)

China ROHS

ELV

RoHS Phthalates

China RoHS

Green Image

Not Relevant

Not Contained

Search Parts in this Series

505572 Series

Use With

Micro-Lock Plus Receptacle Housing
505570

Application Tooling | FAQ

Tooling specifications and manuals are found by selecting the products below. Crimp Height Specifications are then contained in the Application Tooling Specification document.

Global

Description

Product #

Hand Crimp Tool for Micro-Lock Plus 2.00mm Pitch Wire-to-Board Receptacle Terminals, 22-26 AWG, 0.30mm ² AVSS wires	2002180800
Hand Crimp Tool for Micro-Lock Plus Receptacle	2002184500

Crimp Terminals,
0.22mm² CIVUS,
0.30mm² CAVUS,
and 0.30mm² AVSS
wires

FA2 Mechanical 2130690100
Feed Crimp

Applicator for Micro-
Lock Plus Terminals,
22-26 AWG, UL1061
and 0.30mm² AVSS

Wire

FA2 Pneumatic Feed 2130690110

Crimp Applicator
for Micro-Lock Plus
Crimp Terminals,
22-26 AWG, UL1061
and 0.30mm² AVSS

Wire

Japan

Description	Product #
--------------------	------------------

S-1 Applicator for Micro-Lock Plus Receptacle Terminal, 22-26 AWG	<u>5781523700</u>
--	-------------------

This document was generated on 09/02/2021

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Headers & Wire Housings](#) category:

Click to view products by [Molex](#) manufacturer:

Other Similar products are found below :

[892-18-020-10-001101](#) [58102-G61-06LF](#) [582553-1](#) [0009485154](#) [009176003701906](#) [0050291907](#) [LY20-4P-DT1-P1E-BR](#) [02.125.8002.8](#)
[609-3404](#) [61062-3](#) [61082-181009](#) [622-3653LF](#) [63453-116](#) [636-1030](#) [636-1427](#) [636-3427](#) [636-4007](#) [641938-9](#) [641991-4](#) [644827-2](#) [65817-](#)
[010LF](#) [65817-015LF](#) [65863-015LF](#) [66207-023LF](#) [67095-007LF](#) [67601157](#) [68648-049](#) [70.362.1628.0](#) [70-4210](#) [70-4226B](#) [70-4853B](#) [707-](#)
[5020](#) [707-5028](#) [71.350.2428.0](#) [71918-208LF](#) [71961-016LF](#) [733-134](#) [733-162](#) [754199-000](#) [760-3052](#) [787-8014-00](#) [79531-3000](#) [FCN-](#)
[360C032-B](#) [FCN-367T-T012/H](#) [FCN-723D010/2](#) [80.063.4001.1](#) [800-90-001-10-001000](#) [800-90-010-10-002000](#) [801-43-002-10-013000](#)
[801-43-006-10-002000](#)