

Voltage - Maximum

## This document was generated on 08/30/2021 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Status:IOverview:IDescription:I	D512335011 Active CRC (Compact Roboti CRC Shielded Rectand Circuits, Polarization T	gular I/O Receptacle Housing for Male Terminal, Signal, 50	
Documents: <u>3D Model</u> <u>3D Model (PDF)</u> Drawing (PDF) Product Specification PS	-51238-016-001 (PDI	Product Specification PS-51238-017-001 (PDF) Application Specification AS-51238-017-001 (PDF) RoHS Certificate of Compliance (PDF) E)	Series image - Reference only
Agency Certification		1 540000	EU ELV Not Relevant
CSA		LR19980	
UL		E29179	EU RoHS China RoHS
General			Compliant
Product Family		I/O Connectors	REACH SVHC
Series		51233	Not Contained Per -
			D(2021)4569-DC (8
Application		Panel-Mount, Wire-to-Wire	July 2021)
Component Type		Housing	Halogen-Free
Overview		CRC (Compact Robotic Connectors)	Status
Product Name		CRC	
Туре		N/A	Not Low-Halogen
UPC		756054154656	For more information, please visit Contact I
Physical			China ROHS Green Image
Circuits (Loaded)		50	ELV Not Relevant
Circuits (maximum)		50	RoHS Phthalates Not Contained
Color - Resin		Gray	Not Contained
	may	100	
Durability (mating cycles	max)	94V-0	
Flammability			Search Parts in this Series
Gender Kaving to Mating Dart		Receptacle	<u>51233</u> Series
Keying to Mating Part		Yes	
Lock to Mating Part		Yes	Mates With
Material - Metal Material - Plating Mating		Stainless Steel	CRC Shielded Rectangular I/O Plug Hou
		N/A	51239 , 54332
Material - Resin		Polyester	<u>51255</u> , <u>54552</u>
Net Weight		9770.000/mg	
Number of Rows		10	Use With
Orientation		Vertical	CRC Shielded Rectangular I/O Male
PCB Locator		No	Terminal <u>56116</u> , <u>56117</u> , <u>56118</u> , <u>56119</u>
Packaging Type		Tray	<u>56377</u>
Panel Mount		Front, Rear	
Pitch - Mating Interface		3.00mm	
Pitch - Termination Interf		3.00mm	
Polarized to Mating Part		Yes	
Polarized to PCB		N/A	
Surface Mount Compatib		No	
Temperature Range - Op		-40° to +105°C	
Termination Interface: St	yle	N/A	
Waterproof / Dustproof		No	
Electrical			
Current - Maximum per C	Contact	7.0A	
Shielded		No	
Voltago Movimum			

250V AC (RMS)/DC

## **Material Info**

**Reference - Drawing Numbers** Application Specification Product Specification Sales Drawing

AS-51238-017-001 PS-51238-016-001, PS-51238-017-001 SD-51233-013-001, SD-51233-013-002, SD-51233-013-003, SD-51233-013-004

This document was generated on 08/30/2021 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for I/O Connectors category:

Click to view products by Molex manufacturer:

Other Similar products are found below :

 571763P
 58098-0628
 72.250.1628.2
 72.250.2428.2
 74720-0505
 76.350.0729.0
 76871-1403
 FCN-244F080-G/1
 FCN-260A9920
 PCR 

 E36PM
 PCS-XE26MA+
 G38A71314B
 1571250010
 157-22500-3
 MS3471L14-19P L/C
 192991-0703
 172501-4002
 172501-6002
 FCN 

 260C008-A/L0
 FCN-260C024-AL0
 FCN-261Z008
 2000314-1
 200331-1
 PCR-E36FC+
 PCS-E28FS+
 PCS-XE26SLFD+
 PCS 

 XE26SLFDT+
 G730VID08BDC24
 U90B2054081210
 UE86K842720321
 38113800006
 DP3AR020WQ1R200
 Z4.102.0680.0
 500-1040

 500-1052
 500-1054
 ZP-4008-66L
 0709821002
 DX40-20P(55)
 5554841-1
 MS3474W18-8P-LC\*
 U90B3054061110
 U65-E04-4020

 ZPF000000000097891
 747360449
 10099439-003C-TRLF
 10137239-0021LF
 E9320-001-01
 10137239-0011LF
 70289-001LF