

## This document was generated on 02/01/2022 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: Status:	<u>0512383011</u> Active			
Overview: Description:	<u>CRC (Compact Robotic Connectors)</u> CRC Shielded Rectangular I/O Receptacle Housing for Female Terminal, Signal, 30 Circuits, Polarization Type Standard			2
Documents: <u>3D Model</u> <u>Drawing (PDF)</u>		Product Specification PS-51238-018-001 (PDF) Application Specification AS-51238-011-001 (PDF)		
<u>3D Model (PDF)</u> Product Specification PS-51238-010-001 (PDF)		<u>RoHS Certificate of Compliance (PDF)</u> <u>DF)</u>	Series image - Reference only	
Agency Certification			EU ELV	
CSA	•	LR19980	Not Relevant	
UL		E29179		
0L		223113	EU RoHS	China RoHS
General			Compliant	
Product Family		I/O Connectors	REACH SVHC	
Series		<u>51238</u>	Not Contained Pe	
Application		Panel-Mount, Wire-to-Wire	D(2021)4569-DC	(8
Component Type		Housing	July 2021)	
Overview		CRC (Compact Robotic Connectors)	Halogen-Free	
Product Name		CRC	Status	
Туре		N/A	Not Low-Haloger	1
UPC		800756205779	For more informat	ion, please visit <u>Cont</u> a
Physical			China ROHS	Green Image
Circuits (Loaded)		30	ELV	Not Relevant
Circuits (maximum)		30	RoHS Phthalates	Not Contained
Color - Resin		Black	,	
Durability (mating cyc	les max)	100		
Flammability		94V-0	Convola Doute in	this Carico
Gender		Receptacle	Search Parts in this Series	
Keying to Mating Part		Yes	51238 Series	
Lock to Mating Part		Yes		
Material - Metal		Stainless Steel	Mates With	
Material - Plating Mating		N/A	CRC Shielded Rectangular I/O Plug	
Material - Resin	5	Polyester	<u>51234</u> , <u>55836</u>	
Net Weight		5573.200/mg		
Number of Rows		6	Use With	
Orientation		Vertical	CRC Shielded Rectangular I/O Rece	
PCB Locator		No	Shell <u>56377</u> , <u>56</u>	
Packaging Type		Tray	1	
Panel Mount		Front, Rear		
Pitch - Mating Interfac	ce	3.00mm		
Pitch - Termination In		3.00mm		
Polarized to Mating Part		Yes		
Polarized to PCB		N/A		
Surface Mount Comp	atible (SMC)	N/A		
Temperature Range -	Operating	-40° to +105°C		
Termination Interface		N/A		
Waterproof / Dustproo		No		
Electrical				
Current - Maximum p	er Contact	1.0A, 2.5A, 2.0A, 3.0A		
<b>.</b>				

No

250V AC (RMS)/DC

Shielded Voltage - Maximum sit Contact US

Plug Housing

Receptacle

## **Material Info**

**Reference - Drawing Numbers** Application Specification Product Specification Sales Drawing

AS-51238-011-001 PS-51238-010-001, PS-51238-018-001 SD-51238-009-001, SD-51238-009-002, SD-51238-009-003, SD-51238-009-004

This document was generated on 02/01/2022 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for I/O Connectors category:

Click to view products by Molex manufacturer:

Other Similar products are found below :

 571763P
 58098-0628
 72.250.1628.2
 72.250.2428.2
 74720-0505
 76.350.0729.0
 76871-1403
 FCN-244F080-G/1
 FCN-260A9920
 PCR 

 E36PM
 PCS-XE26MA+
 G38A71314B
 1571250010
 157-22500-3
 MS3471L14-19P L/C
 192991-0703
 172501-4002
 172501-6002
 FCN 

 260C008-A/L0
 FCN-260C024-AL0
 FCN-261Z008
 2000314-1
 200331-1
 PCR-E36FC+
 PCS-E28FS+
 PCS-XE26SLFD+
 PCS 

 XE26SLFDT+
 G730VID08BDC24
 U90B2054081210
 38113800006
 DP3AR020WQ1R200
 Z4.102.0680.0
 500-1040
 500-1052
 500-1054

 ZP-4008-66L
 0709821002
 DX40-20P(55)
 5554841-1
 MS3474W18-8P-LC\*
 U90B3054061110
 U65-E04-4020
 ZPF000000000097891

 747360449
 10099439-003C-TRLF
 10137239-001LF
 F0329-001LF
 70.060.1028.0