

This document was generated on 12/14/2021 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: 051	<u>3870530</u>			
Status: Active			EU ELV	
Overview:			Not Relevant	
	Mini USB, B-Receptacle, Right-Angle, Short Body, Surface Mount Solder Tails and Through Hole Shell Tabs, with Cover Tape, Reflow DIP Type, Lead-Free		EU RoHS	China RoHS
Thro			Compliant	
			REACH SVHC	
General			Not Contained Per -	
Product Family		I/O Connectors	D(2021)4569-DC (8	6
Series		51387	July 2021)	
Application		Wire-to-Board	Halogen-Free	
Component Type		Receptacle	Status	
Overview		usb	Low-Halogen	
Product Name		USB	· · · · · · · · · · · · · · · · · · ·	n, please visit <u>Contact US</u>
			For more informatio	n, please visit <u>Contact OS</u>
Standard		USB 2.0	China ROHS	Green Image
Туре		Mini-B	ELV	Not Relevant
UPC		822348520787	RoHS Phthalates	Not Contained
Physical			Non's Filinalales	Not Contained
Physical		F		
Circuits (Loaded)		5		
Circuits (maximum)		5	Search Parts in t	his Series
Color - Resin		Black	51387 Series	
Gender		Female		
Lock to Mating Part		Yes		
Material - Metal		High Performance Alloy (HPA), Phosphor Bronze	Mates With	
Material - Plating Mating		Gold	<u>592049405</u>	
Material - Plating Terminatio	n	Tin		
Material - Resin		High Temperature Thermoplastic		
Mounting Style		Top-Mount		
Net Weight		0.300/g		
Number of Rows		1		
Orientation		, Right Angle		
PCB Locator		Yes		
PCB Retention		Yes		
Packaging Type		Embossed Tape on Reel		
Panel Mount		No		
Pitch - Mating Interface		0.80mm		
Pitch - Termination Interface		0.80mm		
Plating min - Mating		0.762µm		
Plating min - Termination		1.016µm		
Polarized to Mating Part		Yes		
Polarized to PCB		Yes		
Ports		1		
Surface Mount Compatible (SMC)		Yes		
Temperature Range - Operating		0° to +50°C		
Termination Interface: Style		Surface Mount		
Waterproof / Dustproof		No		
Electrical				
Current - Maximum per Cont	act	1.0A		
Shield Type		Full Shield		
Shielded		Yes		
Voltage - Maximum		30V AC (RMS)/DC		
voltago iviaximum				
Solder Process Data				
Duration at Max. Process Te	mperature (seconds)	003		
Lead-freeProcess Capability		REFLOW		
Max. Cycles at Max. Process		001		
Process Temperature max.		245		

Material Info

Reference - Drawing Numbers Product Specification

PS-51387-003-001

This document was generated on 12/14/2021 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for USB Connectors category:

Click to view products by Molex manufacturer:

Other Similar products are found below :

65-647-8-BK-BU 950 952 E8144-B01021-L A-USB A-LP-SMT-C A-USB B-TOP-C MUSBA511N5 MUSBD11135 217450-1 CA 6 W LD KMBVX-TH-5S-B30 896-30-004-00-000000 KUSBVX-BS1N-W30 KUSBX-AP-KIT-SCBLK KUSBX-AS2N-W KUSBX-SMT2AP1S-W KUSBX-SMT2AP1S-W30 935 957 30-498-6 17-210051 1734082-1 30-1574 30-470 30-489 30-541 30-572-3 MAB 8 SN V A-USB A-2P-C MIKROE-1451 USBFTV2PEM2G USBFTVC6ZN KUSBX-AS2N-W30 KUSBX-SLAS1N-W KUSBX-SMT-AS1N-W30 4689-1 1-1734084-2 E8110-001-01 MUSBA81130 33UBARS1-04SW11 33UBAR-04SW11 USBF21ZNSCC USBBFTV6ZC 10135326-001LF M9177/3-1 USB-A-S-F-B-VT 925 4198 690-024-633-031 KUSBEX-BSFS1N-W