

This document was generated on 02/07/2019

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: <u>0523163619</u>

Status: Active

Description: 1.27mm Pitch Wire-to-Board Shielded Plug, Dual Row, IDT, 36 Circuits

Documents:

<u>3D Model</u> <u>Product Specification PS-52986-017-001 (PDF)</u>
<u>Drawing (PDF)</u> <u>Packaging Specification SPK-52316-001-001 (PDF)</u>

Product Specification PS-52316-003 (PDF)

RoHS Certificate of Compliance (PDF)

Product Specification PS-52515-002 (PDF)

Agency Certification

UL E29179

General

Product Family I/O Connectors

Series <u>52316</u>
Application Wire-to-Board

Comments Conforms-IEEE 1284C Standard, Conforms-IEEE

1284C Standard

Component Type Plug

Product Name Leaf Style Contact

Type N/A

UPC 822348198450

Physical

Electrical

Boot Color N/A
Circuits (Loaded) 36
Circuits (maximum) 36
Durability (mating cycles max) 500
Flammability 94V-0

Flammability 94VGender Plug
Lock to Mating Part Yes

Material - Metal Phosphor Bronze

Material - Plating Mating Gold Material - Plating Termination Tin

Net Weight 6056.252/mg


Number of Rows Orientation N/A **PCB** Locator No **PCB** Retention N/A Packaging Type Trav Panel Mount Nο Pitch - Mating Interface 1.27mm Pitch - Termination Interface 1.27mm Plating min - Mating 0.762µm Plating min - Termination 1.016µm Polarized to Mating Part Yes Polarized to PCB No Ports 1 Surface Mount Compatible (SMC) No

Temperature Range - Operating -55° to +85°C
Termination Interface: Style IDT or Pierce

Waterproof / Dustproof No

Wire Insulation Diameter 0.58mm max.

Wire Size AWG 28



EU ELV

Not Relevant

EU RoHS China RoHS

Compliant REACH SVHC Not Contained Per -ED/61/2018 (27 June

2018) Halogen-Free

Status

Not Low-Halogen

For more information, please visit Contact US

China ROHS Green Image
ELV Not Relevant
RoHS Phthalates Not Contained

Search Parts in this Series

52316 Series

Mates With

<u>52822</u>, <u>54122</u>, <u>52986</u>

Current - Maximum per Contact 1.0A
Shield Type Full Shield
Shielded Yes

Voltage - Maximum 250V AC (RMS)/DC

Material Info

Reference - Drawing Numbers

Packaging Specification SPK-52316-001-001

Product Specification PS-52316-003, PS-52515-002, PS-52986-017-001

Sales Drawing SD-52316-002

This document was generated on 02/07/2019

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for I/O Connectors category:

Click to view products by Molex manufacturer:

Other Similar products are found below:

571763P 58098-0628 72.250.1628.2 72.250.2428.2 74720-0505 76.350.0729.0 76871-1403 FCN-244F080-G/1 FCN-260A9920 PCR-E36PM PCS-XE26MA+ G38A71314B 1571250010 157-22500-3 MS3471L14-19P L/C 192991-0703 172501-4002 172501-6002 FCN-260C008-A/L0 FCN-260C024-AL0 FCN-261Z008 2000314-1 200331-1 PCR-E36FC+ PCS-E28FS+ PCS-XE26SLFD+ PCS-XE26SLFD+ PCS-XE26SLFD+ G730VID08BDC24 U90B2054081210 UE86K842720321 38113800006 DP3AR020WQ1R200 Z4.102.0680.0 500-1040 500-1052 500-1054 ZP-4008-66L 0709821002 DX40-20P(55) 5554841-1 MS3474W18-8P-LC* U90B3054061110 U65-E04-4020 ZPF0000000000097891 747360449 10099439-003C-TRLF 10137239-0021LF E9320-001-01 10137239-0011LF 70289-001LF