

**PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION**

**Part Number:** [0528851074](#)  
**Status:** **Active**  
**Overview:** SlimStack Board-to-Board/Board-to-FPC Connectors  
**Description:** SlimStack Board-to-Board Connector, 0.635mm Pitch, 0.635 Series, Receptacle, 6.00 to 10.00mm Mated Height, 6.40mm Mated Width, 100 Circuits

**Documents:**

|   |  |
|---|--|
| <a href="#">3D Model</a>  | <a href="#">Datasheet (PDF)</a>                      |
| <a href="#">3D Model (PDF)</a>                                  | <a href="#">Product Guide (PDF)</a>                  |
| <a href="#">Drawing (PDF)</a>                                   | <a href="#">RoHS Certificate of Compliance (PDF)</a> |
| <a href="#">Product Specification 527600000-000 (PDF)</a>       | <a href="#">Reference Guide (PDF)</a>                |
| <a href="#">Packaging Specification SPK-52885-001-001 (PDF)</a> |  |

**Agency Certification**

UL E29179

**General**

|                |  |
|----------------|--|
| Product Family | PCB Receptacles  |
| Series         | <a href="#">52885</a>  |
| Application    | Board-to-Board, Signal   |
| Comments       | Stacking-Type  |
| Overview       | <a href="#">SlimStack Board-to-Board/Board-to-FPC Connectors</a> |
| Product Name   | SlimStack  |
| Series Name    | 0.635, Rigid   |
| UPC            | 822348166060   |

**Physical**

|                                |   |
|--------------------------------|---|
| Circuits (Loaded)              | 100                                     |
| Circuits (maximum)             | 100                                     |
| Color - Resin                  | Natural                                 |
| Durability (mating cycles max) | 50                                      |
| Flammability                   | 94V-0                                   |
| Glow-Wire Capable              | No                                      |
| Lock to Mating Part            | None                                    |
| Mated Height                   | 10.00mm, 6.00mm, 7.00mm, 8.00mm, 9.00mm |
| Mated Width                    | 6.40mm                                  |
| Material - Metal               | Copper Alloy                            |
| Material - Plating Mating      | Gold                                    |
| Material - Plating Termination | Tin                                     |
| Material - Resin               | High Temperature Thermoplastic          |
| Net Weight                     | 1149.696/mg                             |
| Number of Rows                 | 2                                       |
| Orientation                    | Vertical                                |
| PCB Locator                    | Yes                                     |
| PCB Retention                  | Yes                                     |
| PCB Thickness - Recommended    | 1.60mm                                  |
| Packaging Type                 | Embossed Tape on Reel                   |
| Pitch - Mating Interface       | 0.635mm                                 |
| Plating min - Mating           | 0.254µm                                 |
| Plating min - Termination      | 2.032µm                                 |
| Polarized to PCB               | Yes                                     |
| Robotic Placement              | Pick and Place Cap                      |
| Surface Mount Compatible (SMC) | N/A                                     |
| Temperature Range - Operating  | -55° to +105°C                          |
| Termination Interface: Style   | Surface Mount                           |

**Electrical**



*Series image - Reference only*

**EU ELV**

**Not Relevant**

**EU RoHS**

**Compliant**

**REACH SVHC**

Not Contained Per -  
D(2021)4569-DC (8  
July 2021)

**Halogen-Free**

**Status**

**Low-Halogen**

For more information, please visit [Contact US](#)

China ROHS

ELV

RoHS Phthalates

**China RoHS**

Green Image

Not Relevant

Not Contained

**Search Parts in this Series**

[52885 Series](#)

**Mates With**

SlimStack 0.635 Plug [55091](#) , [53625](#) , [53647](#)  
 , [53649](#) , [53627](#)

|                               |      |
|-------------------------------|------|
| Current - Maximum per Contact | 0.5A |
| Voltage - Maximum             | 100V |

**Material Info**

**Reference - Drawing Numbers**

|                         |                                    |
|-------------------------|------------------------------------|
| Packaging Specification | SPK-52885-001-001                  |
| Product Specification   | 527600000-000                      |
| Sales Drawing           | SD-52885-003-001, SD-52885-004-001 |

This document was generated on 10/06/2021

**PLEASE CHECK [WWW.MOLEX.COM](http://WWW.MOLEX.COM) FOR LATEST PART INFORMATION**

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Board to Board & Mezzanine Connectors](#) category:*

*Click to view products by [Molex](#) manufacturer:*

Other Similar products are found below :

[589158040000018](#) [MDF7C-18P-2.54DSA\(55\)](#) [FCN-230C068-11](#) [FCN-268F012-G/BD](#) [FCN-268F036-G/BD](#) [FCN-268M012-G/0D](#) [FCN-268M024-G/1D](#) [FCN-723J004/1](#) [MIS-048-01-F-D-DP-K](#) [832-10-034-10-001000](#) [FX4C-80S-1.27DSA](#) [FCN-214Q030-G/0](#) [FCN-234P048-G/0](#) [FCN-235D050-G/C](#) [210-93-314-41-105000](#) [2-22603-0](#) [MDF7-40DP-2.54DSA\(55\)](#) [AXG720047](#) [5031084030](#) [MIT-114-03-F-D-K](#) [55323-1519](#) [DF33-2P-3.3DSA\(24\)](#) [YFT-20-05-H-03-SB-K](#) [503308-3040](#) [026-6203-PDB](#) [027-6203-PDB](#) [069159702701000](#) [101A10019X](#) [55650-0588-C](#) [68682-310LF](#) [68684-306](#) [75140-7012](#) [87471-650](#) [194261-1](#) [FCN-268F024-G0D](#) [10124054-515LF](#) [68685-603](#) [8-1616154-3](#) [MIS-019-01-F-D](#) [FCN-268M024-G/3D](#) [FCN-268M036-G/BD](#) [20021832-06016C1LF](#) [KX15-20KLDL-E1000E](#) [AXE810124](#) [FCN-214J100-G/0](#) [FCN-230C068-E/S](#) [AXE812124](#) [AXE816124](#) [AXE720127](#) [354184](#)