

This document was generated on 03/01/2017 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:	<u>0543325003</u>		
Status:	Active		
Overview:	CRC [™] (Compact Robotic	Connectors)	
Description:		lar I/O Plug Assembly Set, Female Terminal, With Shield	
	Cover, Signal, 50 Circuits,		
	, , , ,		
Documents:			
Drawing (PDF)		Product Specification PS-51238-017-001 (PDF)	
3 ()	n PS-51238-016-001 (PDF)	RoHS Certificate of Compliance (PDF)	
	······································	······	
General			Series image - Reference only
Product Family		I/O Connectors	
Series		<u>54332</u>	EUELV
Application		Wire-to-Wire	Not Relevant
Component Type		Housing	
Overview		<u>CRC[™] (Compact Robotic Connectors)</u>	EU RoHS China RoHS
Product Name		CRC™	Compliant
		N/A	REACH SVHC
Type UPC			Not Contained Per
UPC		756054154311	-ED/01/2017 (12
Physical			January 2017)
Circuits (Loaded)		50	Halogen-Free
			Status
Circuits (maximum)		50	Not Low-Halogen
Color - Resin		Gray	· · · · · · · · · · · · · · · · · · ·
Durability (mating cycles max)		100	Need more information on product
Gender		Plug	environmental compliance?
Keying to Mating Part		Yes	Empil productos policinos @moley.com
Lock to Mating Part		Yes	Email productcompliance@molex.com
Material - Metal		Phosphor Bronze, Stainless Steel, Zinc Alloy	Please visit the <u>Contact Us</u> section for
Material - Plating Mating		N/A	non-product compliance questions.
Material - Resin		Polyester	China DOUR Cross Image
Net Weight		7551.844/mg	China ROHS Green Image
Number of Rows		4	ELV Not Relevant
		Vertical	RoHS Phthalates Not Contained
Orientation		No	
PCB Locator			
Packaging Type		Tray	Search Parts in this Series
Panel Mount		No	54332 Series
Pitch - Mating Interface		3.00mm	<u>54552</u> Selles
Pitch - Termination Interface		3.00mm	
Polarized to Mating Part		Yes	Mates With
Polarized to PCB		No	CRC [™] Shielded Rectangular I/O
Surface Mount Compatible (SMC)		No	Receptacle Housing <u>51233</u> , CRC™
Temperature Range - Operating		-40°C to +105°C	Shielded Rectangular I/O Receptacl
Termination Interface	e: Style	N/A	Assembly 55837, 55838
Waterproof / Dustproof		No	
Electrical			
Current - Maximum p	per Contact	2.0A, 3.0A, 4.0A, 5.0A, 7.0A	
		Full Shield	
Shield Type Shielded		Yes	
Voltage - Maximum		250V AC (RMS)/DC	
Material Info			
Reference - Drawin	a Numbers		

Reference - Drawing Numbers Product Specification Sales Drawing

PS-51238-016-001, PS-51238-017-001 SD-54332-005 This document was generated on 03/01/2017 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for I/O Connectors category:

Click to view products by Molex manufacturer:

Other Similar products are found below :

 571763P
 58098-0628
 72.250.1628.2
 72.250.2428.2
 74720-0505
 76.350.0729.0
 76871-1403
 FCN-244F080-G/1
 FCN-260A9920
 PCR

 E36PM
 PCS-XE26MA+
 G38A71314B
 1571250010
 157-22500-3
 MS3471L14-19P L/C
 192991-0703
 172501-4002
 172501-6002
 FCN

 260C008-A/L0
 FCN-260C024-AL0
 FCN-261Z008
 2000314-1
 200331-1
 PCR-E36FC+
 PCS-E28FS+
 PCS-XE26SLFD+
 PCS

 XE26SLFDT+
 G730VID08BDC24
 U90B2054081210
 UE86K842720321
 38113800006
 DP3AR020WQ1R200
 Z4.102.0680.0
 500-1040

 500-1052
 500-1054
 ZP-4008-66L
 0709821002
 DX40-20P(55)
 5554841-1
 MS3474W18-8P-LC*
 U90B3054061110
 U65-E04-4020

 ZPF000000000097891
 747360449
 10099439-003C-TRLF
 10137239-0021LF
 E9320-001-01
 10137239-0011LF
 70289-001LF