

This document was generated on 09/13/2019 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:	1300980188			
Status: Active				
Overview:	Strain-Relief Cord Grip	8		
Description:	MAX-LOC Strain Relief Cord-Sealing Grip for UF Cable, 1/2" NPT, Straight Male, Cable			
Description.	Diameter 5.54X16.26mm (.218X.640") Oval		20	
	Diameter 5.54X10.201	iiii (.2 107.040) Oval		
Documents:				
RoHS Certificate of	Compliance (PDE)	Product Literature (PDF)		
Agency Certification	on			
CSA		LR32159	Series imag	e - Reference only
UL		E76954		
			EU ELV	
General			Not Reviewed	
Product Family		Cable Grips		
Series		<u>130098</u>	EU RoHS	<u>China RoHS</u>
Exclude SD Check		Yes	Not Reviewed	
Еуе Туре		N/A	REACH SVHC	
NEMA Rating		NEMA 3R	Not Reviewed	
O-Ring		No	Halogen-Free	
Overview		Strain-Relief Cord Grips	<u>Status</u>	
Product Literature Order No		987651-6081	Not Reviewed	
Product Name		MAX-LOC	For more information, please visit Contact US	
Туре		Strain Relief Grip		
UPC		78678872145	China ROHS	Not Reviewed
Use With		1/2" NPT MAX-LOC Lock Nut <u>1300990143</u> , MAX-LOC	ELV	Not Reviewed
		O-Ring, 1/2" NPT <u>1301800314</u> , 1/2" NPT MAX-LOC	RoHS Phthalates	Not Reviewed
		Gasket <u>1300990149</u>		
Physical			Secret Derte in t	hia Cariaa
Approximate Break	Strength	N/A	Search Parts in this Series <u>130098</u> Series	
Bale Length		N/A	130030 Selles	
Body Style		Straight		
Cable Diameter		5.54x16.26mm (.218x.640") Oval		
Color - Grommet		N/A		
Gender		Male		
Material - Body		Nylon		
Material - Grip		N/A		
Mesh Length		N/A		
Number of Holes		1		
Thread Size		1/2" NPT		
Material Info				
Engineering Numbe	r	5582		

This document was generated on 09/13/2019

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Cable Glands, Strain Reliefs & Cord Grips category:

Click to view products by Molex manufacturer:

Other Similar products are found below :

 120-116-1-1-20BP
 120-116-1-1-32BE
 120-117-40
 120-123-14
 120-125-16
 120-125-16R
 120-125-16Y
 120-125-24Y
 120-125-24Y

 28
 120-125-28R
 120-125-32
 120-125-32R
 120-125-40
 120-125-56
 120-126-16
 120-126-20
 120-126-20BL
 120-126-20R
 120-