

This document was generated on 10/25/2012 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:	67491-1030		(MIN)
Status:	Active		
Overview:	Serial ATA Products		
Description:		High Speed Header, Through Hole, Vertical, 7 Circuits, Gold	
Jescription.		PC Tail Length, for 1.60mm PCB, Black Housing, Lead-Free	
	(//d) / /doin, with 2.001111		
Documents:			
3D Model		Product Specification PS-67491-001 (PDF)	
Drawing (PDF)		RoHS Certificate of Compliance (PDF)	1 Year
			- National Series
General			image - Reference only
Product Family		PCB Headers	
Series		<u>67491</u>	EU RoHS China RoHS
Application		Board-to-Board, Signal, Wire-to-Board	ELV and RoHS
Overview		Serial ATA Products	Compliant
Product Name		Serial ATA	REACH SVHC
UPC		822348677542	Contains SVHC: No
-			Low-Halogen Status
Physical			Not Low-Halogen
Breakaway		No	Need more information on product
Circuits (Loaded)		7	Need more information on product
Circuits (maximum)		7	environmental compliance?
Color - Resin		Black	Email productcompliance@molex.com
Durability (mating cycles max)		50	For a multiple part number RoHS Certificate of
First Mate / Last Break		Yes	Compliance, click here
Glow-Wire Compliant		No	
Guide to Mating Part		No	Please visit the Contact Us section for any
Keying to Mating Part		Yes	non-product compliance questions.
Lock to Mating Part		Yes	
Material - Plating Mating		Gold	
		Tin	
Material - Plating Termination Material - Resin		Polyester	Search Parts in this Series
		•	
Net Weight		1.227/g	<u>67491</u> Series
Number of Rows		Vortical	
Orientation		Vertical	Mates With
PC Tail Length		2.05mm	Serial ATA Signal Connector 67489, 88755
PCB Locator		Yes	
PCB Retention		Yes	
PCB Thickness - Re	ecommenaea	1.60mm	
Packaging Type		Tray	
Pitch - Mating Interfa		1.27mm	
Pitch - Termination		1.27mm	
Plating min - Mating	·	0.051µm	
Plating min - Termin		1.270µm	
Polarized to Mating	Part	Yes	
Polarized to PCB		Yes	
Shrouded		No	
Stackable		No	
Surface Mount Com		No	
Temperature Range - Operating		-35°C to +85°C	
Termination Interfac	ce: Style	Through Hole	
Electrical			
Current - Maximum	per Contact	1.5A	
Voltage - Maximum		15V DC	

Material Info

Reference - Drawing Numbers

Electrical Model Document	
Product Specification	
Sales Drawing	

This document was generated on 10/25/2012 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

EE-67491-001 PS-67491-001 SD-67491-002

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for I/O Connectors category:

Click to view products by Molex manufacturer:

Other Similar products are found below :

 571763P
 58098-0628
 72.250.1628.2
 72.250.2428.2
 74720-0505
 76.350.0729.0
 76871-1403
 FCN-244F080-G/1
 FCN-260A9920
 PCR

 E36PM
 PCS-XE26MA+
 G38A71314B
 1571250010
 157-22500-3
 MS3471L14-19P L/C
 192991-0703
 172501-4002
 172501-6002
 FCN

 260C008-A/L0
 FCN-260C024-AL0
 FCN-261Z008
 2000314-1
 200331-1
 PCR-E36FC+
 PCS-E28FS+
 PCS-XE26SLFD+
 PCS

 XE26SLFDT+
 G730VID08BDC24
 U90B2054081210
 UE86K842720321
 38113800006
 DP3AR020WQ1R200
 Z4.102.0680.0
 500-1040

 500-1052
 500-1054
 ZP-4008-66L
 0709821002
 DX40-20P(55)
 5554841-1
 MS3474W18-8P-LC*
 U90B3054061110
 U65-E04-4020

 ZPF000000000097891
 747360449
 10099439-003C-TRLF
 10137239-0021LF
 E9320-001-01
 10137239-0011LF
 70289-001LF