

This document was generated on 10/25/2012

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: 67800-7005

Status: Active

Overview: Serial ATA Products

Description: 1.27mm Pitch Serial ATA High Speed Header, Vertical, Through Hole, with Locking

Latch, 7 Circuits, 0.38µm Gold (Au) Plating, for 1.60mm PCB, Black, Footprint B, with

PCB Locator Tabs, Lead-Free

Documents:

<u>3D Model</u> <u>Product Specification PS-67491-001 (PDF)</u>
<u>Drawing (PDF)</u> <u>RoHS Certificate of Compliance (PDF)</u>

Agency Certification

CSA LR19980 UL E29179

General

Product Family PCB Headers

Series <u>67800</u>

Application Board-to-Board, Signal, Wire-to-Board Comments Staggered Solder Pin|Footprint B

Overview Serial ATA Products

Product Name Serial ATA UPC 822348710683


Physical

Breakaway No Circuits (Loaded) 7 Circuits (maximum) 7 Color - Resin Black Durability (mating cycles max) 50 First Mate / Last Break Yes Flammability 94V-0 Glow-Wire Compliant No Guide to Mating Part No Keying to Mating Part Yes Lock to Mating Part Yes Material - Metal **Brass** Material - Plating Mating Gold Material - Plating Termination Tin Net Weight 0.909/gNumber of Rows Orientation Vertical PC Tail Length 2.45mm **PCB** Locator Yes **PCB** Retention Yes PCB Thickness - Recommended 1.60mm Packaging Type Tray Pitch - Mating Interface 1.27mm Pitch - Termination Interface 1.27mm Polarized to Mating Part Yes Shrouded Fully Stackable No

Temperature Range - Operating -35°C to +85°C Termination Interface: Style Through Hole

No

Surface Mount Compatible (SMC)



EU RoHS
ELV and RoHS
Compliant
REACH SVHC
Contains SVHC: No
Low-Halogen Status
Not Low-Halogen



Need more information on product environmental compliance?

Email <u>productcompliance@molex.com</u>
For a multiple part number RoHS Certificate of Compliance, click here

Please visit the <u>Contact Us</u> section for any non-product compliance questions.

Search Parts in this Series 67800Series

Electrical

Current - Maximum per Contact 1.5A Voltage - Maximum 15V DC

Solder Process Data

Lead-free Process Capability Wave Capable (TH only)

Material Info

Reference - Drawing Numbers
Electrical Model Document

Electrical Model Document EE-67800-001
Product Specification PS-67491-001
Sales Drawing SD-67800-007

This document was generated on 10/25/2012

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for I/O Connectors category:

Click to view products by Molex manufacturer:

Other Similar products are found below:

571763P 58098-0628 72.250.1628.2 72.250.2428.2 74720-0505 76.350.0729.0 76871-1403 FCN-244F080-G/1 FCN-260A9920 PCR-E36PM PCS-XE26MA+ G38A71314B 1571250010 157-22500-3 MS3471L14-19P L/C 192991-0703 172501-4002 172501-6002 FCN-260C008-A/L0 FCN-260C024-AL0 FCN-261Z008 2000314-1 200331-1 PCR-E36FC+ PCS-E28FS+ PCS-XE26SLFD+ PCS-XE26SLFD+ PCS-XE26SLFD+ G730VID08BDC24 U90B2054081210 UE86K842720321 38113800006 DP3AR020WQ1R200 Z4.102.0680.0 500-1040 500-1052 500-1054 ZP-4008-66L 0709821002 DX40-20P(55) 5554841-1 MS3474W18-8P-LC* U90B3054061110 U65-E04-4020 ZPF0000000000097891 747360449 10099439-003C-TRLF 10137239-0021LF E9320-001-01 10137239-0011LF 70289-001LF