

This document was generated on 10/10/2012 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:	67000 0040		
	<u>67926-0012</u>		
Status:	Active		a contraction of the second se
Overview:	Serial ATA Power Connect		
Description:		DT Power Receptacle, 0.76µm (0.76µm) Gold (Au) Plating,	Annang
	18AWG, without Latch, wit	n Bump, Lead-Free	
Documents:			
3D Model		RoHS Certificate of Compliance (PDF)	
Drawing (PDF)			
<u></u>			Series
General			image - Reference only
Product Family		IDT and Solder Connectors	
Series		<u>67926</u>	EU RoHS China RoHS
Crimp Quality Equipment		Yes	ELV and RoHS
Overview		Serial ATA Power Connector	Compliant
Product Name		Serial ATA	REACH SVHC
UPC		756054872932	Contains SVHC: No
Use With		<u>679260040</u> Feed-to Cover, <u>679260041</u> Feed-Through	Low-Halogen Status
		Cover	Not Low-Halogen
Physical			Need more information on product
Physical		r.	environmental compliance?
Circuits (Loaded)		5	
Circuits (maximum)		5	Email productcompliance@molex.com
Color - Resin		Black	For a multiple part number RoHS Certificate of
Durability (mating cycles max)		50	Compliance, <u>click here</u>
Gender		Female	Please visit the <u>Contact Us</u> section for any
Glow-Wire Compliant		No	non-product compliance questions.
Lock to Mating Part		Yes	non-product compliance questions.
Material - Metal		Copper Alloy	
Material - Plating Mating		Gold	
Material - Plating Termination		Tin	
Net Weight		4.469/g	Search Parts in this Series
Number of Rows		1	<u>67926</u> Series
Packaging Type		Tray	
Panel Mount		No	Mates With
Pitch - Mating Interface		3.81mm	<u>87679</u>
Pitch - Termination Interface		3.81mm	
Plating min - Mating		0.762µm	Application Tooling FAQ
Plating min - Termination Polarized to Mating Part		1.905µm Yes	Tooling specifications and manuals are
Temperature Range - Operating		-35°C to +85°C	found by selecting the products below.
Wire Size AWG		-35 C 10 +65 C 18	Crimp Height Specifications are then
WITE SIZE AWG			contained in the Application Tooling
Electrical			Specification document.
Current - Maximum per Contact		1.5A	Global
Voltage - Maximum		15V DC	Description Product #
		-	Insertion Tool for 0638133503
Solder Process Data			3.96mm Pitch IDT
Process Temperature max. C		230	Crimp Terminals
Material Info			
Reference - Draw	vina Numbers		
Sales Drawing	J	SD-67926-001	
,			

This document was generated on 10/10/2012 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for I/O Connectors category:

Click to view products by Molex manufacturer:

Other Similar products are found below :

 571763P
 58098-0628
 72.250.1628.2
 72.250.2428.2
 74720-0505
 76.350.0729.0
 76871-1403
 FCN-244F080-G/1
 FCN-260A9920
 PCR

 E36PM
 PCS-XE26MA+
 G38A71314B
 1571250010
 157-22500-3
 MS3471L14-19P L/C
 192991-0703
 172501-4002
 172501-6002
 FCN

 260C008-A/L0
 FCN-260C024-AL0
 FCN-261Z008
 2000314-1
 200331-1
 PCR-E36FC+
 PCS-E28FS+
 PCS-XE26SLFD+
 PCS

 XE26SLFDT+
 G730VID08BDC24
 U90B2054081210
 UE86K842720321
 38113800006
 DP3AR020WQ1R200
 Z4.102.0680.0
 500-1040

 500-1052
 500-1054
 ZP-4008-66L
 0709821002
 DX40-20P(55)
 5554841-1
 MS3474W18-8P-LC*
 U90B3054061110
 U65-E04-4020

 ZPF000000000097891
 747360449
 10099439-003C-TRLF
 10137239-0021LF
 E9320-001-01
 10137239-0011LF
 70289-001LF