

Sales Drawing

This document was generated on 10/07/2013 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: 679	<u>926-0315</u>		
Status: Act	tive		CHONG -
	al ATA Power Connecto	r	A Realis
			1 And
	3.81mm Pitch Serial ATA IDT Power Receptacle, 0.38µm (0.38µm) Gold (Au) Plating, 20AWG, without Latch, with Bump, Lead-Free		1 11 DY DATA
20A)	WG, without Latch, with	Bump, Lead-Free	
			S NY X
Documents:			
3D Model		RoHS Certificate of Compliance (PDF)	
Drawing (PDF)			
<u> </u>			Serie
General			image - Reference only
Product Family		IDT and Solder Connectors	
Series		<u>67926</u>	EU RoHS China RoHS
Crimp Quality Equipment		Yes	ELV and RoHS
		Serial ATA Power Connector	Compliant
Overview Product Name UPC Use With			REACH SVHC
		Serial ATA	Contains SVHC: No
		883906438562	
		<u>67926-0040</u> Feed-to Cover, <u>67926-0041</u> Feed-Through	Low-Halogen Status
		Cover	Not Low-Halogen
Physical			Need more information on product
Circuits (Loaded)		5	environmental compliance?
Circuits (maximum)		5	
			Email productcompliance@molex.com
Color - Resin		Black	For a multiple part number RoHS Certificate
Durability (mating cycles max)		50	Compliance, <u>click here</u>
Gender		Female	
Glow-Wire Compliant		No	Please visit the <u>Contact Us</u> section for any
Lock to Mating Part		Yes	non-product compliance questions.
Material - Metal		Copper Alloy	
Material - Plating Mating		Gold	
Material - Plating Termination		Tin	
Net Weight		1.803/g	Search Parts in this Series
Number of Rows		1	67926Series
Packaging Type		Tray	
Panel Mount		No	
Pitch - Mating Interface		3.81mm	Mates With
		3.81mm	<u>87679</u>
Pitch - Termination Interface			
Plating min - Mating		0.381µm	Application Tooling FAQ
Plating min - Termination		1.905µm	Tooling specifications and manuals are
Polarized to Mating Part		Yes	found by selecting the products below.
Temperature Range - Operating		-35°C to +85°C	Crimp Height Specifications are then
Wire Size AWG		20	
			contained in the Application Tooling
Electrical			Specification document.
Current - Maximum per Contact		1.5A	Global
Voltage - Maximum		15V DC	Description Product #
-			Insertion Tool for 0638133503
Solder Process Data			3.96mm Pitch IDT
Duration at Max. Process Temperature (seconds)		3	Crimp Terminals
Lead-free Process Capability		Reflow Capable (SMT only)	,
Max. Cycles at Max. Process Temperature		1	
Process Temperature max. C		255	
FIDERS TEMPERATURE MAX.	0	200	
Material Info			
Potoronoo Drowing	lumbors		
Reference - Drawing N		SD 67026 001	

This document was generated on 10/07/2013 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for I/O Connectors category:

Click to view products by Molex manufacturer:

Other Similar products are found below :

 571763P
 58098-0628
 72.250.1628.2
 72.250.2428.2
 74720-0505
 76.350.0729.0
 76871-1403
 FCN-244F080-G/1
 FCN-260A9920
 PCR

 E36PM
 PCS-XE26MA+
 G38A71314B
 1571250010
 157-22500-3
 MS3471L14-19P L/C
 192991-0703
 172501-4002
 172501-6002
 FCN

 260C008-A/L0
 FCN-260C024-AL0
 FCN-261Z008
 2000314-1
 200331-1
 PCR-E36FC+
 PCS-E28FS+
 PCS-XE26SLFD+
 PCS

 XE26SLFDT+
 G730VID08BDC24
 U90B2054081210
 UE86K842720321
 38113800006
 DP3AR020WQ1R200
 Z4.102.0680.0
 500-1040

 500-1052
 500-1054
 ZP-4008-66L
 0709821002
 DX40-20P(55)
 5554841-1
 MS3474W18-8P-LC*
 U90B3054061110
 U65-E04-4020

 ZPF000000000097891
 747360449
 10099439-003C-TRLF
 10137239-0021LF
 E9320-001-01
 10137239-0011LF
 70289-001LF