

This document was generated on 04/07/2016

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: 0709282000

Status: Active

Overview: LFH™ Interconnect System

Description: 1.27mm Pitch LFH™ Matrix 50 Receptacle, Shielded, Right Angle, 2.01mm PC Tail

Length, Screw Hole M3 Thread, Gold Plating, 60 Circuits

Documents:

3D Model Test Summary TS-70928-001 (PDF)
Drawing (PDF) RoHS Certificate of Compliance (PDF)

Product Specification PS-70928 (PDF)

Agency Certification

CSA LR19980 UL E29179

General

Product Family I/O Connectors

Series <u>70928</u>

Application Board-to-Board, Wire-to-Board

Comments Dim.B for 1.00mm max. Panel Thickness is 9.65mm and

10.67mm for 1.63mm max. Panel Thickness

Component Type Receptacle

Overview <u>LFH™ Interconnect System</u>

Product Name LFH™ Type N/A

UPC 800753597341

Physical

Circuits (Loaded) 60
Circuits (maximum) 60
Color - Resin Black
Durability (mating cycles max) 500
Flammability 94V-0
Gender Receptacle

Keying to Mating Part

Lock to Mating Part

Yes

Material - Metal Beryllium Copper

Material - Plating Mating Gold Material - Plating Termination Tin

Material - Resin High Temperature Thermoplastic


Net Weight 7.040/g Number of Rows 4

Orientation Right Angle
PC Tail Length 2.00mm
PCB Retention None
PCB Thickness - Recommended 1.60mm

Packaging Type Tube **Panel Mount** Yes Pitch - Mating Interface 1.27mm Pitch - Termination Interface 1.27mm Plating min - Mating 0.762µm Plating min - Termination 2.540um Polarized to Mating Part Yes Surface Mount Compatible (SMC) Yes

Temperature Range - Operating -20°C to +80°C Termination Interface: Style Surface Mount

Wire Size AWG N/A



EU ELV

Not Relevant

EU RoHS China RoHS

Compliant REACH SVHC Not Contained Per -ED/79/2015 (17

December 2015)
Halogen-Free

Status

Low-Halogen

Need more information on product environmental compliance?

Email <u>productcompliance@molex.com</u>
Please visit the <u>Contact Us</u> section for any non-product compliance questions.

China ROHS Green Image ELV Not Relevant

Search Parts in this Series

70928 Series

Mates With 70929 LFH™ Plug

Use With

 $\underline{71628}$ Guide Pin, Guide Sleeve 71629 or

71771, 70982 Hex Screw Kit

Electrical

Current - Maximum per Contact 1.0A Shielded Yes Voltage - Maximum 40V

Solder Process Data

Duration at Max. Process Temperature (seconds)

Lead-freeProcess Capability

Max. Cycles at Max. Process Temperature

003

Process Temperature max. C

260

Material Info

Reference - Drawing Numbers

Product Specification PS-70928, RPS-70928-001, RPS-70928-002

Sales Drawing SDA-70928-20** Test Summary TS-70928-001

This document was generated on 04/07/2016

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for I/O Connectors category:

Click to view products by Molex manufacturer:

Other Similar products are found below:

571763P 58098-0628 72.250.1628.2 72.250.2428.2 74720-0505 76.350.0729.0 76871-1403 FCN-244F080-G/1 FCN-260A9920 PCR-E36PM PCS-XE26MA+ G38A71314B 1571250010 157-22500-3 MS3471L14-19P L/C 192991-0703 172501-4002 172501-6002 FCN-260C008-A/L0 FCN-260C024-AL0 FCN-261Z008 2000314-1 200331-1 PCR-E36FC+ PCS-E28FS+ PCS-XE26SLFD+ PCS-XE26SLFD+ PCS-XE26SLFD+ G730VID08BDC24 U90B2054081210 UE86K842720321 38113800006 DP3AR020WQ1R200 Z4.102.0680.0 500-1040 500-1052 500-1054 ZP-4008-66L 0709821002 DX40-20P(55) 5554841-1 MS3474W18-8P-LC* U90B3054061110 U65-E04-4020 ZPF0000000000097891 747360449 10099439-003C-TRLF 10137239-0021LF E9320-001-01 10137239-0011LF 70289-001LF