

This document was generated on 10/19/2016

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: 0714300013

Status: Active

Overview: Ultra+TM VHDCI Interconnects

Description: 0.80mm Pitch Ultra+™ VHDCI Receptacle, Right Angle, 68 Circuits, PC Tail Length

2.08mm, Shield with Enhanced Ground Tabs, No Screwlocks

Documents:

3D Model Packaging Specification PK-71430-0101 (PDF)

Drawing (PDF)
Product Specification PS-71425-9999 (PDF)
RoHS Certificate of Compliance (PDF)

Agency Certification

CSA LR19980 UL E29179

General

Product Family I/O Connectors

Series 71430
Application Wire-to-Board

Comments Shield with Enhanced Ground Tabs, No Screwlocks

Component Type Receptacle

Overview <u>Ultra+™ VHDCI Interconnects</u>

Product Name SCSI+, VHDCI

Type N/A

UPC 800756916514

Physical

Boot ColorN/ACircuits (Loaded)68Circuits (maximum)68Color - ResinBlackDurability (mating cycles max)500Flammability94V-0

Gender Receptacle
Lock to Mating Part Yes
Material - Plating Mating Gold

Material - Resin High Temperature Thermoplastic

Net Weight 4.315/g Number of Rows 2

Orientation Right Angle PC Tail Length 2.08mm PCB Locator Yes **PCB** Retention Yes PCB Thickness - Recommended 1.60mm Packaging Type Tube **Panel Mount** Yes Pitch - Mating Interface 0.80mm

Pitch - Mating Interface

Pitch - Termination Interface

Polarized to Mating Part

Polarized to PCB

Ports

Surface Mount Compatible (SMC)


Pes

1

Yes

Temperature Range - Operating -55°C to +85°C Termination Interface: Style Through Hole

Waterproof / Dustproof No Wire Size AWG N/A



EU ELV Not Relevant

EU RoHS China RoHS

Compliant with
Exemption 6(c)
REACH SVHC
Not Contained Per ED/21/2016 (20 June

2016) <u>Halogen-Free</u>

Status Low-Halogen

Need more information on product environmental compliance?

Email <u>productcompliance@molex.com</u>
Please visit the <u>Contact Us</u> section for any non-product compliance questions.

China ROHS 50 Image
ELV Not Relevant
RoHS Phthalates Not Contained

Search Parts in this Series

71430 Series

Mates With

71425 Ultra+™ VHDCI Plug Kit

Electrical

Current - Maximum per Contact 0.5A Shield Type Full Shield

Shielded Yes

Voltage - Maximum 30V AC (RMS)/DC

Solder Process Data

Duration at Max. Process Temperature (seconds)

Lead-freeProcess Capability

Max. Cycles at Max. Process Temperature

003

Process Temperature max. C

245

Material Info

Reference - Drawing Numbers

Packaging Specification PK-71430-0101 Product Specification PS-71425-9999

Sales Drawing SD-71430-015, SD-71430-3000

Test Summary TS-71425-9999

This document was generated on 10/19/2016

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for I/O Connectors category:

Click to view products by Molex manufacturer:

Other Similar products are found below:

571763P 58098-0628 72.250.1628.2 72.250.2428.2 74720-0505 76.350.0729.0 76871-1403 FCN-244F080-G/1 FCN-260A9920 PCR-E36PM PCS-XE26MA+ G38A71314B 1571250010 157-22500-3 MS3471L14-19P L/C 192991-0703 172501-4002 172501-6002 FCN-260C008-A/L0 FCN-260C024-AL0 FCN-261Z008 2000314-1 200331-1 PCR-E36FC+ PCS-E28FS+ PCS-XE26SLFD+ PCS-XE26SLFD+ PCS-XE26SLFD+ G730VID08BDC24 U90B2054081210 UE86K842720321 38113800006 DP3AR020WQ1R200 Z4.102.0680.0 500-1040 500-1052 500-1054 ZP-4008-66L 0709821002 DX40-20P(55) 5554841-1 MS3474W18-8P-LC* U90B3054061110 U65-E04-4020 ZPF0000000000097891 747360449 10099439-003C-TRLF 10137239-0021LF E9320-001-01 10137239-0011LF 70289-001LF