



ELECTRICAL SPECIFICATIONS :

- Frequency range : 758 to 803 MHz
- Input power : 130 W
- Input power, peak : 1300 W
- Reflected power : 80 W
- Isolation (within frequency range, port 2 to 1) : 22 dB Min
- Return Loss (Measured at port 1 and port 2) : 23 dB Min (0°C-115°C)
(Measured at port 1 and port 2) : 20 dB Min (-40°C-0°C)
- Insertion Loss (within frequency range, port 1 to 2) : 0.25 dB Max
- Intermodulation distortion, IM3(2 x 50 W) : -65 dBc Max
IM5(2 x 50 W) : -79 dBc Max
- Harmonics: 2 x f(100W CW) : 0dBm Max
3-4 x f (100W CW) : -10 dBm Max
5 x f (100W CW) : -35dBm Max
6-7 x f (100W CW) : -25 dBm Max
- Operating temperature range: -40°C to +115°C
- Storage temperature range : -40°C to +115°C
- Direction : CCW

BODY: STEEL, SILVER PLATED
RIGID PINS: COPPER, SILVER PLATED
NOTES:

1. STANDARD INPUT/OUTPUT IMPEDANCE 50 Ohm.
2. LEAD FREE, NO Nd MATERIAL, BeO FREE.
3. THE DIMENSION OF THE DATA MATRIX IS 7.6MM*7.6MM, INFORMATION INCLUDED WORK ORDER NUMBER-SERIAL NUMBER-MATERIAL NUMBER
4. THIS PART COMPLIES WITH ALL ROHS REQUIREMENTS

ENG PART#: 811-075-080-WB040

FUNCTIONAL SYMBOLS F=0 E=0 P=0	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION		CURRENT REV DESC: RELEASE TO PROD		molex	
	DIMENSION UNITS MM	SCALE 1:1	EC NO: 696580			
	GENERAL TOLERANCES (UNLESS SPECIFIED)		DRWN: SREN05	2022/02/21		SMSJ ISOLATOR/758~803 MHZ/CCW
			CHK'D: JLI252	2022/02/23		
DIVISIONAL SYMBOLS	4 PLACES ±0.005 ±----	mm	APPR: HWANG186	2022/03/01	RESTRICTED PRODUCT CUSTOMER DRAWING	
	3 PLACES ±0.025 ±----	INCH	INITIAL REVISION:		DOCUMENT NUMBER	
	2 PLACES ±0.13 ±----		DRWN: SREN05	2021/12/09	735912096	
	1 PLACE ±0.25 ±----		APPR: HWANG186	2022/03/01	PSD 000 A	
	0 PLACES ±0.4 ±----	ANGULAR TOL ± 1.5 °	DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS	THIRD ANGLE PROJECTION	DRAWING	
				SERIES	MATERIAL NUMBER	
				A3-SIZE	73591	
				CUSTOMER	0735912096	
				CUSTOM PART	1 OF 1	

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [RF Connectors / Coaxial Connectors](#) category:

Click to view products by [Molex](#) manufacturer:

Other Similar products are found below :

[8915-1511-000](#) [89674-0827](#) [6001-7071-019](#) [6002-7051-003](#) [6002-7551-202](#) [6059674-1](#) [619550-1](#) [630059-000](#) [M39030/3-01N](#) [6500-7071-046](#) [6769](#) [CX050L2AQ](#) [7002-1541-010](#) [7002-1542-011](#) [7002-1572-002](#) [7003-1542-011](#) [7004-1512-000](#) [7009-1511-004](#) [7010-1511-000](#) [7029-1511-060](#) [7101-1541-010](#) [7101-1571-002](#) [7145-1521-002](#) [7203-1571-003](#) [7209-1511-011](#) [7210-1511-015](#) [7210-1511-019](#) [73137-5015](#) [73216-2241](#) [73404-2300](#) [7405-1521-005](#) [7405-1521-802](#) [8527](#) [8547](#) [FS11V](#) [9049-9513-000](#) [9074-9513-000](#) [9101-9573-002](#) [910A205F](#) [9130-9573-002](#) [PL11SC-026](#) [PL375-33](#) [PL40-5](#) [PL74C-221](#) [PL75MC-217](#) [PL803-7](#) [980-8666-005](#) [1200690078](#) [1-201144-1](#) [R107003010W](#)