

Temperature Range - Operating

Termination Interface: Style

## This document was generated on 12/13/2021 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

| Part Number: 0  | 736420000           |  | 6 V.   |   |
|---|---------------------|--|--|---|
|   | ctive               |  |  | ×.                                      |
| Overview: HDM Backplane Co                                  |                     | n e sten Quetern   | 200  | were .                                  |
|   |                     |  |  | "The all                                |
| Description: H  | DIVI Board-to-Board | Backplane Header, Vertical, Press-Fit, Open End, 72 Circuits |  | De re                                   |
| Documents:  |                     |  |  | Con the                                 |
| 3D Model  |                     | Product Specification PS-73670-9999-001 (PDF)                |  |   |
| Drawing (PDF)   |                     | Packaging Specification PK-70873-0818-001 (PDF)              | 1  |   |
| <u>3D Model (PDF)</u>                                       |                     | RoHS Certificate of Compliance (PDF)                         |  |   |
|   |                     |  |  | N. C.                                   |
| Agency Certification  |                     |  | Series ima   | ge - Reference only                     |
| CSA   |                     | LR19980  |  | - · · · · · · · · · · · · · · · · · · · |
| UL  |                     | E29179   | EU ELV   |   |
| 01  |                     | 220110   | Not Relevant   |   |
| General   |                     |  | Not Kelevant   |   |
| Product Family  |                     | Backplane Connectors   | EU RoHS  | China RoHS                              |
| Series  |                     | 73642  | Compliant  |   |
| Application   |                     | Backplane  | REACH SVHC   |   |
| Comments  |                     | Standard Press-Fit   | Not Contained Pe   | r -                                     |
| Component Type  |                     | PCB Header   | D(2021)4569-DC   |   |
| Overview  |                     | HDM Backplane Connector System                               | July 2021)   | (0                                      |
| Product Name  |                     | HDM  | Halogen-Free   |   |
| UPC   |                     | 800754345057   | Status   |   |
| 010   |                     | 000104040001   | Low-Halogen  |   |
| Physical  |                     |  | · · · · · · · · · · · · · · · · · · ·                                  | ion places visit Contact I              |
| Circuits (Loaded)   |                     | 72   | For more mormal  | ion, please visit <u>Contact l</u>      |
| Circuits (maximum)  |                     | 72   | China ROHS   | Green Image                             |
| Color - Resin   |                     | Black, Natural   | ELV  | Not Relevant                            |
| Durability (mating cycles max)                              |                     | 250  | RoHS Phthalates  | Not Contained                           |
| First Mate / Last Break                                     |                     | No   |  | Not Contained                           |
| Flammability  |                     | 94V-0  |  |   |
| Guide to Mating Part  |                     | No   |  |   |
| Keying to Mating Part                                       |                     | None   | Search Parts in this Series  |   |
| Material - Metal  |                     | Phosphor Bronze  | 73642 Series   |   |
| Material - Plating Mating                                   |                     | Gold   |  |   |
| Material - Plating Mating<br>Material - Plating Termination |                     | Gold   | Mates With   |   |
| Material - Resin  |                     |  |  | pard-to-Board Daughterc                 |
|   |                     | <b>J</b>   |  |   |
| Net Weight  |                     | 3.371/g  | Receptacle. <u>73780</u> HDM Board-to-Board<br>Daughtercard Receptacle |   |
| Number of Columns   |                     | 12<br>On on Dia Field  |  | eceptacle                               |
| Number of Pairs   |                     | Open Pin Field   |  |   |
| Number of Rows  |                     | 6  | Application To   |   |
| Orientation   |                     | Vertical   |  | ations and manuals are                  |
| PC Tail Length  |                     | 3.50mm   |  | ng the products below.                  |
| PCB Locator   |                     | No   |  | pecifications are then                  |
| PCB Retention   |                     | Yes  |  | Application Tooling                     |
| PCB Thickness - Recommended                                 |                     | 1.60mm   | Specification do   | cument.                                 |
| Packaging Type  |                     | Tube   | Global   |   |
| Pitch - Mating Interface                                    |                     | 2.00mm   | Description  | Product #                               |
| Pitch - Termination Interface                               |                     |  |  | 621001000                               |
| Plating min - Mating  |                     | 0.762µm  | Extraction Tool  |   |
| Plating min - Termination                                   |                     | 0.051µm  |  |   |
| Polarized to PCB  |                     | No   |  |   |
| Stackable   |                     | Yes  |  |   |
| Surface Mount Compatib                                      | le (SMC)            | Yes  |  |   |
| Tomporaturo Pango Op  | · · · ·             | 55° to 1105°C  |  |   |

Yes -55° to +105°C Through Hole - Compliant Pin

| Electrical   |                   |  |  |
|--|-------------------|--|--|
| Current - Maximum per Contact                      | 1.0A              |  |  |
| Data Rate  | 1.0 Gbps          |  |  |
| Real Signals (per 25mm)                            | 75                |  |  |
| Shielded   | No                |  |  |
| Voltage - Maximum                                  | 250V AC           |  |  |
| Solder Process Data<br>Lead-freeProcess Capability | N/A               |  |  |
| Material Info                                      |                   |  |  |
| Reference - Drawing Numbers                        |                   |  |  |
| Packaging Specification                            | PK-70873-0818-001 |  |  |
| Product Specification                              | PS-73670-9999-001 |  |  |
|  |                   |  |  |

Sales Drawing

PS-73670-9999-001 SDA-73642-XXXX-001, SDA-73642-XXXX-002

## This document was generated on 12/13/2021 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for High Speed/Modular Connectors category:

Click to view products by Molex manufacturer:

Other Similar products are found below :

650827-1 74040-1346 1410191-1 1410337-1 1410368-3 1410964-2 1410326-3 1410367-3 1410971-4 1467833-1 2000877-1 2000878-1 2041314-1 2065387-1 2187307-1 163P 1934290-1 2000875-1 2065917-1 2102736-2 FSR-40 2169868-2 22354-8 437-5040-000 5- 1393565-0 039-0246-000 0761601016 0784461022 10123159-12ELF 030-2415-003/100 PK 030-7380-004 030-2494-001 532939-1 5532901-3 3-1469268-7 74748-102LF 73670-0247 10041743-101LF 10066670-100002LF 1-533915-1 249-4515-000 7-1469373-3 DL2- 2J/S 2000713-8 2000713-7 10124313-101LF 3011-21 757105208 EBTF-4-10-2.0-S-RA-1 430305-001