

## This document was generated on 07/31/2021 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:	<u>0736441007</u>		~
Status:	Active		
Overview:HDM Backplane CoDescription:HDM Board-to-Board		nnector System d Backplane Header, Vertical, SMC, Press-Fit, Guide Post Location sition D, 144 Circuits, Mating Length 5.00mm	
Documents:			
<u>3D Model</u>		Packaging Specification PK-70873-0818-001 (PDF)	
<u>Drawing (PDF)</u>		RoHS Certificate of Compliance (PDF)	
<u>3D Model (PDF)</u>			Series image Deference only
Agency Certificat	tion		Series image - Reference only
CSA		LR19980	EU ELV
UL		E29179	Not Reviewed
General			EU RoHS China RoHS
Product Family		Backplane Connectors	Not Reviewed
Series		<u>73644</u>	REACH SVHC
Application		Backplane	Not Reviewed
Comments		Standard Press-Fit	Halogen-Free
Component Type		PCB Header	<u>Status</u>
Overview		HDM Backplane Connector System	Not Reviewed
Product Name		HDM	For more information, please visit Contact L
UPC		800755023046	
			China ROHS Not Reviewed
Physical			ELV Not Reviewed
Circuits (Loaded)		144	RoHS Phthalates Not Reviewed
Circuits (maximum)		144	
Color - Resin		Black, Natural	
Durability (mating cycles max)		250	Connete Dente in this Conice
First Mate / Last Break		No	Search Parts in this Series
Flammability		94V-0	73644 Series
Guide to Mating Part		Yes	
Keying to Mating Part		Yes	Mates With
Material - Metal		Phosphor Bronze, Stainless Steel	73632 HDM+ Board-to-Board Daughterca
Material - Plating Mating		Gold	Receptacle. <u>73780</u> HDM Board-to-Board
Material - Plating Termination		Gold	Daughtercard Receptacle
Material - Resin		High Temperature Thermoplastic	
Number of Columns		24	Application Tooling   FAQ
Number of Pairs		Open Pin Field	Tooling specifications and manuals are
Number of Rows		6	found by selecting the products below.
Orientation		Vertical	Crimp Height Specifications are then
PC Tail Length		3.50mm	contained in the Application Tooling
PCB Locator		No	Specification document.
PCB Retention		Yes	Global
PCB Thickness - Recommended		2.50mm	Description Product #
Packaging Type		Tube	I L
Pitch - Mating Interface		2.00mm	Extraction Tool <u>621001000</u>
Pitch - Termination		2.00mm	
Plating min - Matin		0.762µm	
		0.051µm	
Plating min - Term Polarized to PCB	ination	•	
		No	
Stackable	montible (CMC)	Yes	
Surface Mount Co			
Temperature Rang	ye - Operating	-55° to +105°C	

Temperature Range - Operating Termination Interface: Style

## Electrical

Current - Maximum per Contact Data Rate Real Signals (per 25mm) Shielded Voltage - Maximum

**Material Info** 

**Reference - Drawing Numbers** 

Packaging Specification Sales Drawing PK-70873-0818-001 SDA-73644-XXXX

1.0A

75

No

1.0 Gbps

250V AC

## This document was generated on 07/31/2021 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for High Speed/Modular Connectors category:

Click to view products by Molex manufacturer:

Other Similar products are found below :

650827-1 74040-1346 1410191-1 1410337-1 1410368-3 1410964-2 1410326-3 1410367-3 1410971-4 1467833-1 2000877-1 2000878-1 2041314-1 2065387-1 2187307-1 163P 1934290-1 2000875-1 2065917-1 2102736-2 FSR-40 2169868-2 22354-8 437-5040-000 5- 1393565-0 039-0246-000 0761601016 0784461022 10123159-12ELF 030-2415-003/100 PK 030-7380-004 030-2494-001 532939-1 5532901-3 3-1469268-7 74748-102LF 73670-0247 10041743-101LF 10066670-100002LF 1-533915-1 249-4515-000 7-1469373-3 DL2- 2J/S 2000713-8 2000713-7 10124313-101LF 3011-21 757105208 EBTF-4-10-2.0-S-RA-1 430305-001