

Surface Mount Compatible (SMC) Temperature Range - Operating Termination Interface: Style

This document was generated on 09/27/2021 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:	0737801255		AD DOM DA	
Status:				2000
	Active			COST AND A
Overview:		DM Backplane Connector System		
Description:		HDM Board-to-Board Daughtercard Receptacle, Vertical, Signal Module, 144 Circuits,		REPERSE
	Mounted Height 15	.00mm, Pin Length 3.50mm, Solder Tail	1 March 1	
			ALL AL	qe - Reference only
Documents:				
<u>3D Model</u>		Product Specification PS-73780-999-001 (PDF)		
<u>3D Model (PDF)</u>		RoHS Certificate of Compliance (PDF)		
Drawing (PDF)				
			Series ima	ge - Reference only
Agency Certification	on			
UL		E29179	EU ELV	
			Not Relevant	
General		De chalen e Compostere		
Product Family		Backplane Connectors	EU RoHS	China RoHS
Series		73780	Compliant	
Application		Daughtercard, Mezzanine	REACH SVHC	
Comments		Solder Tail	Not Contained Per	
Component Type		PCB Receptacle	D(2020)9139-DC	(19
Overview		HDM Backplane Connector System	Jan 2021)	
Product Name		HDM	Halogen-Free	
UPC		822348038732	<u>Status</u>	
Physical			Low-Halogen	
Circuits (Loaded)		144	For more informat	ion, please visit <u>Contact US</u>
Circuits (maximum)		144	China ROHS	Croop Imaga
Color - Resin		Black	ELV	Green Image Not Relevant
Durability (mating cycles max)		250	RoHS Phthalates	Not Contained
First Mate / Last Break		No		Not Contained
Flammability		94V-0		
Guide to Mating Part		No		
Keying to Mating Part		None	Search Parts in this Series	
Material - Metal		Copper-Nickel-Tin	73780 Series	
Material - Plating Mating		Gold		
Material - Plating Termination		Tin	Mates With	
Material - Resin		High Temperature Thermoplastic	HDM Board-to-E	Board Backplane Header
Net Weight		20.030/g	<u>73642</u> , <u>73643</u> ,	<u>73644</u> , <u>73942</u> , <u>73943</u> ,
Number of Columns		24	<u>73944</u> , <u>7</u> 4349,	74428. HDM Board-to-
Number of Pairs		Open Pin Field	Board Stacking	Header <u>73769</u> , <u>73770</u> ,
Number of Rows		6	<u>73782</u> , <u>73783</u> ,	73771
Orientation		Vertical	, -	
PC Tail Length		3.50mm		
PCB Locator		No		
PCB Retention		None		
PCB Thickness - Recommended		1.60mm		
Packaging Type		Tube		
Pitch - Mating Interface		2.00mm		
Pitch - Termination Interface		2.00mm		
Plating min - Mating		0.762µm		
Plating min - Termination		2.540µm		
Polarized to PCB		No		
Stackable		Yes		
Surface Mount Com	anotible (CMC)	Voo		

Yes

-55° to +105°C Through Hole

Electrical Current - Maximum per Contact Data Rate Real Signals (per 25mm) Shielded Voltage - Maximum	15.0A, 1.0A 1.0 Gbps 75 No 250V AC			
Solder Process Data Duration at Max. Process Temperature (seconds) Lead-freeProcess Capability Max. Cycles at Max. Process Temperature Process Temperature max. C	005 WAVE 001 260			
Material Info				
Reference - Drawing Numbers Product Specification Sales Drawing	PS-73780-999-001 SD-73780-004-001			

This document was generated on 09/27/2021 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Board to Board & Mezzanine Connectors category:

Click to view products by Molex manufacturer:

Other Similar products are found below :

Molex