

Real Signals (per 25mm)

Voltage - Maximum

## This document was generated on 12/13/2019 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Status:AOverview:HIDescription:HI		Bystem he Header, Vertical SMC, Press-Fit, Slide On Housing, Post Location B, Polarizing Key Position N/A, 144 Circuits		
Documents: <u>3D Model</u> Drawing (PDF)		<u>3D Model (PDF)</u> RoHS Certificate of Compliance (PDF)		
			Series imag	 e - Reference only
Agency Certification CSA		LR19980	Series inage	
UL		E29179	EU ELV	
OL		223179	Not Relevant	
General			NOT Relevant	
Product Family		Backplane Connectors	EU RoHS	China RoHS
Series		73810	Compliant	
Application		Midplane	REACH SVHC	
Comments		Polar/Guide Version, Polar/Guide Version	Not Contained Per -	
Component Type		PCB Header	ED/71/2019 (16 July	
Overview		HDM Backplane Connector System	2019)	•
Product Name		HDM	Halogen-Free	
UPC		800755030570	Status	
61.6		00070000070	Low-Halogen	
Physical			· · · · · · · · · · · · · · · · · · ·	n places visit Centest LIC
Circuits (Loaded)		N/A	For more informatio	n, please visit <u>Contact US</u>
Circuits (maximum)		144	China ROHS	Green Image
Color - Resin		Black	ELV	Not Relevant
Durability (mating cycles r	nax)	250	RoHS Phthalates	Not Contained
First Mate / Last Break	nux)	No		Not Contained
Flammability		94V-0		
Guide to Mating Part		Yes		
Keying to Mating Part		None	Search Parts in this Series	
Material - Metal		Stainless Steel	73810 Series	
		N/A		
Material - Plating Mating			Mates With	
Material - Resin		High Temperature Thermoplastic		rd-to-Board Daughtercard
Net Weight		5.714/g 24		0 HDM Board-to-Board
Number of Columns			Daughtercard Rec	
Number of Pairs		Open Pin Field		
Number of Rows		6 Vertical		
Orientation		Vertical		
PC Tail Length		5.55mm		
PCB Locator		No		
PCB Retention		None		
Packaging Type				
Pitch - Mating Interface		2.00mm		
Pitch - Termination Interfa	ice	2.00mm		
Polarized to PCB		N/A		
Stackable	(0140)	Yes		
Surface Mount Compatible		Yes		
Temperature Range - Ope	erating	-55° to +105°C		
Electrical				
Current - Maximum per Co	ontact	1.0A		
Data Rate	ondot	1.0 Gbps		
Real Signals (per 25mm)		0		

0

250V AC

Solder Process Data Lead-freeProcess Capability Process Temperature max. C

REFLOW 260

## **Material Info**

**Reference - Drawing Numbers** Sales Drawing

SD-73810-001

## This document was generated on 12/13/2019 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for High Speed/Modular Connectors category:

Click to view products by Molex manufacturer:

Other Similar products are found below :

650827-1 74040-1346 1410191-1 1410337-1 1410368-3 1410964-2 1410326-3 1410367-3 1410971-4 1467833-1 2000877-1 2000878-1 2041314-1 2065387-1 2187307-1 163P 1934290-1 2000875-1 2065917-1 2102736-2 FSR-40 2169868-2 22354-8 437-5040-000 5- 1393565-0 039-0246-000 0761601016 0784461022 10123159-12ELF 030-2415-003/100 PK 030-7380-004 030-2494-001 532939-1 5532901-3 3-1469268-7 74748-102LF 73670-0247 10041743-101LF 10066670-100002LF 1-533915-1 249-4515-000 7-1469373-3 DL2- 2J/S 2000713-8 2000713-7 10124313-101LF 3011-21 757105208 EBTF-4-10-2.0-S-RA-1 430305-001