

This document was generated on 12/13/2019 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: Status: Overview: Description:		o <u>r System</u> blane Header, Vertical SMC, Press-Fit, Slide On Housing, le Post Location A, Polarizing Key Position N/A, 144 Circuits	
Documents: <u>3D Model</u> 3D Model (PDF)		Drawing (PDF) RoHS Certificate of Compliance (PDF)	
Agency Certification			Series image - Reference only
CSA		LR19980	
UL		E29179	EUELV
02		220110	Not Relevant
General			Not Nelevant
Product Family		Backplane Connectors	EU RoHS China RoHS
Series		<u>73810</u>	Compliant
Application		Midplane	REACH SVHC
Comments		Polar/Guide Version, Polar/Guide Version	Not Contained Per -
Component Type		PCB Header	ED/71/2019 (16 July
Overview		HDM Backplane Connector System	2019)
Product Name		HDM	Halogen-Free
UPC		800755030587	Status
			Low-Halogen
Physical			For more information, please visit Contact US
Circuits (Loaded)		N/A	
Circuits (maximum)		144	China ROHS Green Image
Color - Resin		Black	ELV Not Relevant
Durability (mating cycle		250	RoHS Phthalates Not Contained
First Mate / Last Break		No	
Flammability		94V-0	
Guide to Mating Part		Yes	Search Parts in this Series
Keying to Mating Part		None	<u>73810</u> Series
Material - Metal		Stainless Steel	<u>13010</u> Selles
Material - Plating Matin	Ig	N/A	
Material - Resin		High Temperature Thermoplastic	Mates With
Net Weight		5.714/g	73632 HDM+ Board-to-Board Daughtercard
Number of Columns		24	Receptacle. <u>73780</u> HDM Board-to-Board
Number of Pairs		Open Pin Field	Daughtercard Receptacle
Number of Rows		6	
Orientation		Vertical	
PC Tail Length		5.55mm	
PCB Locator		No	
PCB Retention		None	
Packaging Type			
Pitch - Mating Interface		2.00mm	
Pitch - Termination Inte	enace	2.00mm	
Polarized to PCB		N/A Xaa	
Stackable	tible (SMC)	Yes	
Surface Mount Compare		Yes	
Temperature Range - 0	operating	-55° to +105°C	
Electrical			
Current - Maximum per	r Contact	1.0A	
Data Rate		1.0 Gbps	

Real Signals (per 25mm) Voltage - Maximum

250V AC

Solder Process Data Lead-freeProcess Capability Process Temperature max. C

REFLOW 260

Material Info

Reference - Drawing Numbers Sales Drawing

SD-73810-001

This document was generated on 12/13/2019 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for High Speed/Modular Connectors category:

Click to view products by Molex manufacturer:

Other Similar products are found below :

650827-1 74040-1346 1410191-1 1410337-1 1410368-3 1410964-2 1410326-3 1410367-3 1410971-4 1467833-1 2000877-1 2000878-1 2041314-1 2065387-1 2187307-1 163P 1934290-1 2000875-1 2065917-1 2102736-2 FSR-40 2169868-2 22354-8 437-5040-000 5-1393565-0 039-0246-000 0740618502 0761601016 0784461022 10123159-12ELF 030-2415-003/100 PK 030-7380-004 030-2494-001 532939-1 5532901-3 3-1469268-7 74748-102LF 73670-0247 10041743-101LF 10066670-100002LF 1-533915-1 249-4515-000 7-1469373-3 DL2-2J/S 2000713-8 2000713-7 10124313-101LF 3011-21 757105208 EBTF-4-10-2.0-S-RA-1