

Temperature Range - Operating

This document was generated on 08/27/2018 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:	0740571002		
Status: Active			
		actor Sustana	
		oard-to-Board Backplane Header, 2.00mm Pitch, Vertical, 6-	
		dule, 60 Circuits, 10 Columns, Pin Length 6.25mm, 0.76µm	
		074 Enables designers to create custom loaded connectors	
	utilizing standard pin le	ngths 4.25, 4.75, 5.15 and 6.25mm	
Documents:			
3D Model		Packaging Specification PK-74057-003 (PDF)	The second se
Drawing (PDF) RoHS Certificate of Compliance (PDF)			Series image - Reference only
	PS-74031-999-001 (PDF		Series image Therefore emy
<u>Floduct Specification</u>	<u>IF 3-74031-333-001 (F DI</u>	1	
			EU ELV
Agency Certification	n		Not Relevant
UL		E29179	
0			EU RoHS China RoHS
General			Compliant
Product Family		Backplane Connectors	REACH SVHC
Series		74057	Not Contained Per -
Application		Backplane	ED/61/2018 (27 June
Application Tooling Documents		TM-622010999	2018)
Comments		Open Header	Halogen-Free
Component Type		PCB Header	Status
Overview		VHDM Backplane Connector Systems	Low-Halogen
Product Name		VHDM	Need more information on product
UPC		800754780353	environmental compliance?
			environmental compliance.
Physical			Email productcompliance@molex.com
Circuits (Loaded)		60	Please visit the Contact Us section for any
Circuits (maximum)		60	non-product compliance questions.
Color - Resin		Black	
Durability (mating cyc	cles max)	200	China ROHS Green Image
First Mate / Last Brea		No	ELV Not Relevant
Flammability		94V-0	RoHS Phthalates Not Contained
Guide to Mating Part		No	
Keying to Mating Part		None	
Material - Metal		Beryllium Copper, High Performance Alloy (HPA)	
Material - Plating Mating		Gold	Search Parts in this Series
Material - Plating Termination		Matte Tin	<u>74057</u> Series
Material - Resin	mination	High Temperature Thermoplastic	
			Mates With
Net Weight		4.418/g	74030 VHDM Board-to-Board Daughtercard
Number of Columns		10 Open Din Field	Receptacle
Number of Pairs		Open Pin Field	
Number of Rows			
Orientation		Vertical	
PC Tail Length		2.50mm	
PCB Locator		No	
PCB Retention		None	
PCB Thickness - Rec	commended	1.80mm	
Packaging Type		Tube	
Pitch - Mating Interfac	се	2.00mm	
Pitch - Termination In	nterface	1.00mm	
Plating min - Mating		0.762µm	
Plating min - Termina	ation	0.762µm	
Polarized to PCB		Yes	
Surface Mount Comp	atible (SMC)	Yes	
Temperature Range		105°C	

105°C

Termination Interface: Style

Electrical Current - Maximum per Contact Data Rate Shield Type Shielded Voltage - Maximum

Material Info

Reference - Drawing Numbers Packaging Specification Product Specification Sales Drawing Through Hole - Compliant Pin

2.0A 3.125 Gbps Ground Plane Shield Yes 120V AC (RMS)/DC

PK-74057-003 PS-74031-999-001 SD-74057-002

This document was generated on 08/27/2018 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for High Speed/Modular Connectors category:

Click to view products by Molex manufacturer:

Other Similar products are found below :

650827-1 74040-1346 1410191-1 1410337-1 1410368-3 1410964-2 1410326-3 1410367-3 1410971-4 1467833-1 2000877-1 2000878-1 2041314-1 2065387-1 2187307-1 163P 1934290-1 2000875-1 2065917-1 2102736-2 FSR-40 2169868-2 22354-8 437-5040-000 5-1393565-0 039-0246-000 0740618502 0761601016 0784461022 10123159-12ELF 030-2415-003/100 PK 030-7380-004 030-2494-001 532939-1 5532901-3 3-1469268-7 74748-102LF 73670-0247 10041743-101LF 10066670-100002LF 1-533915-1 249-4515-000 7-1469373-3 DL2-2J/S 2000713-8 2000713-7 10124313-101LF 3011-21 757105208 EBTF-4-10-2.0-S-RA-1