

This document was generated on 09/21/2021

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: 0740591001

Status: Active

Overview: VHDM Backplane Connector Systems

Description: VHDM Single-Ended Board-to-Board Backplane Header, 2.00mm Pitch, Vertical, 6

Rows, Guide Pin Signal Module, Shield End Version, 60 Circuits, 10 Columns, Pin

Length 4.75mm

Documents:

3D Model Product Specification PS-74031-999-001 (PDF)

Drawing (PDF)

RoHS Certificate of Compliance (PDF)

3D Model (PDF)

Agency Certification

UL E29179

General

Product Family Backplane Connectors

Series <u>74059</u> Application Backplane

Application Tooling Documents

Comments

Component Type

TM-622010999-001

No Keying Position

PCB Header

Overview VHDM Backplane Connector Systems

Product Name VHDM

UPC 800754780711

Physical

Keying to Mating Part

Circuits (Loaded) 60
Circuits (maximum) 60
Color - Resin Black
Durability (mating cycles max) 200
First Mate / Last Break No
Flammability 94V-0
Guide to Mating Part Yes

Material - Metal Beryllium Copper, High Performance Alloy (HPA),

Stainless Steel

Material - Plating Mating Gold
Material - Plating Termination Matte Tin

Material - Resin High Temperature Thermoplastic

Net Weight 7.200/g Number of Columns 10

Number of Pairs Open Pin Field

Number of Rows 6 Orientation Vertical PC Tail Length 2.50mm **PCB** Locator No **PCB** Retention None PCB Thickness - Recommended 1.80mm Packaging Type Tube Pitch - Mating Interface 2.00mm Pitch - Termination Interface 1.00mm

Polarized to PCB Yes Surface Mount Compatible (SMC) Yes

Temperature Range - Operating -55° to +105°C

Termination Interface: Style Through Hole - Compliant Pin



Series image - Reference only

EU ELV

Not Relevant

EU RoHS China RoHS

Compliant REACH SVHC Not Contained Per -D(2021)4569-DC (8 July 2021)

Halogen-Free

Status

Low-Halogen

For more information, please visit Contact US

China ROHS Green Image
ELV Not Relevant
RoHS Phthalates Not Contained

Search Parts in this Series

74059 Series

Mates With

74030 VHDM Board-to-Board Daughtercard

Receptacle

Application Tooling | FAQ

Tooling specifications and manuals are found by selecting the products below. Crimp Height Specifications are then contained in the Application Tooling Specification document.

Global

DescriptionProduct #Signal Pin Inserter622015700

Repair Tool

6-Row Pin and <u>622015800</u>

Shield Repair Tool

6-Row Shield 622016000

Extraction Tool

Electrical

Current - Maximum per Contact 2.0A
Data Rate 3.125 Gbps

Shield Type Ground Plane Shield

Shielded

Voltage - Maximum 120V AC (RMS)/DC

Solder Process Data

Lead-freeProcess Capability N/A

Material Info

Reference - Drawing Numbers

Product Specification PS-74031-999-001 Sales Drawing SD-74059-002-001

This document was generated on 09/21/2021

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for High Speed/Modular Connectors category:

Click to view products by Molex manufacturer:

Other Similar products are found below:

650827-1 74040-1346 1410191-1 1410337-1 1410368-3 1410964-2 1410326-3 1410367-3 1410971-4 1467833-1 2000877-1 2000878-1 2041314-1 2065387-1 2187307-1 163P 1934290-1 2000875-1 2065917-1 2102736-2 FSR-40 2169868-2 22354-8 437-5040-000 5-1393565-0 039-0246-000 0761601016 0784461022 10123159-12ELF 030-2415-003/100 PK 030-7380-004 030-2494-001 532939-1 5532901-3 3-1469268-7 74748-102LF 73670-0247 10041743-101LF 10066670-100002LF 1-533915-1 249-4515-000 7-1469373-3 DL2-2J/S 2000713-8 2000713-7 10124313-101LF 3011-21 757105208 EBTF-4-10-2.0-S-RA-1 430305-001