

This document was generated on 09/21/2021 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: 07	40602504		
	tive		
		r Svetome	and the second se
Description: VH	<u>VHDM Backplane Connector Systems</u> VHDM Single-Ended Board-to-Board Backplane Header, 2.00mm Pitch, Vertical, 8 Rows, Open Signal Module, 200 Circuits, 25 Columns, Pin Length 5.15mm		
Documents:			
<u>3D Model (PDF)</u>		Product Specification PS-74031-999-001 (PDF)	
Drawing (PDF)		Packaging Specification PK-74060-003-001 (PDF)	
<u>3D Model</u>		RoHS Certificate of Compliance (PDF)	
A nonov Contification			Series image - Reference only
Agency Certification		E29179	EU ELV
		220110	Not Relevant
General Product Family		Backplane Connectors	EU RoHS China RoHS
Series		74060	
			Compliant
Application	anta	Backplane	REACH SVHC
Application Tooling Docum	ents	TM-622010999-001	Not Contained Per -
Comments		Open Header	D(2021)4569-DC (8
Component Type		PCB Header	July 2021)
Overview		VHDM Backplane Connector Systems	Halogen-Free
Product Name		VHDM	<u>Status</u>
UPC		800753260047	Low-Halogen
Physical			For more information, please visit Contact
Circuits (Loaded)		200	China ROHS Green Image
Circuits (maximum)		200	ELV Not Relevant
Color - Resin		Black	RoHS Phthalates Not Contained
Durability (mating cycles m	ax)	200	
First Mate / Last Break	,	No	
Flammability		94V-0	
Guide to Mating Part		No	Search Parts in this Series
Keying to Mating Part		None	74060 Series
Material - Metal		Beryllium Copper, High Performance Alloy (HPA)	
Material - Plating Mating		Gold	Mates With
Material - Plating Terminati	an	Matte Tin	74040 VHDM Board-to-Board Daughter
	511		Receptacle
Material - Resin		High Temperature Thermoplastic	Receptacie
Net Weight		13.630/g	
Number of Columns		25 Decembra Field	Application Tooling FAQ
Number of Pairs		Open Pin Field	Tooling specifications and manuals are
Number of Rows		ð Mæthal	found by selecting the products below.
Orientation		Vertical	Crimp Height Specifications are then
PC Tail Length		2.50mm	contained in the Application Tooling
PCB Locator		No	Specification document.
PCB Retention		None	Global
PCB Thickness - Recomme	ended	1.80mm	Description Product #
Packaging Type		Tube	Signal Pin Inserter 622015700
Pitch - Mating Interface		2.00mm	Repair Tool
Pitch - Termination Interfac	e	1.00mm	8-Row Pin and 622015900
Plating min - Mating		0.762µm	Shield Repair Tool
Plating min - Termination		0.762µm	8-Row Shield <u>622016100</u>
Polarized to PCB		Yes	Extraction Tool
Surface Mount Compatible	(SMC)	Yes	
Temperature Range - Oper		-55° to +105°C	
Termination Interface: Style		Through Hole - Compliant Pin	

Electrical

Current - Maximum per Contact Data Rate Shield Type Shielded Voltage - Maximum

Material Info

Reference - Drawing Numbers

Packaging Specification Product Specification Sales Drawing PK-74060-003-001 PS-74031-999-001 SD-74060-002-001

Ground Plane Shield

120V AC (RMS)/DC

3.0A

Yes

3.125 Gbps

This document was generated on 09/21/2021 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for High Speed/Modular Connectors category:

Click to view products by Molex manufacturer:

Other Similar products are found below :

650827-1 74040-1346 1410191-1 1410337-1 1410368-3 1410964-2 1410326-3 1410367-3 1410971-4 1467833-1 2000877-1 2000878-1 2041314-1 2065387-1 2187307-1 163P 1934290-1 2000875-1 2065917-1 2102736-2 FSR-40 2169868-2 22354-8 437-5040-000 5-1393565-0 039-0246-000 0740618502 0761601016 0784461022 10123159-12ELF 030-2415-003/100 PK 030-7380-004 030-2494-001 532939-1 5532901-3 3-1469268-7 74748-102LF 73670-0247 10041743-101LF 10066670-100002LF 1-533915-1 249-4515-000 7-1469373-3 DL2-2J/S 2000713-8 2000713-7 10124313-101LF 3011-21 757105208 EBTF-4-10-2.0-S-RA-1