

Temperature Range - Operating

Termination Interface: Style

This document was generated on 08/18/2014 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:	74320-9000		
Status:	Active		
		ctors and Cable Assemblies	HILLING WAR
Description:		Digital Visual Interface, PCB Receptacle, Panel Mount, Through	
Description.		ed Metal Pins, Right Angle, 0.76µm Gold (Au), 2.34mm Solder	
		ble, 4-40 Thread, 24 Circuits, Lead-Free	Connert and a marked of the
Documents:			
Drawing (PDF)		Test Summary TS-74320-001 (PDF)	
Product Specification PS-74320-001 (PDF)		RoHS Certificate of Compliance (PDF)	Serie
			image - Reference only
Agency Certific	cation		
UL		E29179	EU RoHS China RoHS
-			ELV and RoHS
General			Compliant
Product Family		I/O Connectors	REACH SVHC
Series		<u>74320</u>	Contains SVHC: No
Application		Wire-to-Board	Low-Halogen Status
Comments		DDWG (Digital Display Working Group) Standard	Not Low-Halogen
Component Type		Receptacle	Need more information on product
Overview		MicroCross [™] DVI Connectors and Cable Assemblies	environmental compliance?
Product Name		MicroCross™DVI	environmental compliance?
Туре		N/A	Email productcompliance@molex.com
UPC		800754773201	For a multiple part number RoHS Certificate
			Compliance, click here
Physical			
Boot Color		N/A	Please visit the <u>Contact Us</u> section for any
Circuits (Loaded)		24	non-product compliance questions.
Circuits (maximum)		24	
Color - Resin		Natural	
Durability (mating cycles max)		100	
Flammability		94V-0	Search Parts in this Series
Gender		Receptacle	<u>74320</u> Series
Keying to Mating Part		Yes	
Lock to Mating Part		Yes	Mates With
Material - Metal		Copper Alloy	<u>88744</u> , <u>74323</u>
Material - Plating M	-	Gold	
Material - Plating Termination		Tin	Use With
Net Weight		6.264/g	71781 Panel Mount Hex Screw Kit
Number of Rows		3 Diskt Assels	
Orientation		Right Angle	
PC Tail Length		2.34mm	
PCB Locator		Yes	
PCB Retention		Yes	
Packaging Type		Tray	
Panel Mount		Yes	
Pitch - Mating Inter		1.90mm	
Pitch - Termination Interface		1.90mm	
Plating min - Mating		0.762µm	
Plating min - Termination		2.540µm	
Polarized to Mating Part		Yes	
Polarized to PCB		Yes	
Ports Surface Mount Con	nnatible (CMC)	I No	
Surface Mount Con	,	No -20° C to $\pm 85^{\circ}$ C	

-20°C to +85°C

Through Hole

Waterproof / Dustproof Wire Size AWG	No N/A			
Electrical Current - Maximum per Contact Grounding to Panel Shield Type Shielded Voltage - Maximum	3A Yes Full Shield Yes 40V AC (RMS)			
Material Info				
Reference - Drawing Numbers Product Specification	PS-74320-001			

Sales Drawing Test Summary

This document was generated on 08/18/2014 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

SD-74320-009 TS-74320-001

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for HDMI, Displayport & DVI Connectors category:

Click to view products by Molex manufacturer:

Other Similar products are found below :

<u>1775247-3</u> <u>2-1932649-5</u> <u>30-1231</u> <u>30-528</u> <u>2069485-1</u> <u>30-504</u> <u>30-519</u> <u>30-542</u> <u>47648-2000</u> <u>2002-400</u> <u>769-103/021-000</u> <u>1932649-1</u> <u>233-</u> <u>368NFG6-17NH</u> <u>PJ-210A</u> <u>PJ-35825</u> <u>6321-026RDS1MWA02</u> <u>FDB0901-M0DB300K6KF</u> <u>3VD51203-3D6A-7H</u> <u>DV11201-H5R6-4F</u> <u>RPI-</u> <u>16337</u> <u>CC-MDPM-VGAM-6</u> <u>RPI-16338</u> <u>CCB-HDMIL-1.5M</u> <u>CCB-HDMIL-1M</u> <u>CCB-HDMIL-2M</u> <u>CCB-HDMIL-3M</u> <u>CCB-HDMIL-5M</u> <u>CCB-HDMIL-5M</u> <u>CCB-HDMIL-1M</u> <u>CCBP-HDMI-3M</u> <u>CCBP-HDMI-5M</u> <u>CCB-HDMIL-5M</u> <u>CCBP-HDMI-10M</u> <u>CCBP-HDMI-1M</u> <u>CCBP-HDMI-2M</u> <u>CCBP-HDMI-5M</u> <u>CCBP-HDMI-7.5M</u> <u>CCBP-HDMI-7.5M</u> <u>CCBP-HDMI8K-1M</u> <u>CCBP-HDMI8K-2M</u> <u>CCBP-HDMI8K-3M</u> <u>AK-AV-02</u> <u>AK-AV-03</u> <u>AK-AV-05</u> <u>AK-AV-11</u> <u>AK-AV-13</u> <u>AK-AV-15</u> <u>CCP-MDP2-6</u> <u>CCP-MDP2-6</u> <u>AK-HD-05A</u> <u>AK-HD-100A</u> <u>AK-HD-15A</u> <u>AK-HD-15P</u>