

This document was generated on 08/02/2017 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:	<u>0743232003</u>		
Status:	Active		141A - 257
Overview: Description:	MicroCross [™] DVI Connectors and Cable Assemblies MicroCross [™] DVI Digital Dual Link Component, High Volume Plug Connector Sub- assembly, Vertical, Gold (Au) Flash, with key, 24 Circuits, Lead-Free		
Documents:		RoHS Certificate of Compliance (PDF)	
Agency Certification			
CSA		LR19980	Series image - Reference only
UL		E29179	
Conoral			EU ELV
General Broduct Family		I/O Connectors	Not Relevant
Product Family		74323	
Series		<u>74323</u> Wire-to-Board	EU RoHS China RoHS
Application			Compliant
Comments		DDWG (Digital Display Working Group) Standard	REACH SVHC
Component Type		I/O Plug Connector Subassembly	Not Contained Per -
Electrical Model		Yes	ED/30/2017 (7 July
Overview		MicroCross™ DVI Connectors and Cable Assemblies	2017)
Product Name		MicroCross™DVI	Halogen-Free
Туре		N/A	<u>Status</u>
UPC		800754826013	Not Low-Halogen
Dhusiaal			Need more information on product
Physical Dest Oaler		N1/A	environmental compliance?
Boot Color		N/A	
Circuits (Loaded)		24	Email productcompliance@molex.com
Circuits (maximum)		24	Please visit the <u>Contact Us</u> section for any
Circuits Detail		Circuits 1-24 are loaded; with key	non-product compliance questions.
Color - Resin		Black	
Durability (mating cycles max)		100	China ROHS Green Image
Flammability		94V-0	ELV Not Relevant
Keying to Mating Part		Yes	RoHS Phthalates Not Contained
Lock to Mating Part		Yes	
Material - Metal		Copper Alloy	
Material - Plating Mating		Gold	Search Parts in this Series
Material - Plating Termination		Tin	74323 Series
Material - Resin		High Temperature Thermoplastic	
Net Weight		7.420/g	Mates With
Number of Rows		3	
Orientation		Vertical	Other Receptacle components, <u>74320</u> DV Receptacle, 67351 DVI Receptacle
PCB Retention		None	
Packaging Type		Tray	
Panel Mount		N/A	Application Tooling FAQ
Pitch - Mating Interface		1.90mm, 2.54mm	Tooling specifications and manuals are
Pitch - Termination Interface		1.90mm, 2.54mm	found by selecting the products below.
Plating min - Mating		0.254µm	Crimp Height Specifications are then
Plating min - Termination		3.810µm	contained in the Application Tooling
Polarized to Mating Part		Yes	Specification document.
Polarized to PCB		Yes	Global
Ports		1	Description Product #
Temperature Range -	Operating	-20°C to +85°C	Soldering Fixture 0621003700
Termination Interface:		Solder or Weld	
Waterproof / Dustproo		No	
Wire Size AWG		N/A	

Electrical	
Current - Maximum per Contact	3.0A
Grounding to Panel	Yes
Shield Type	Full Shield
Shielded	Yes
Voltage - Maximum	40V AC (RMS)
Material Info	

Reference - Drawing NumbersElectrical Model DocumentEE-74320-002S-Parameter ModelSP-74320-002Sales DrawingSD-74323-003

This document was generated on 08/02/2017 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for HDMI, Displayport & DVI Connectors category:

Click to view products by Molex manufacturer:

Other Similar products are found below :

<u>1775247-3</u> 2-1932649-5 30-1231 30-528 2069485-1 30-504 30-519 30-542 47648-2000 2002-400 769-103/021-000 1932649-1 233-368NFG6-17NH PJ-210A PJ-35825 3VD51203-3D6A-7H DV11201-H5R6-4F RPI-16337 CC-MDPM-VGAM-6 RPI-16338 CCB-HDMIL-1.5M CCB-HDMIL-1M CCB-HDMIL-2M CCB-HDMIL-3M CCB-HDMIL-5M CCB-HDMIL-7.5M CCBP-HDMI-10M CCBP-HDMI-1M CCBP-HDMI-2M CCBP-HDMI-3M CCBP-HDMI-7.5M CCBP-HDMI8K-1M CCBP-HDMI8K-2M CCBP-HDMI8K-3M AK-AV-02 AK-AV-03 AK-AV-05 AK-AV-11 AK-AV-13 AK-AV-15 CCP-MDP2-6 CCP-MDPMDP2-6 AK-HD-05A AK-HD-100A AK-HD-100P AK-HD-15A AK-HD-15P AK-HD-30A AK-HD-30P 49959