

This document was generated on 10/19/2016

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: 0743370070

Status: **Active**

Ultra+™ VHDCI Interconnects Overview:

0.80mm Pitch Ultra+™ VHDCI Wire-to-Board Receptacle, Stacked, Right Angle, with **Description:**

Enhanced Shield, Version 1 Footprint, 136 Circuits

Documents:

Packaging Specification PK-74337-001 (PDF) 3D Model RoHS Certificate of Compliance (PDF) **Drawing (PDF)**

Product Specification PS-71425-9999 (PDF)

Agency Certification

LR19980 **CSA** UL E29179

General

I/O Connectors **Product Family**

Series 74337 **Application** Wire-to-Board Comments With Top Cover Component Type Receptacle

Ultra+™ VHDCI Interconnects Overview

Product Name SCSI+, VHDCI

Type N/A

UPC 800756610498

Physical

Boot Color N/A Circuits (Loaded) 136 Circuits (maximum) 136 Color - Resin Black Durability (mating cycles max) 500 Flammability 94V-0 Gender Female Lock to Mating Part Yes

Material - Metal **Brass** Material - Plating Mating Tin Material - Plating Termination


Material - Resin High Temperature Thermoplastic

Net Weight 13.970/g Number of Rows

Right Angle Orientation 3.62mm PC Tail Length **PCB** Locator Yes **PCB** Retention Yes PCB Thickness - Recommended 2.36mm Packaging Type Tray Panel Mount No Pitch - Mating Interface 0.80mm Pitch - Termination Interface 0.80mm Plating min - Mating 1.016um Plating min - Termination 1.016um Polarized to Mating Part Yes

Polarized to PCB Yes Ports 2 Surface Mount Compatible (SMC) Yes

Temperature Range - Operating -55°C to +85°C



EU ELV

Not Reviewed

EU RoHS China RoHS

Compliant with Exemption 6(c) REACH SVHC Not Contained Per -

ED/21/2016 (20 June

2016)

Halogen-Free

Status

Not Low-Halogen

Need more information on product environmental compliance?

Email productcompliance@molex.com Please visit the Contact Us section for any non-product compliance questions.

China ROHS 50 Image Not Reviewed **ELV Not Contained RoHS Phthalates**

Search Parts in this Series

74337 Series

Mates With

71425 Ultra+™ VHDCI Plug Kit

Termination Interface: Style Through Hole

Waterproof / Dustproof No Wire Size AWG N/A

Electrical

Current - Maximum per Contact 0.5A
Shield Type Full Shield
Shielded Yes

Voltage - Maximum 30V AC (RMS)/DC

Solder Process Data

Duration at Max. Process Temperature (seconds)

Lead-freeProcess Capability

Max. Cycles at Max. Process Temperature

003

Process Temperature max. C

245

Material Info

Reference - Drawing Numbers

Packaging Specification PK-74337-001 Product Specification PS-71425-9999

Sales Drawing SD-74337-004, SD-74337-014, SD-74337-017

This document was generated on 10/19/2016

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for I/O Connectors category:

Click to view products by Molex manufacturer:

Other Similar products are found below:

571763P 58098-0628 72.250.1628.2 72.250.2428.2 74720-0505 76.350.0729.0 76871-1403 FCN-244F080-G/1 FCN-260A9920 PCR-E36PM PCS-XE26MA+ G38A71314B 1571250010 157-22500-3 MS3471L14-19P L/C 192991-0703 172501-4002 172501-6002 FCN-260C008-A/L0 FCN-260C024-AL0 FCN-261Z008 2000314-1 200331-1 PCR-E36FC+ PCS-E28FS+ PCS-XE26SLFD+ PCS-XE26SLFD+ PCS-XE26SLFD+ G730VID08BDC24 U90B2054081210 UE86K842720321 38113800006 DP3AR020WQ1R200 Z4.102.0680.0 500-1040 500-1052 500-1054 ZP-4008-66L 0709821002 DX40-20P(55) 5554841-1 MS3474W18-8P-LC* U90B3054061110 U65-E04-4020 ZPF0000000000097891 747360449 10099439-003C-TRLF 10137239-0021LF E9320-001-01 10137239-0011LF 70289-001LF