

This document was generated on 09/29/2016 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:	0749812513		AD a
Status:	Active erview: VHDM-HSD™ Backplane Connectors		///MM
Dverview: Description:			
	0.201111		
Documents: Drawing (PDF) Product Specification	PS-74031-999 (PDF)	RoHS Certificate of Compliance (PDF)	Series image - Reference only
Agency Certification	•		EU ELV
CSA	1	LR19980	EU ELV Not Reviewed
General		Destate of Ocean stress	EU RoHS China RoHS
Product Family		Backplane Connectors	Not Reviewed
Series		<u>74981</u>	REACH SVHC
Application		Backplane	Not Reviewed
Application Tooling Documents		TM-622010999	Halogen-Free
Comments		Keying Orientation A	<u>Status</u>
Component Type		PCB Header	Not Reviewed
Overview		VHDM-HSD [™] Backplane Connectors	Need more information on product
Product Name		VHDM-HSD™	environmental compliance?
UPC		822350644631	
			Email productcompliance@molex.com
Physical			Please visit the <u>Contact Us</u> section for any
Circuits (Loaded)		100	non-product compliance questions.
Circuits (maximum)		100	
Color - Resin		Black	China ROHS Not Reviewed
Durability (mating cyc	cles max)	200	ELV Not Reviewed
First Mate / Last Brea		No	
Flammability		94V-0	
Guide to Mating Part		Yes	
Keying to Mating Part		Yes	Search Parts in this Series
Material - Metal	L	Copper-Nickel-Silicon, High Performance Alloy (HPA), Stainless Steel	74981 Series
Motorial Disting Mat	ling	Gold	Mates With
Material - Plating Mat			<u>74880</u> VHDM-HSD™ Daughtercard
Material - Plating Ter	mination	Matte Tin	
Material - Resin		High Temperature Thermoplastic	Use With
Net Weight		11.910/g	
Number of Columns		25	Daughtercard Modules
Number of Pairs		Open Pin Field	
Number of Rows		6	Application Tooling FAQ
Orientation		Vertical	Tooling specifications and manuals are
PC Tail Length		2.50mm	found by selecting the products below.
PCB Locator		No	Crimp Height Specifications are then
PCB Retention		None	contained in the Application Tooling
PCB Thickness - Rec	commended	1.80mm	Specification document.
Packaging Type		Tube	Global
Pitch - Mating Interfa	се	2.00mm	Description Product #
Pitch - Termination Ir		2.00mm	Signal Pin Inserter 0622015700
Plating min - Mating		0.762µm	
Plating min - Termina	ation	0.762µm	Repair Tool
Polarized to PCB		•	Insertion Module <u>0622020217</u>
	atible (CMC)	Yes	Signal Header, 6
Surface Mount Comp		Yes	Row by 25 Wide,
Temperature Range	- Operating	-55°C to +105°C	50.00mm

Termination Interface: Style Through Hole - Compliant Pin Electrical Current - Maximum per Contact 2.0A Data Rate 5.0 Gbps Shielded No Voltage - Maximum 120V AC (RMS)/DC **Material Info Reference - Drawing Numbers** Product Specification PS-74031-999 Sales Drawing SD-74981-010 Note: HDM, HDM+, VHDM, VHDM-HSD and GbX are trademarks or registered trademarks of Amphenol TCS.

> This document was generated on 09/29/2016 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for High Speed/Modular Connectors category:

Click to view products by Molex manufacturer:

Other Similar products are found below :

650827-1 74040-1346 1410191-1 1410337-1 1410368-3 1410964-2 1410326-3 1410367-3 1410971-4 1467833-1 2000877-1 2000878-1 2041314-1 2065387-1 2187307-1 163P 1934290-1 2000875-1 2065917-1 2102736-2 FSR-40 2169868-2 22354-8 437-5040-000 5- 1393565-0 039-0246-000 0761601016 0784461022 10123159-12ELF 030-2415-003/100 PK 030-7380-004 030-2494-001 532939-1 5532901-3 3-1469268-7 74748-102LF 73670-0247 10041743-101LF 10066670-100002LF 1-533915-1 249-4515-000 7-1469373-3 DL2- 2J/S 2000713-8 2000713-7 10124313-101LF 3011-21 757105208 EBTF-4-10-2.0-S-RA-1 430305-001