

This document was generated on 09/29/2016

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: 0752372104

Status: Active

Overview: GbX® Backplane Connector System

Description: 5-Pair GbX® Backplane Connector System, Left Guide Header, 100 Circuits, Gold (Au)

0.76µm, Pin Length 4.55mm

Documents:

<u>3D Model</u> <u>Product Specification PS-75221-999 (PDF)</u>
<u>Drawing (PDF)</u> <u>RoHS Certificate of Compliance (PDF)</u>

Agency Certification

UL E29179

General

Product Family Backplane Connectors

Series 75237
Application Backplane
Application Tooling Documents TM-622022099

Comments Left Guide Header, No Keying Position

Component Type PCB Header

Overview GbX® Backplane Connector System

Product Name GbX®

UPC 822350176453

Physical

Circuits (Loaded) 100
Circuits (maximum) 100
Color Region 100

Color - Resin Gray (Dark)

Durability (mating cycles max)

First Mate / Last Break

No

Flammability

Guide to Mating Part

Keying to Mating Part

Yes

Material - Metal High Performance Alloy (HPA), Stainless Steel

Material - Plating Mating Gold
Material - Plating Termination Tin-Lead

Material - Resin High Temperature Thermoplastic


Net Weight10.087/gNumber of Columns10Number of Pairs5Number of Rows10OrientationVerticalPC Tail Length2.30mmPCB LocatorNoPCR RetentionYes

PCB Retention Yes PCB Thickness - Recommended 1.60mm Packaging Type Tray Pitch - Mating Interface 1.85mm Pitch - Termination Interface 1.85mm Plating min - Mating 0.762µm Plating min - Termination 0.762um Polarized to PCB No Stackable Yes Surface Mount Compatible (SMC) Yes

Temperature Range - Operating

Termination Interface: Style Through Hole - Compliant Pin

105°C



EU ELV Not Relevant

Not Relevant

EU RoHS China RoHS

Compliant REACH SVHC Not Contained Per -ED/21/2016 (20 June

2016)

<u>Halogen-Free</u>

<u>Status</u>

Low-Halogen

Need more information on product environmental compliance?

Email <u>productcompliance@molex.com</u>
Please visit the <u>Contact Us</u> section for any non-product compliance questions.

China ROHS Green Image ELV Not Relevant

Search Parts in this Series

75237 Series

Mates With

75360 GbX® Daughtercard

Application Tooling | FAQ

Tooling specifications and manuals are found by selecting the products below. Crimp Height Specifications are then contained in the Application Tooling Specification document.

Global

Description Product # Single Pin Repair 0622022090

Tool

Shield Removal Tool $\underline{0622022100}$ Insertion Tool, 5-pair $\underline{0622022030}$

by 10-Wide

Insertion Tool, 5-pair 0622022040

by 20-Wide

Electrical

Current - Maximum per Contact 1.0A
Data Rate 8.0 Gbps

Real Signals (per 25mm) 135

Shield Type Ground Plane Shield

Shielded Yes

Voltage - Maximum 120V AC (RMS)/DC

Solder Process Data

Lead-freeProcess Capability N/A

Material Info

Reference - Drawing Numbers

Product Specification PS-75221-999
Sales Drawing SD-75237-210

Note: HDM, HDM+, VHDM, VHDM-HSD and GbX are trademarks or registered trademarks of Amphenol TCS.

This document was generated on 09/29/2016

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for High Speed/Modular Connectors category:

Click to view products by Molex manufacturer:

Other Similar products are found below:

650827-1 74040-1346 1410191-1 1410337-1 1410368-3 1410964-2 1410326-3 1410367-3 1410971-4 1467833-1 2000877-1 2000878-1 2041314-1 2065387-1 2187307-1 163P 1934290-1 2000875-1 2065917-1 2102736-2 FSR-40 2169868-2 22354-8 437-5040-000 5- 1393565-0 039-0246-000 0740618502 0761601016 0784461022 10123159-12ELF 030-2415-003/100 PK 030-7380-004 030-2494-001 532939-1 5532901-3 3-1469268-7 74748-102LF 73670-0247 10041743-101LF 10066670-100002LF 1-533915-1 249-4515-000 7-1469373-3 DL2-2J/S 2000713-8 2000713-7 10124313-101LF 3011-21 757105208 EBTF-4-10-2.0-S-RA-1