

## This document was generated on 09/13/2021 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: Status: Overview: Description:	0754625001 Active SFP+ and SFP Interc Small Form-factor Plu PC Tails, 40 Circuits,	uggable (SFP) Stacked 2-by-1 Multi-Port Connector with Press-fit		
Documents: <u>3D Model</u> <u>3D Model (PDF)</u> <u>Drawing (PDF)</u> Product Specification	PS-75310-001-001 (PE	Application Specification AS-75310-001-001 (PDF)Application Specification AS-76090-001-001 (PDF)Packaging Specification PK-75462-001-001 (PDF)OF)RoHS Certificate of Compliance (PDF)	Series image - Reference only	
Agency Certification	n	LR19980	EU ELV	
UL		E29179	Not Relevant	
UL		E29179	EU RoHS China RoHS	
General			Compliant	
Product Family		I/O Connectors	REACH SVHC	
Series		<u>75462</u>	Not Contained Per -	
Application		Module-to-Board	D(2021)4569-DC (8	
Component Type		Receptacle	July 2021)	
Overview		SFP+ and SFP Interconnect Solutions	Halogen-Free	
Product Name		SFP	Status	
Туре		N/A	Low-Halogen	
UPC		822350234795	For more information, please visit Contact	
Physical			China ROHS Green Image	
Boot Color		N/A	ELV Not Relevant	
Circuits (Loaded)		40	RoHS Phthalates Not Contained	
Circuits (maximum)		40		
Color - Resin		Black		
Durability (mating cycles max)		100	Connete Dente in this Conice	
Flammability		94V-0	Search Parts in this Series	
Gender		Female	75462 Series	
Lock to Mating Part		Yes		
Material - Metal		High Performance Alloy (HPA)	Use With	
Material - Plating Mating		Gold	759510999 SFP Dust Plug	
Material - Plating Ter	mination	Tin		
Material - Resin		High Temperature Thermoplastic	Application Tooling   FAQ	
Net Weight		23.760/g	Tooling specifications and manuals are	
Number of Rows		2	found by selecting the products below.	
Orientation		Right Angle	Crimp Height Specifications are then	
PC Tail Length		2.07mm	contained in the Application Tooling	
PCB Locator		Yes	Specification document.	
PCB Retention		Yes	Global	
PCB Thickness - Rec	commended	2.36mm	Description Product #	
Packaging Type		Tray	Extraction Tool, 2 x 1 622029930	
Panel Mount		No	Medium	
Pitch - Mating Interfa		0.80mm	,	
Pitch - Termination In	iterface	0.80mm		
Plating min - Mating		0.762µm		
Plating min - Termination		0.762µm		
Polarized to Mating F	Part	Yes		
Polarized to PCB		Yes		
Ports		2		
Surface Mount Comp		No		
Temperature Range - Operating		-40° to +85°C		

Termination Interface: Style Waterproof / Dustproof	Through Hole - Compliant Pin No			
<b>Electrical</b> Current - Maximum per Contact Shield Type Shielded Voltage - Maximum	0.5A EMI Fingers Yes 120V AC (RMS)/DC			
Solder Process Data Lead-freeProcess Capability	N/A			
Material Info				
<b>Reference - Drawing Numbers</b> Application Specification Packaging Specification Product Specification Sales Drawing	AS-75310-001-001, AS-76090-001-001 PK-75462-001-001 PS-75310-001-001 SD-75462-100-001			

## This document was generated on 09/13/2021 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for I/O Connectors category:

Click to view products by Molex manufacturer:

Other Similar products are found below :

 571763P
 58098-0628
 72.250.1628.2
 72.250.2428.2
 74720-0505
 76.350.0729.0
 76871-1403
 FCN-244F080-G/1
 FCN-260A9920
 PCR 

 E36PM
 PCS-XE26MA+
 G38A71314B
 1571250010
 157-22500-3
 MS3471L14-19P L/C
 192991-0703
 172501-4002
 172501-6002
 FCN 

 260C008-A/L0
 FCN-260C024-AL0
 FCN-261Z008
 2000314-1
 200331-1
 PCR-E36FC+
 PCS-E28FS+
 PCS-XE26SLFD+
 PCS 

 XE26SLFDT+
 G730VID08BDC24
 U90B2054081210
 UE86K842720321
 38113800006
 DP3AR020WQ1R200
 Z4.102.0680.0
 500-1040

 500-1052
 500-1054
 ZP-4008-66L
 0709821002
 DX40-20P(55)
 5554841-1
 MS3474W18-8P-LC\*
 U90B3054061110
 U65-E04-4020

 ZPF000000000097891
 747360449
 10099439-003C-TRLF
 10137239-0021LF
 E9320-001-01
 10137239-0011LF
 70289-001LF