

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: [0755940000](#)
Status: **Active**
Overview: [EdgeLine High-Speed Connectors](#)
Description: MicroTCA EdgeLine Connector, 0.75mm Pitch, 0.76µm Select Gold (Au), 170 Circuit

Documents:

Drawing (PDF)	Packaging Specification PK-75594-999-001 (PDF)
Application Specification AS-75594-001-001 (PDF)	Symbol Footprint Data SYM-75594-0000-001 (PDF)
Application Specification AS-75594-100-001 (PDF)	RoHS Certificate of Compliance (PDF)

Agency Certification

CSA	LR19980
UL	E29179

Application tooling part link


Application Tooling Part Link	62100-5200
Application Tooling Part Link	62201-8626

General

Product Family	Edge Card Connectors
Series	75594
Component Type	Edgecard to PCB
Data Rate	5.0-12.0 Gbps
Edge Card Thickness	1.57mm
Electrical Model	Yes
High Power Bay (30.0A or more)	No
Orientation	Vertical
Overview	EdgeLine High-Speed Connectors
Product Name	EdgeLine
Standard Based	MicroTCA
UPC	822350869607

Physical

(p)ower-(s)ignal Configuration	170s - 0p
Circuit Size Range	65-200 Circuits
Circuits (Loaded)	170
Circuits (maximum)	170
Color - Resin	Black
Durability (mating cycles max)	200
Entry Angle	N/A
Flammability	94V-0
Keying to Mating Part	N/A
Material - Metal	Brass
Material - Plating Mating	Gold
Material - Plating Termination	Tin
Material - Resin	High Temperature Thermoplastic
Net Weight	5.997/g
PCB Locator	No
PCB Thickness - Recommended	2.79mm
Packaging Type	Tray
Pitch - Mating Interface	0.75mm
Pitch - Termination Interface	0.75mm
Plating min - Mating	0.762µm
Plating min - Termination	0.762µm
Polarized to Mating Part	Yes
Temperature Range - Operating	-40° to +105°C
Termination Interface: Style	Through Hole - Compliant Pin



Series image - Reference only

EU ELV

Not Relevant

EU RoHS

Compliant

REACH SVHC

Not Contained Per -
D(2021)4569-DC (8
July 2021)

Halogen-Free

Status

Low-Halogen

For more information, please visit [Contact US](#)

China ROHS

ELV

RoHS Phthalates

China RoHS

Green Image

Not Relevant

Not Contained

Search Parts in this Series

[75594 Series](#)

Application Tooling | FAQ

Tooling specifications and manuals are found by selecting the products below. Crimp Height Specifications are then contained in the Application Tooling Specification document.

Global

Description

Product #

Micro TCA Removal Tool	621005200
------------------------	---------------------------

Electrical

Current - Maximum per Contact 1.52A
Voltage - Maximum 250V AC

Solder Process Data

Lead-free Process Capability N/A

Material Info**Reference - Drawing Numbers**

Application Specification AS-75594-001-001, AS-75594-100-001
Electrical Model Document EE-75594-0002-002
Packaging Specification PK-75594-999-001
S-Parameter Model SP-75594-0002-002
Sales Drawing SD-75594-001-001
Symbol/Footprint Data SYM-75594-0000-001

This document was generated on 10/05/2021

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Micro TCA Connectors](#) category:

Click to view products by [Molex](#) manufacturer:

Other Similar products are found below :

[MEB97318-219](#) [MDM-9PSM2-A174](#) [MEB2-64SL83-A159](#) [MDM-25SSK](#) [MDM-15SBSM7-A174](#) [MDM-21PCBRP-A174](#) [MDM-21PCBRM7-A174](#) [MDM-9SBSP-A174](#) [MDM-25PH074M5](#) [MDM-9PL93M7-A174](#) [MEB1-128P](#) [13-000161](#) [13-000141](#) [16111705207000](#) [10058831-110LF](#) [10058831-111LF](#) [10058835-1001LF](#) [10070163-01LF](#) [10084423-103LF](#) [10084423-102LF](#) [10084423-101LF](#) [MDM-25PSB-A174](#) [MDM-9PBSP](#) [MDM-9PL1B](#) [MEB2-64SBR](#) [MDM-21PCBR-A174](#) [13-000201](#) [16041705106000](#) [16310341201000](#) [16320301101000](#) [16320341101000](#) [16340961101000](#) [MDM-21PSB](#) [MDM-21SSB-A174](#) [75594-0000](#) [MTCA-085-02-S-DV-SMT-K-TR](#) [UCC8-010-1-H-S-1-A](#) [UEC5-019-1-H-D-RA-1-A](#) [UEC5-019-1-H-D-RA-2-A](#) [UEC5-019-2-H-D-RA-1](#) [1-1469820-1](#) [1766501-2](#) [1888803-1](#) [4-1469372-2](#) [5-1469373-5](#) [6-1469372-8](#) [6-1469373-8](#)