

This document was generated on 02/20/2020 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: 0757053603				
Status:				
Active			and the second second	
Overview:	GbX I-Trac Backplane Connector System			
Description:		Header Module, 1.85mm by 3.70mm Pitch, Left Guide, Right Open,		
	11 Rows, 6 Columns	s, 132 Circuits, Mating Pin Length 4.70mm		
Documents:				
<u>3D Model</u> <u>3D Model (PDF)</u>		<u>Drawing (PDF)</u> <u>RoHS Certificate of Compliance (PDF)</u>		
,				
Agency Certification			Series image - Reference only	
UL		E29179		
General			EU ELV	
Product Family		Backplane Connectors	Not Relevant	
Series		•		
		75705 Reakalana Midalana Orthogonal	EU RoHS China RoHS	
Application		Backplane, Midplane, Orthogonal	Not Reviewed	
Component Type		PCB Header	REACH SVHC	
Overview		GbX I-Trac Backplane Connector System	Not Reviewed	
Product Name		GbX I-Trac	Halogen-Free	
UPC		822350290371	<u>Status</u>	
			Not Reviewed	
Physical			For more information, please visit Contact US	
Circuits (Loaded)		132		
Circuits (maximum)		132	China ROHS Not Reviewed	
Color - Resin		Black	ELV Not Relevant	
Durability (mating cycles max)		200	RoHS Phthalates Not Reviewed	
First Mate / Last Break		No		
Flammability		94V-0		
Guide to Mating Part		Yes		
Keying to Mating Part		None	Search Parts in this Series	
Material - Metal		High Performance Alloy (HPA)	<u>75705</u> Series	
Material - Plating Mati	na	Gold		
Material - Plating Termination		Tin	Mates With	
Material - Resin		High Temperature Thermoplastic	75710 GbX I-Trac Right Angle Receptacle	
Net Weight		7.530/g	Module	
Number of Columns		6		
Number of Pairs		6, Open Pin Field		
Number of Rows		11	Use With	
Orientation			78232 GbX I-Trac Vertical Power	
		Vertical	Receptacle. <u>75234</u> Backplane Free Standi	
PC Tail Length		2.10mm	Guide Pin	
PCB Locator		No		
PCB Retention	, .	Yes	Application Tooling FAQ	
PCB Thickness - Reco	ommended	1.60mm	Tooling specifications and manuals are	
Packaging Type		Tray	found by selecting the products below.	
Pitch - Mating Interface		1.85mm, 3.70mm	Crimp Height Specifications are then	
Pitch - Termination Interface		1.00mm, 2.70mm	contained in the Application Tooling	
Plating min - Mating		0.762µm	Specification document.	
Plating min - Termination		0.762µm	Global	
Polarized to PCB		No	Description Product #	
Stackable		No		
Surface Mount Compatible (SMC)		Yes	Backplane Insertion <u>621005110</u>	
Temperature Range - Operating		-55° to +80°C	Tool for Signal	
Termination Interface: Style		Through Hole - Compliant Pin	Contact Insertion	
			Press-In Tool for <u>622018602</u>	
Electrical			Vertical Header 11-	
Current - Maximum per Contact		1.0A	Row, 6-Column	

Data Rate 12.0 Gbps Real Signals (per 25mm) 148 Shield Type N/A Shielded No Voltage - Maximum **Solder Process Data**

120V AC (RMS)/DC

N/A

Material Info

Lead-freeProcess Capability

This document was generated on 02/20/2020 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for High Speed/Modular Connectors category:

Click to view products by Molex manufacturer:

Other Similar products are found below :

650827-1 74040-1346 1410191-1 1410337-1 1410368-3 1410964-2 1410326-3 1410367-3 1410971-4 1467833-1 2000877-1 2000878-1 2041314-1 2065387-1 2187307-1 163P 1934290-1 2000875-1 2065917-1 2102736-2 FSR-40 2169868-2 22354-8 437-5040-000 5- 1393565-0 039-0246-000 0761601016 0784461022 10123159-12ELF 030-2415-003/100 PK 030-7380-004 030-2494-001 532939-1 5532901-3 3-1469268-7 74748-102LF 73670-0247 10041743-101LF 10066670-100002LF 1-533915-1 249-4515-000 7-1469373-3 DL2- 2J/S 2000713-8 2000713-7 10124313-101LF 3011-21 757105208 EBTF-4-10-2.0-S-RA-1 430305-001