

This document was generated on 12/28/2021

## PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: 0757840139

Status: Active

Overview: iPass Connector System

**Description:** 0.80mm Pitch, iPass I/O Surface Mount Receptacle, Vertical, Internal Assembly with

Shell, 36 Circuit, 0.38µm Gold (Au), Through Hole Option, Tail Length 2.79mm, Dual

Kev

**Documents:** 

<u>3D Model</u> <u>Application Specification AS-75783-001-001 (PDF)</u>
Drawing (PDF) Packaging Specification PK-75784-001-001 (PDF)

3D Model (PDF) RoHS Certificate of Compliance (PDF)

Product Specification PS-75783-001-001 (PDF)

**Agency Certification** 

CSA LR19980 UL E29179

General

Product Family I/O Connectors

Series <u>75784</u>

Application Wire-to-Board

Comments Positive or passive latching cable available

Component Type Receptacle

Electrical Model Yes

Overview <u>iPass Connector System</u>

Product Name iPass, Mini Multi-Lane, PCI Express

Type N/A

UPC 822350355490

**Physical** 

Circuits (Loaded) 36
Circuits (maximum) 36
Color - Resin Black
Durability (mating cycles max) 50
Flammability 94V-0
Gender Female
Keying to Mating Part Yes
Lock to Mating Part None

Material - Metal Copper-Nickel-Zinc, High Performance Alloy (HPA)

Material - Plating Mating Gold Material - Plating Termination Tin

Material - Resin High Temperature Thermoplastic

Net Weight3.962/gNumber of Rows2OrientationVerticalPC Tail Length2.79mmPCB LocatorYesPCB RetentionYesPCB Thickness - Recommended2.36mm

Packaging Type Embossed Tape on Reel

Panel Mount No
Pitch - Mating Interface 0.80mm
Pitch - Termination Interface 0.80mm
Plating min - Mating 0.381µm
Plating min - Termination 2.540µm
Polarized to Mating Part Yes
Ports 1



# EU ELV

**Not Relevant** 

EU RoHS China RoHS

Compliant

REACH SVHC
Not Contained Per -

D(2021)4569-DC (8

July 2021)

**Halogen-Free** 

Status

Low-Halogen

For more information, please visit Contact US

China ROHS Green Image
ELV Not Relevant
RoHS Phthalates Not Contained

#### **Search Parts in this Series**

75784 Series

Use With

iPass Cable Assemblies,  $\underline{79575}$ ,  $\underline{79576}$ ,

74562, 74563, 79536, 74573,

Surface Mount Compatible (SMC) Yes

Temperature Range - Operating -40° to +80°C

Termination Interface: Style Surface Mount and Through Hole

Waterproof / Dustproof No
Wire Insulation Diameter N/A
Wire Size AWG N/A

**Electrical** 

Current - Maximum per Contact 0.5A
Grounding to Panel None

Voltage - Maximum 30V AC (RMS)/DC

**Solder Process Data** 

Duration at Max. Process Temperature (seconds)

Lead-freeProcess Capability

Max. Cycles at Max. Process Temperature

O01

Process Temperature max. C

260

#### **Material Info**

## **Reference - Drawing Numbers**

Application Specification AS-75783-001-001
Electrical Model Document EE-75577-001-001
Packaging Specification PK-75784-001-001
Product Specification PS-75783-001-001
S-Parameter Model SP-75577-001-001
Sales Drawing SD-75784-001-001

This document was generated on 12/28/2021

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

# **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for High Speed/Modular Connectors category:

Click to view products by Molex manufacturer:

Other Similar products are found below:

650827-1 74040-1346 1410191-1 1410337-1 1410368-3 1410964-2 1410326-3 1410367-3 1410971-4 1467833-1 2000877-1 2000878-1 2041314-1 2065387-1 2187307-1 163P 1934290-1 2000875-1 2065917-1 2102736-2 FSR-40 2169868-2 22354-8 437-5040-000 5-1393565-0 039-0246-000 0761601016 0784461022 10123159-12ELF 030-2415-003/100 PK 030-7380-004 030-2494-001 532939-1 5532901-3 3-1469268-7 74748-102LF 73670-0247 10041743-101LF 10066670-100002LF 1-533915-1 249-4515-000 7-1469373-3 DL2-2J/S 2000713-8 2000713-7 10124313-101LF 3011-21 757105208 EBTF-4-10-2.0-S-RA-1 430305-001