

This document was generated on 08/17/2021

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: 0760445002

Status: Active

Overview: SFP+ and SFP Interconnect Solutions

Description: Small Form-factor Pluggable Plus (SFP+) Stacked 2-by-1 Multi-Port Connector with 2

Inner Lightpipe Ports, EMI Metal Gasket, 40 Circuits, Tin (Sn) Tails

Documents:

3D ModelApplication Specification AS-75310-001-001 (PDF)3D Model (PDF)Application Specification AS-76090-001-001 (PDF)Drawing (PDF)Packaging Specification PK-75462-001-001 (PDF)

Product Specification PS-75310-001-001 (PDF)

RoHS Certificate of Compliance (PDF)

Agency Certification

CSA LR19980 UL E29179

General

Product Family I/O Connectors

Series <u>76044</u>

Application Module-to-Board Component Type Receptacle Yes

Overview SFP+ and SFP Interconnect Solutions

Product Name SFP Plus, SFP+

Type N/A

UPC 883906422936

Physical

Polarized to PCB

Boot Color N/A
Circuits (Loaded) 40
Circuits (maximum) 40
Circuits Detail 40

Color - Resin Black, Clear (Blue Tint)

Durability (mating cycles max) 100
Flammability 94V-0
Gender Female
Keying to Mating Part None
Lock to Mating Part Yes

Material - Metal Brass, Phosphor Bronze

Material - Plating Mating Gold Material - Plating Termination Tin

Material - Resin High Temperature Thermoplastic, Polycarbonate

Yes

Net Weight 27.138/g Number of Rows 2

Right Angle Orientation 2.07mm PC Tail Length **PCB** Locator Yes **PCB** Retention Yes PCB Thickness - Recommended 1.57mm Packaging Type Tray Panel Mount No Pitch - Mating Interface 0.80mm Pitch - Termination Interface 0.80mm Plating min - Mating 0.762µm Plating min - Termination 0.762µm Polarized to Mating Part Yes



Series image - Reference only

EU ELV

Not Relevant

EU RoHS China RoHS Compliant

REACH SVHC
Not Contained Per D(2020)9139-DC (19
Jan 2021)

Halogen-Free Status

Low-Halogen

For more information, please visit Contact US

China ROHS Green Image
ELV Not Relevant
RoHS Phthalates Not Contained

Search Parts in this Series

76044 Series

Use With

759510999 SFP Dust Plug

Application Tooling | FAQ

Tooling specifications and manuals are found by selecting the products below. Crimp Height Specifications are then contained in the Application Tooling Specification document.

Global

Description Product # Extraction Tool, 2 x 1622029930

Medium

Ports 2
Surface Mount Compatible (SMC) No

Temperature Range - Operating -40° to +85°C

Termination Interface: Style Through Hole - Compliant Pin

Waterproof / Dustproof No.

Electrical

Current - Maximum per Contact 0.5A
Grounding to Panel None
Shield Type EMI Gasket

Shielded Yes

Voltage - Maximum 120V AC (RMS)/DC

Solder Process Data

Lead-freeProcess Capability N/A

Material Info

Reference - Drawing Numbers

Application Specification AS-75310-001-001, AS-76090-001-001

Electrical Model Document EE-76090-001-001
Packaging Specification PK-75462-001-001
Product Specification PS-75310-001-001
S-Parameter Model SP-76090-001-001
Sales Drawing SD-76044-001-001

This document was generated on 08/17/2021

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for I/O Connectors category:

Click to view products by Molex manufacturer:

Other Similar products are found below:

571763P 58098-0628 72.250.1628.2 72.250.2428.2 74720-0505 76.350.0729.0 76871-1403 FCN-244F080-G/1 FCN-260A9920 PCR-E36PM PCS-XE26MA+ G38A71314B 1571250010 157-22500-3 MS3471L14-19P L/C 192991-0703 172501-4002 172501-6002 FCN-260C008-A/L0 FCN-260C024-AL0 FCN-261Z008 2000314-1 200331-1 PCR-E36FC+ PCS-E28FS+ PCS-XE26SLFD+ PCS-XE26SLFD+ PCS-XE26SLFD+ G730VID08BDC24 U90B2054081210 UE86K842720321 38113800006 DP3AR020WQ1R200 Z4.102.0680.0 500-1040 500-1052 500-1054 ZP-4008-66L 0709821002 DX40-20P(55) 5554841-1 MS3474W18-8P-LC* U90B3054061110 U65-E04-4020 ZPF0000000000097891 747360449 10099439-003C-TRLF 10137239-0021LF E9320-001-01 10137239-0011LF 70289-001LF