

This document was generated on 01/03/2022

## PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: 0760455002

Status: Active

Overview: SFP+ and SFP Interconnect Solutions

**Description:** Small Form-factor Pluggable Plus (SFP+) Stacked 2-by-2 Multi-Port Connector with 2

Inner Lightpipe Ports, EMI Metal Gasket, 80 Circuits, Tin (Sn) Tails

**Documents:** 

3D ModelApplication Specification AS-75310-001-001 (PDF)Drawing (PDF)Application Specification AS-76090-001-001 (PDF)3D Model (PDF)Packaging Specification PK-75714-001-001 (PDF)

Product Specification PS-75310-001-001 (PDF)

RoHS Certificate of Compliance (PDF)

**Agency Certification** 

CSA LR19980 UL E29179

General

Product Family I/O Connectors

Series <u>76045</u>

Application Module-to-Board Component Type Receptacle Yes

Overview SFP+ and SFP Interconnect Solutions

Product Name SFP Plus Type N/A

UPC 883906494919

**Physical** 

Boot ColorN/ACircuits (Loaded)80Circuits (maximum)80Circuits Detail80

Color - Resin Black, Clear (Blue Tint)

Durability (mating cycles max) 100
Flammability 94V-0
Gender Female
Keying to Mating Part None
Lock to Mating Part Yes

Material - Metal High Performance Alloy (HPA)

Material - Plating Mating Gold Material - Plating Termination Tin

Material - Resin High Temperature Thermoplastic, Polycarbonate

Net Weight 50.387/g Number of Rows 2

Right Angle Orientation 2.07mm PC Tail Length **PCB** Locator Yes **PCB** Retention Yes PCB Thickness - Recommended 1.57mm Packaging Type Tray Panel Mount No Pitch - Mating Interface 0.80mm Pitch - Termination Interface 0.80mm Plating min - Mating 0.762µm Plating min - Termination 0.762µm Polarized to Mating Part Yes Polarized to PCB Yes



Series image - Reference only

**EU ELV** 

**Not Relevant** 

EU RoHS China RoHS

Compliant REACH SVHC Not Contained Per -D(2021)4569-DC (8 July 2021)

**Halogen-Free** 

**Status** 

Low-Halogen

For more information, please visit Contact US

China ROHS Green Image
ELV Not Relevant
RoHS Phthalates Not Contained

**Search Parts in this Series** 

76045 Series

**Use With** 

759510999 SFP Dust Plug

Surface Mount Compatible (SMC) No

Temperature Range - Operating -40° to +85°C

Termination Interface: Style Through Hole - Compliant Pin

Waterproof / Dustproof No.

**Electrical** 

Current - Maximum per Contact 0.5A
Grounding to Panel None
Shield Type EMI Gasket

Shielded Yes

Voltage - Maximum 120V AC (RMS)/DC

**Solder Process Data** 

Lead-freeProcess Capability N/A

**Material Info** 

**Reference - Drawing Numbers** 

Application Specification AS-75310-001-001, AS-76090-001-001

Electrical Model Document EE-76090-001-001
Packaging Specification PK-75714-001-001
Product Specification PS-75310-001-001
S-Parameter Model SP-76090-001-001
Sales Drawing SD-76045-001-001

This document was generated on 01/03/2022

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for I/O Connectors category:

Click to view products by Molex manufacturer:

Other Similar products are found below:

571763P 58098-0628 72.250.1628.2 72.250.2428.2 74720-0505 76.350.0729.0 76871-1403 FCN-244F080-G/1 FCN-260A9920 PCR-E36PM PCS-XE26MA+ G38A71314B 1571250010 157-22500-3 MS3471L14-19P L/C 192991-0703 172501-4002 172501-6002 FCN-260C008-A/L0 FCN-260C024-AL0 FCN-261Z008 2000314-1 200331-1 PCR-E36FC+ PCS-E28FS+ PCS-XE26SLFD+ PCS-XE26SLFD+ PCS-XE26SLFD+ G730VID08BDC24 U90B2054081210 UE86K842720321 38113800006 DP3AR020WQ1R200 Z4.102.0680.0 500-1040 500-1052 500-1054 ZP-4008-66L 0709821002 DX40-20P(55) 5554841-1 MS3474W18-8P-LC\* U90B3054061110 U65-E04-4020 ZPF0000000000097891 747360449 10099439-003C-TRLF 10137239-0021LF E9320-001-01 10137239-0011LF 70289-001LF