

This document was generated on 10/05/2021

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: 0760905001

Status: Active

Overview: SFP+ and SFP Interconnect Solutions

Description: Small Form-factor Pluggable Plus (SFP+) Stacked 2-by-1 Multi-Port Connector with 4

Lightpipe Ports, Elastomeric Gasket, 40 Circuits, Tin (Sn) Tails

Documents:

3D Model Application Specification AS-76090-001-001 (PDF)
Drawing (PDF) Packaging Specification PK-75462-001-001 (PDF)

Product Specification PS-75310-001-001 (PDF)
Application Specification AS-75310-001-001 (PDF)
Application Specification AS-75310-001-001 (PDF)
RoHS Certificate of Compliance (PDF)

Agency Certification

CSA LR19980 UL E29179

General

Product Family I/O Connectors

Series <u>76090</u>

Application Module-to-Board Component Type Receptacle Yes

Overview SFP+ and SFP Interconnect Solutions

Product Name SFP Plus, SFP+

Type N/A

UPC 800756842899

Physical

Boot Color N/A Circuits (Loaded) 40 Circuits (maximum) 40 Circuits Detail 40 Durability (mating cycles max) 100 Flammability 94V-0 Gender **Female** Keying to Mating Part None Lock to Mating Part Yes Material - Plating Mating Gold Net Weight 29.110/g Number of Rows Right Angle Orientation

PC Tail Length 2.07mm **PCB** Locator Yes **PCB** Retention Yes PCB Thickness - Recommended 2.36mm Packaging Type Tray **Panel Mount** No Pitch - Mating Interface 0.80mm Pitch - Termination Interface 0.80mm Polarized to Mating Part Yes Polarized to PCB Yes Ports Surface Mount Compatible (SMC) Nο

Temperature Range - Operating -40° to +85°C

Termination Interface: Style Through Hole - Compliant Pin

Waterproof / Dustproof No



Series image - Reference only

EU ELV

Not Relevant

EU RoHS China RoHS

Compliant REACH SVHC

Not Contained Per - D(2021)4569-DC (8

July 2021)

<u>Halogen-Free</u>

Status

Low-Halogen

For more information, please visit Contact US

China ROHS Green Image
ELV Not Relevant
ROHS Phthalates Not Contained

Search Parts in this Series

76090 Series

Use With

759510999 SFP Dust Plug

Application Tooling | FAQ

Tooling specifications and manuals are found by selecting the products below. Crimp Height Specifications are then contained in the Application Tooling Specification document.

Global

Description Product # Extraction Tool, 2 x 1622029930

Medium

Electrical

Current - Maximum per Contact 0.5A
Grounding to Panel None
Shield Type EMI Gasket

Shielded Yes

Voltage - Maximum 120V AC (RMS)/DC

Solder Process Data

Lead-freeProcess Capability N/A

Material Info

Reference - Drawing Numbers

Application Specification AS-75310-001-001, AS-76090-001-001

 Electrical Model Document
 EE-76090-001-001

 Packaging Specification
 PK-75462-001-001

 Product Specification
 PS-75310-001-001

 S-Parameter Model
 SP-76090-001-001

 Sales Drawing
 SD-76090-001-001

 Test Summary
 TS-76092-999-001

This document was generated on 10/05/2021

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for I/O Connectors category:

Click to view products by Molex manufacturer:

Other Similar products are found below:

571763P 58098-0628 72.250.1628.2 72.250.2428.2 74720-0505 76.350.0729.0 76871-1403 FCN-244F080-G/1 FCN-260A9920 PCR-E36PM PCS-XE26MA+ G38A71314B 1571250010 157-22500-3 MS3471L14-19P L/C 192991-0703 172501-4002 172501-6002 FCN-260C008-A/L0 FCN-260C024-AL0 FCN-261Z008 2000314-1 200331-1 PCR-E36FC+ PCS-E28FS+ PCS-XE26SLFD+ PCS-XE26SLFD+ PCS-XE26SLFD+ G730VID08BDC24 U90B2054081210 UE86K842720321 38113800006 DP3AR020WQ1R200 Z4.102.0680.0 500-1040 500-1052 500-1054 ZP-4008-66L 0709821002 DX40-20P(55) 5554841-1 MS3474W18-8P-LC* U90B3054061110 U65-E04-4020 ZPF0000000000097891 747360449 10099439-003C-TRLF 10137239-0021LF E9320-001-01 10137239-0011LF 70289-001LF