

This document was generated on 03/30/2020

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: 0764551618

Status: Active

Overview: Impact Backplane Connector and Cable Assembly System

Description: Impact 100 Ohm 2 Pair Vertical Backplane Header, Unguided, Left Endwall, 16

Columns, 96 Circuits, Pin Length 5.50mm, Plated Through Hole Dimension 0.39mm,

Lead-Free

Documents:

3D ModelApplication Specification AS-76060-9999-001 (PDF)3D Model (PDF)Packaging Specification PK-70873-761-001 (PDF)Drawing (PDF)Packaging Specification PK-70873-7704-001 (PDF)

Product Specification PS-76060-999-001 (PDF)
Application Specification AS-76060-990-001 (PDF)
Application Specification AS-76060-990-001 (PDF)
Rohs Certificate of Compliance (PDF)

Agency Certification

UL E29179

General

Product Family Backplane Connectors

Series 76455
Application Conventional
Application Tooling Documents TM-622018799
Component Type PCB Header

Overview <u>Impact Backplane Connector and Cable Assembly</u>

System Impact

No

UPC 884982069145

Physical

Product Name

Circuits (Loaded) 96
Circuits (maximum) 96
Color - Resin Black
Durability (mating cycles max) 200
First Mate / Last Break No
Flammability 94V-0
Guide to Mating Part No
Keying to Mating Part None

Material - Metal High Performance Alloy (HPA)

Material - Plating Mating Gold Material - Plating Termination Tin

Material - Resin High Temperature Thermoplastic

Net Weight 2.886/a **Number of Columns** 16 Number of Pairs 2 Number of Rows 6 Orientation Vertical PC Tail Length 1.40mm **PCB** Locator No **PCB** Retention None PCB Thickness - Recommended 1.00mm Packaging Type Trav

Pitch - Mating Interface

Pitch - Termination Interface

Plating min - Mating

Polarized to PCB

Stackable

1.90mm

0.762µm

No

Surface Mount Compatible (SMC)



Series image - Reference only

EU ELV

Not Relevant

EU RoHS China RoHS

CompliantREACH SVHC

Not Contained Per -ECHA_01_2020 (16 January 2020

Halogen-Free

<u>Status</u>

Low-Halogen

For more information, please visit Contact US

China ROHS Green Image
ELV Not Relevant
ROHS Phthalates Not Contained

Search Parts in this Series

76455 Series

Mates With

76460 Impact 100 Ohm Daughtercard

Use With

75234 Backplane Free Standing Guide Pin

Application Tooling | FAQ

Tooling specifications and manuals are found by selecting the products below. Crimp Height Specifications are then contained in the Application Tooling Specification document.

Global

Description Product # Backplane Insertion 621005800

Tool for Signal Contact

Backplane Header 621009610

Removal Tool for GbX U-Series, GbX I-Trac, Impact, or Z-PACK TinMan Temperature Range - Operating -55° to +85°C

Termination Interface: Style Through Hole - Compliant Pin

Electrical

 $\begin{array}{ccc} \text{Current - Maximum per Contact} & 0.75\text{A} \\ \text{Data Rate} & 25.0 \text{ Gbps} \\ \text{Impedance} & 100\Omega \\ \text{Shield Type} & \text{N/A} \\ \text{Shielded} & \text{No} \\ \end{array}$

Voltage - Maximum 30V AC (RMS)/DC

Solder Process Data

Lead-freeProcess Capability N/A

Material Info

Reference - Drawing Numbers

Application Specification AS-76060-990-001, AS-76060-9999-001 Packaging Specification PK-70873-761-001, PK-70873-7704-001

 Product Specification
 PS-76060-999-001

 Sales Drawing
 SD-76455-001-001

 Symbol/Footprint Data
 SYM-76455-1618

 Test Summary
 TS-76460-0001-001

Press-In Tool for 622018694
Backplane Signal
Module, 2-Pair by

16-Column

This document was generated on 03/30/2020

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for DIN 41612 Connectors category:

Click to view products by Molex manufacturer:

Other Similar products are found below:

09231126901 PCN10F-24P-2.54DS(72) 004.767 02221602702 024069 602427301412000 013275 691327-1 74670-0732 74680-0340
75880-0015 76453-0014 86093159ALF 923454 QLC260R 120X10099X 120X10019X 120X10089X 120X10129X 121A10039X
121A10309X 122A10019X 122A10029X 122A10249X 122A10669X 122A11089X 122A13089X 121B10409X 122A10089X
122A10129X 122A10349X 122A13359X 1377391-4 DIN-048CPC-SR1-MH 1393583-2 1393726-7 140X10059X 140X10129X 143-1913000 143-1908-000 1484472-1 173052 2110070-1 2110070-2 CBC20T00-008FDS5-0-1-002VR 983-0SE12-12P6 17041102202 1726995036 173051 20 8457096 010 025