



General Information

Kit Part Number: <u>76650-0249</u>

Description: Molex Quixon™ LIF (Low Insertion Forces) Quick-Disconnect and Male PCB Tab Terminal Kit

Application: Automotive, Consumer Products, HVAC Equipment, Industrial Equipment

Connector Family: Solderless Terminals

Solution: Blind-Mate Connectors, Maintenance, Repair and Operation Connectors

Connector Type: Solderless Terminals

Number of Pieces: 35
RoHS: Yes

Specifications

Circuit Size(s): None

Current Rating: 7A (22-18 AWG), 15A (16-14 AWG), 24A (12-10 AWG)

Flammability Rating: UL94V-2

Insulation: Nylon Fully Insulated

Mounting Style: Non-Mounted

Orientation: Solderless Terminals

Product/Type: .250" Tab Quick Disconnects

Stud/Tab Size: .250" (6.35mm)

Tool Included: No Voltage Rating: 300V

Wire Gauge (AWG): 12-10, 16-14, 22-18

Product Highlights

Quixon™ quick-disconnect terminals expand Molex's existing AviKrimp™, InsulKrimp™ and Krimptite™ product lines. These quick-disconnect terminals offer lower insertion force and greater blind-mate capability versus standard AviKrimp, InsulKrimp and Krimptite terminals. Quixon quick-disconnect terminals are available in loose piece or on continuous plastic strip and Mylar tape for semi- or fully- automatic termination. Quixon quick-disconnect terminals meet UL requirements when used with Molex recommended tooling; however, terminals may be crimped with a variety of industry-standard tooling. Quixon quick-disconnect terminals mate to industry-standard tabs offered by Molex.

Features and Benefits

- Side-relief cut design makes blind mating easy by accommodating a slight angle during mating.
- Flexing beam with standard dimple for Low Insertion Force, to mate easily with UL-compliant male tabs while maintaining a high retention force.
- Flared-barrel entry for easy wire insertion, Captures all the wire strands and funnels them into the crimp barrel.
- Standard on AviKrimp™ terminals with a Brass sleeve on the barrel, Provides strain relief and meets the double-crimp VDE, IEC and DIN requirement with a metal ferrule that crimps onto the wire insulation.
- Un-insulated and partially insulated versions are also available, Provides customers a choice for their applications and safety requirements.
- Terminals mate to industry-standard tabs, 6.35 by 0.81mm (.250 by .032"), Enables universal use in numerous applications.

Applications

- Industrial Markets: PCB Connections, Switches, Terminal Blocks
- Automotive Aftermarket: Gauges, Modules
- Consumer Industry White Goods, Brown Goods
- HVAC: Relays, Capacitors, Contactors









Bill of Materials

Part No.	Qty In Kit	Description	Datasheet	P/N Details	Search Distributors Inventory
<u>19277-0002</u>	10	Quixon™ .250" x .032" Female Fully Insulated Nylon Qui	<u>Datasheet</u>	<u>Details</u>	<u>Search</u>
<u>19277-0005</u>	10	Quixon™ .250" x .032" Female Fully Insulated Nylon Qui	<u>Datasheet</u>	<u>Details</u>	Search
<u>19277-0008</u>	10	Quixon™ .250" x .032" Female Fully Insulated Nylon Qui	<u>Datasheet</u>	<u>Details</u>	Search
<u>19705-4201</u>	5	PCB Tab Quick Disconnect, Male, Box, Tab 6.35 x 0.81mm H =	<u>Datasheet</u>	<u>Details</u>	Search

Recommended Tool

Part No.	Included in Kit
64001-0200	No
<u>64001-0800</u>	No
<u>64001-1100</u>	No



















X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for molex manufacturer:

Other Similar products are found below:

60506-C-50 73108 72903 1062837003 0533241060 68301-1017 71506-C 880504 387790039 53254-0710 85071-0017 387204903

783472003 514412093 0026482195 0191310031 503308-4410 0008650814 791099208 0039000218 89762-1403 89762-1542 89762-1582

0011404526 00136 0022173102 0026615060 CR4006A30M003 0039532085 58098-0628 0003092041 0008520123 0011030025

0011184017 0022162060 0022552102 01312 M15730061 61432 6150300002 CS63W64 CS8264N CS8365N CS8369 62201-8780 62500
1774 M37730026 63103-50 63443-2215 63443-3160