

This document was generated on 07/26/2018

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: 0082226107

Status: Active

Description: 2.54mm Pitch Round Conductor Flat Cable - 22 AWG (7 x 30) Stranded, Tinned, 7

Circuits, Reel 30.48m Length

Documents:

<u>Drawing (PDF)</u> <u>RoHS Certificate of Compliance (PDF)</u>

General

Product Family
Series
7560
Crimp Quality Equipment
Geographic Area
Asia
Product Name
Ribbon
UPC
800754370608

Physical

Cable Length30.48mCircuits (Loaded)7InsulationPVCNet Weight1368.760/gPackaging TypeReelPitch - Termination Interface2.54mm

Temperature Range - Operating -20°C to +105°C

Wire Size AWG 22

Wire/Cable Type (7x30) Stranded, Tinned

Electrical


Current - Maximum per Contact N/A Voltage - Maximum 300V

Material Info

Engineering Number 7560-07-100B

Reference - Drawing Numbers

Sales Drawing SD-7560-001



EU ELV

Not Relevant

EU RoHS China RoHS

Compliant REACH SVHC Not Contained Per -ED/108/2014 (17 Dec

2014)

<u>Halogen-Free</u>

Status

Not Low-Halogen

Need more information on product environmental compliance?

Email <u>productcompliance@molex.com</u>
Please visit the <u>Contact Us</u> section for any non-product compliance questions.

China ROHS Green Image
ELV Not Relevant
ROHS Phthalates Not Reviewed

Search Parts in this Series

<u>7560</u> Series

Use With

70400 C-Grid SL IDT Connector Assembly. 70475 SL IDT Connector Assembly. 7720 KK IDT Double Cantilever Contact

This document was generated on 07/26/2018

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Flat Cables category:

Click to view products by Molex manufacturer:

Other Similar products are found below:

F28-A25G F28-A34G F28-A36G FST-23A-15 AYT1510-US 171-37G C336514-500 902220736002000 902220736006000 28100-0614

9L28010-008-H300 9L28014-008-H300 F28-A24G F28-A60G 25WDY00002 28100-0571 28100-0602 28100-0650 28100-0664 336506
100SF 336512-300 336537-CUT-LENGTH 3447/10-100 362514100MSF 40WDY00005 AYT51163 336506-300 C3302/16 C374910

3625/24100M 3749/10-100 375630 3-971111-6 1-1437356-3 812504 20WDY00001 5-1437214-8 3355/15 40WBY00007 3609/12

5111196336 607.5689.087 607.5689.091 3801/04 8124/04 3801/12 3625/22100MSF 902220736005000 902220736004000 C3811/10-100