

This document was generated on 07/25/2017

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: 0082265506

Status: Active

Description: 2.50mm Pitch Round Conductor Flat Cable - 26 AWG (7 x 34) Stranded, Topcoat, 6

Circuits, Reel 30.48m Length

Documents:

Drawing (PDF) RoHS Certificate of Compliance (PDF)

General

Product Family
Series
40160
Crimp Quality Equipment
Geographic Area
Asia
Product Name
UPC
Cable
40160
Yes
Asia
Ribbon
800755977608

UPC 800/559/760

Physical

Cable Length30.48mCircuits (Loaded)6InsulationPVCPackaging TypeReelPitch - Termination Interface2.50mm

Temperature Range - Operating -20°C to +105°C

Wire Size AWG 26

Wire/Cable Type (7x34) Stranded, Topcoat

Electrical


Current - Maximum per Contact N/A Voltage - Maximum 300V

Material Info

Engineering Number 40160-06-100B

Reference - Drawing Numbers

Sales Drawing SD-40160-001



EU ELV

Not Relevant

EU RoHS China RoHS

Compliant REACH SVHC Not Contained Per -ED/01/2017 (12 January 2017)

<u>Halogen-Free</u>

Status

Not Low-Halogen

Need more information on product environmental compliance?

Email <u>productcompliance@molex.com</u>
Please visit the <u>Contact Us</u> section for any non-product compliance questions.

China ROHS Green Image
ELV Not Relevant
RoHS Phthalates Not Contained

Search Parts in this Series

40160 Series

Use With

42219 SPOX™ IDT Receptacle

This document was generated on 07/25/2017

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Flat Cables category:

Click to view products by Molex manufacturer:

Other Similar products are found below:

F28-A25G F28-A34G F28-A36G FST-23A-15 AYT1510-US 171-37G C336514-500 902220736002000 902220736006000 28100-0614

9L28010-008-H300 9L28014-008-H300 F28-A24G F28-A60G 25WDY00002 28100-0571 28100-0602 28100-0650 28100-0664 336506
100SF 336512-300 336537-CUT-LENGTH 3447/10-100 362514100MSF 40WDY00005 AYT51163 336506-300 C3302/16 C374910

3625/24100M 3749/10-100 375630 3-971111-6 1-1437356-3 812504 20WDY00001 5-1437214-8 3355/15 40WBY00007 3609/12

5111196336 607.5689.087 607.5689.091 3801/04 8124/04 3801/12 3625/22100MSF 902220736005000 902220736004000 C3811/10-100