

This document was generated on 07/25/2017 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

	6820 tch Round Conductor Flat Cable - 26 AWG (7 x 34) Stranded Tinned, 20 eel 30.48m Length	
Documents: Drawing (PDF)	RoHS Certificate of Compliance (PDF)	
General Product Family Series Crimp Quality Equipment	Cable <u>8863</u> Yes	Series image - Reference only
Geographic Area	Asia	<u>EU ELV</u>
Product Name UPC	Ribbon 800754377546	Not Relevant EU RoHS China RoHS
Physical		Compliant
Cable Length	30.48m	REACH SVHC
Circuits (Loaded)	20	Not Contained Per -
Insulation	PVC	ED/108/2014 (17 Dec
Net Weight	1901.520/g	2014)
Packaging Type	Reel	Halogen-Free
Pitch - Termination Interface	1.27mm	<u>Status</u>
Temperature Range - Operating	-20°C to +105°C	Not Low-Halogen
Wire Size AWG	26	Need more information on product
Wire/Cable Type	(7x34) Stranded, Tinned	environmental compliance?
Electrical		Email productcompliance@molex.com
Current - Maximum per Contact	N/A	Please visit the <u>Contact Us</u> section for any
Voltage - Maximum	300V	non-product compliance questions.
Material Info		China ROHS Green Image
Engineering Number	8863-20-100B	ELV Not Relevant RoHS Phthalates Not Reviewed
Reference - Drawing Numbers		
Sales Drawing	SD-8863-001	
		Search Parts in this Series 8863 Series

Use With <u>70121</u> MX-50[™] Slimline Ribbon Cable. <u>90584</u> Picoflex® PF-50 IDT Receptacle

This document was generated on 07/25/2017 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Flat Cables category:

Click to view products by Molex manufacturer:

Other Similar products are found below :

 F28-A25G
 F28-A34G
 F28-A36G
 FST-23A-15
 AYT1510-US
 171-37G
 C336514-500
 902220736002000
 902220736006000
 28100-0614

 9L28010-008-H300
 9L28014-008-H300
 F28-A24G
 F28-A60G
 25WDY00002
 28100-0571
 28100-0602
 28100-0664
 336506

 100SF
 336512-300
 336537-CUT-LENGTH
 3447/10-100
 362514100MSF
 40WDY00005
 AYT51163
 336506-300
 C3302/16
 C374910

 3625/24100M
 3749/10-100
 375630
 3-971111-6
 1-1437356-3
 812504
 20WDY00001
 5-1437214-8
 3355/15
 40WBY0007
 3609/12

 5111196336
 607.5689.087
 607.5689.091
 3801/04
 8124/04
 3801/12
 3625/22100MSF
 902220736005000
 902220736004000
 C3811/10-100