

This document was generated on 05/29/2017

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: 0082285530

Status: Active

Description: 1.27mm Pitch Round Conductor Flat Cable - 28 AWG (7 x 36) Stranded Topcoat, 30

Circuits, Reel 30.48m Length

Documents:

Drawing (PDF) RoHS Certificate of Compliance (PDF)

General

Product Family
Series
Crimp Quality Equipment
Geographic Area
Product Name
UPC
Cable
40158
Yes
Asia
Ribbon
Ribbon
800754626798

Physical

Cable Length30.48mCircuits (Loaded)30InsulationPVCPackaging TypeReelPitch - Termination Interface1.27mm

Temperature Range - Operating -20°C to +105°C

Wire Size AWG 28

Wire/Cable Type (7x36) Stranded, Topcoat

Electrical


Current - Maximum per Contact N/A Voltage - Maximum 300V

Material Info

Engineering Number 40158-30-100B

Reference - Drawing Numbers

Sales Drawing SD-40158-001



EU ELV

Not Reviewed

EU RoHS China RoHS

Not Reviewed REACH SVHC Not Reviewed Halogen-Free Status

Not Reviewed

Need more information on product environmental compliance?

Email <u>productcompliance@molex.com</u>
Please visit the <u>Contact Us</u> section for any non-product compliance questions.

China ROHS Not Reviewed ELV Not Reviewed RoHS Phthalates Not Reviewed

Search Parts in this Series

40158 Series

Use With

70121 MX-50™ Slimline Ribbon Cable. 90584 Picoflex® PF-50 IDT Receptacle

This document was generated on 05/29/2017

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Flat Cables category:

Click to view products by Molex manufacturer:

Other Similar products are found below:

F28-A25G F28-A34G F28-A36G FST-23A-15 AYT1510-US 171-37G C336514-500 902220736002000 902220736006000 28100-0614

9L28010-008-H300 9L28014-008-H300 F28-A24G F28-A60G 25WDY00002 28100-0571 28100-0602 28100-0650 28100-0664 336506
100SF 336512-300 336537-CUT-LENGTH 3447/10-100 362514100MSF 40WDY00005 AYT51163 336506-300 C3302/16 C374910

3749/10-100 375630 3-971111-6 1-1437356-3 812504 20WDY00001 5-1437214-8 3355/15 40WBY00007 3609/12 5111196336

607.5689.087 607.5689.091 3801/04 8124/04 3801/12 3625/22100MSF 902220736005000 902220736004000 C3811/10-100 3625/22-30M