

This document was generated on 10/04/2021 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:	0836149012				
Status:	Active				
		Llich Donaity Connectors	10	And the second s	
Overview: Description:		<u>) High-Density Connectors</u>	L		
Description:	1.27mm Pitch Com	itch Commercial Micro D, PCB Mount, Right-Angle Plug, 25 Circuits		2 3 8 B	
Decumenter					
Documents:		Product Specification PS-83421-001-001 (PDF)		States ()	
<u>3D Model (PDF)</u> 3D Model		Product Specification PS-63421-001-001 (PDF) Packaging Specification PK-83098-636-001 (PDF)			
Drawing (PDF)		RoHS Certificate of Compliance (PDF)			
		<u>Kons Certificate of Compliance (FDF)</u>			
Conorol			Series ima	ge - Reference only	
General Product Family		I/O Connectors		ge Reference entry	
Series		83614	EU ELV		
Application		Wire-to-Board	Not Relevant		
Comments		Pin Contact	NOT Relevant		
Component Type		Plug	EU RoHS	China RoHS	
Overview		Commercial Micro-D High-Density Connectors	Compliant	<u></u>	
Product Name		Commercial Micro-D High-Density Connectors	REACH SVHC		
		N/A	Not Contained Per -		
Type			D(2021)4569-DC		
UPC		800756013633	July 2021)	(8	
Physical			Halogen-Free		
Boot Color		N/A	Status		
Circuits (Loaded)		25	Low-Halogen		
Circuits (maximum)		25		ion plagos visit Contact US	
Durability (mating cycles max)		500	For more mormat	For more information, please visit <u>Contact US</u>	
Gender		Plug	China ROHS	Green Image	
Lock to Mating Part		Yes	ELV	Not Relevant	
Material - Plating Mating		Gold	RoHS Phthalates	Not Contained	
Net Weight		6.349/g			
Number of Rows		2			
Orientation		Z Right Angle			
PC Tail Length		2.79mm	Search Parts in this Series		
PCB Locator		Yes	<u>83614</u> Series		
PCB Retention		Yes			
PCB Retention PCB Thickness - Recommended		1.52mm	Mates With		
		Tube	83424 Cable Assembly		
Packaging Type Panel Mount		Yes	j L	-	
		1.27mm			
Pitch - Mating Interface Pitch - Termination Interface		1.27mm			
Plating min - Mating Polarized to Mating Part		0.381µm Xos			
Polarized to PCB		Yes			
Polarized to PCB		Yes 1			
		•			
Surface Mount Compatible (SMC) Temperature Range - Operating		No 40° to 125° C			
		-40° to +125°C			
Termination Interface: Style		Through Hole			
Waterproof / Dustproof		No			
Wire Size AWG		N/A			
Electrical					
Current - Maximum	per Contact	1.0A			
Shield Type		Full Shield			
Shieldod		Vee			

Yes

350V AC

Voltage - Maximum

Shielded

Reference - Drawing Numbers Packaging Specification Product Specification Sales Drawing

PK-83098-636-001 PS-83421-001-001 SD-83614-001-001

This document was generated on 10/04/2021 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for D-Sub Micro-D Connectors category:

Click to view products by Molex manufacturer:

Other Similar products are found below :

 89076GBEPR
 65-1920-15
 M83513/03-G09N
 M83513/03-G12N
 M83513/04-E15N
 M83513/04-G04C
 664020C06F060
 6R2004A30F015

 6R4006A28A120
 703006A13F060
 704002A03F200
 705001A13F120
 71-147714-19P
 7-1532020-5
 748567-1-P
 MDB1-9SH001
 MDM

 100PH003L
 MDM-15PBS-L58
 MDM-15PCBRM7T
 MDM-15PH001M7-A174
 MDM-15PH003B-A174
 MDM-15SH003A
 MDM

 15SH004B
 MDM-15SH006A-A174
 MDM-15SH048B
 MDM-25PH003B-A174
 MDM-25SH003F
 MDM-25SH003K
 MDM-31PH003L

 MDM-37PH006L-A174
 MDM-37SH003K
 MDM51PH016FA174
 MDM-51PSF
 MDM-9PH003M7
 MDM-9PH003P-A174
 MDM-9SH001P

 MDM-9SH006B
 790-027SH-10P4MEP
 790-041PJ-25P2MPA
 790-043PJ-7P7MPB
 791-004SH-66MSA
 7R3A00A19A1201

 7R5006A19A120
 803000C02M020
 803001B02M040
 803001D01M040
 8030N1A09M020
 804001B03M100
 804006B03M100

 804006C02M030
 603001B02M040
 803001D01M040
 8030N1A09M020
 804001B03M100
 804006B03M100